

GENESYS

This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Genesys Interaction Recording Solution Guide

Installing

Installing

To install Interaction Recording Web Services (RWS), first you need to set up the following two application objects it uses in the Genesys configuration environment:

- Cluster Application
- · Node Application

If RWS is being deployed along with Web Services (GWS), then GWS must be installed first, and the Cluster Application created during the GWS installation is shared between both components.

Interaction Recording Web Services

Interaction Recording Web Services (RWS)

Creating the Application Templates

Using Genesys Administrator Extension, complete the steps below to create application templates to use for your IRWS Cluster and IRWS Node applications.

Start

- To create the Genesys Generic Server template, navigate to Configuration > Environment > Application Templates.
- 2. Select **New...** and configure the properties of the template as shown below:
 - Name: IRWS Cluster Template
 - Type: Genesys Generic Server
 - Version: 8.5State: Enabled
- 3. Click Save & Close.
- 4. To create the Genesys Generic Client template, select **New...** again and configure the properties of the template as shown below:
 - Name: IRWS_Node_Template
 - · Type: Genesys Generic Client

Version: 8.5State: Enabled

5. Click Save & Close.

End

Creating the IRWS Cluster Application

Start

- 1. Navigate to Configuration > Environment > Applications and click New....
- 2. In the General section, configure the properties of the application as shown below:
 - Name: IRWS_Cluster
 - Template: IRWS_Cluster_Template (this is the template you made in Creating the Application Templates)
 - · State: Enabled
 - Working Directory: .
 - · Command Line: .
 - Command Line Arguments: .

Important

You need to add a "." to the Working Directory, Command Line, and Command Line Arguments fields, as shown above. These values are mandatory for all applications and must be entered to save the application object. Interaction Recording Web Services does not use these values, so the "." is used as a placeholder.

- 3. Choose a Host object. See Create Host in the Management Framework Deployment Guide for more information about Host objects.
- 4. Add the following connections:
 - Configuration Server (you can add CS Proxy using the [csproxy].proxy-writable=true option.)
 - Interaction Server (if supporting multimedia)
 - T-Server/SIP Server (when supporting voice)

Important

When working with dual data centers, RWS requires a connection to each Interaction Server Application Cluster (in both data centers), in order to provide support for disaster recovery with an Interaction Server between the data centers. Use the following application parameters to provide the connection between RWS and each Interaction Server Application Cluster:

siteName=DC1;clusterType=eservices #For DC1 Interaction Server

Application cluster

- siteName=DC2;clusterType=eservices #For DC2 Interaction Server Application cluster
- 5. In the **Tenants** section, select a Tenant:
 - 1. Click Add.
 - 2. Choose the Environment tenant (or any other tenant that has a connection to your Configuration Server).
 - 3. Click OK.

Important

This step is for adding a single tenant only. For information about multi-tenant deployments, see Deploying Genesys Interaction Recording in a Multi-Tenant Deployment.

- 6. Add a default Listening Port:
 - 1. Click Add.
 - 2. Enter the application's Port. For instance 7000.
 - 3. Click OK.

End

Creating the RWS Node Application

Start

- 1. Navigate to Configuration > Environment > Applications and click New.....
- 2. In the **General** section, configure the properties of the application as shown below:
 - Name: IRWS_Node
 - Template: IRWS_Node_Template (this is the template you made in Creating the Application Templates)
 - State: Enabled
- 3. Add the following connections:
 - Cluster application that was configured in the previous procedure.
- 4. Click Save & Close.

End

Interaction Recording Web Services with Web Services

Interaction Recording Web Services (RWS) with GWS

Creating the Application Template

Using Genesys Administrator Extension, complete the steps below to create an application template to use for your IRWS_Node applications.

Start

- To create the Genesys Generic Client template, navigate to Configuration > Environment >
 Application Templates.
- 2. Select **New...** and configure the properties of the template as shown below:

Name: IRWS_Node_TemplateType: Genesys Generic Client

Version: 8.5State: Fnabled

3. Click Save & Close.

End

Creating the RWS Node Application

Start

- 1. Navigate to Configuration > Environment > Applications and click New.....
- 2. In the **General** section, configure the properties of the application as shown below:

• Name: IRWS Node

• Template: IRWS Node Template (this is the template you made in Creating the Application Template)

• State: Enabled

- 3. Add the following connections:
 - Cluster application that was configured as part of the GWS installation. For additional information, refer to the Creating the Web Services (WS) Cluster Application section.
- 4. Click Save & Close.

End

Next Step

• Deploy the web application