

# **GENESYS**

This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

# **API** Reference

Delete Record From Service Extension

# Delete Record From Service Extension

| <sup>a</sup> b <sup>c</sup> | PUT /services/\${service_id}/extensions/\${ext_name}/delete/by/unique |
|-----------------------------|---|
|                             | Available since: 8.0.200.00   |

# Contents

- 1 Delete Record From Service Extension
  - 1.1 Description
  - 1.2 Operation
  - 1.3 Response
  - 1.4 Example

API Reference 2

# Description

Deletes a single record in a multi-valued extension. In the operation's body, you must specify the unique attributes that identify the record in the given extension. See Unique Attributes for further information.

### Operation

#### **Prerequisites:** The extension record exists.

| ID  | CV.WS.SRV.22   |           |  |  |
|---|--|-----------|--|--|
| Method  | PUT  |           |  |  |
| URL   | /services/\${service_id}/extensions/\${ext_name}/delete/by/unique  |           |  |  |
| Parameter   | Туре   | Mandatory | Description  |  |
| URI Parameters  |  |           |  |  |
| \${service_id}  | long   | yes       | The service ID.  |  |
| \${ext_name}  | string   | yes       | The name of the Service Extension to modify.                                       |  |
| Body <ref>Unique attributes of the Service Extension.</ref> |  |           |  |  |
| <attribute n=""></attribute>                                | <ul> <li>string</li> <li>integer</li> <li>long</li> <li>double</li> <li>date</li> <li>datetime</li> <li>currency</li> <li>boolean</li> </ul> | yes       | Unique attributes<br>(names and values)<br>which identify the<br>record to delete. |  |

<references />

## Response

The Context Management Service API answers with HTTP codes for every request. The following table shows the correct response for a successful request. See HTTP Response Codes and Errors for further details on the possible codes that this operation can return.

API Reference 3

#### Response

| HTTP code    | 204        |
|--------------|------------|
| HTTP message | No Content |

# Example

**Operation** The following operation deletes the relatedOffers record identified by the attribute "offer\_name" of service 8389.

```
PUT /services/8389/extensions/relatedOffers/by/unique
{
    "offer_name":"3 times payment GOLD"
}
```

#### Result

204 No Content

API Reference 4