

GENESYS

This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

API Reference

Update Service Extension

Update Service Extension



PUT

/services/\${service_id}/extensions/\${ext_name}

Contents

- 1 Update Service Extension
 - 1.1 Description
 - 1.2 Operation
 - 1.3 Response
 - 1.4 Example

API Reference 2

Description

This operation replaces the extension value with a new extension value. The former value of the extension is lost. This operation supports the update of multi-valued extensions.

Operation

Updates a service's extension value

ID	CV.WS.SRV.4		
Method	PUT		
URL	/services/ \${service_id} /extensions/ \${ext_name}		
Name	Туре	Mandatory	Description
URI Parameters			
\${service_id}	integer	yes	The ID of the service.
\${ext_name}	string	yes	The name of the extension
Body			
<attribute n=""> or <attribute n="">[]</attribute></attribute>	value	yes	Attributes for single-valued extensions, or array of attributes for multi-valued extensions (previously defined through the Create Service Extension Schema operation).

Response

The Context Management Service API answers with HTTP codes for every request. The following table shows the correct response for a successful request. See HTTP Response Codes and Errors for further details on the possible codes that this operation can return.

Response

HTTP code	200
HTTP message	OK

API Reference 3

Example

Operation

The following operation updates the single-valued extension "score".

```
PUT /services/8389/extensions/score
{
    "score": 85,
    "agentID": 2025
}
```

Operation

The following operation updates the multi-valued extension "relatedOffers".

Result

200 OK

API Reference 4