




This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

## API Reference

Delete Customer Profile

# Delete Customer Profile

	<b>DELETE</b> /profiles/\${customer_id}
	Available since: 8.1.200.xx

## Contents

- [1 Delete Customer Profile](#)
  - [1.1 Description](#)
  - [1.2 Operation](#)
  - [1.3 Response](#)
  - [1.4 Example](#)

## Description

Deletes a customer profile and all its extension records and identifications keys records. All associated services are also deleted. If those services records are used by states or tasks, they will also be deleted.

## Operation

ID	CV.WS.PROF.8		
Method	DELETE		
URI	/profiles/\${customer_id}		
Parameter	Type	Mandatory	Description
\${customer_id}	string	yes	The unique ID of the given customer that is specified in the URI.

<references />

## Response

The Context Management Service API answers with HTTP codes for every request. The following tables show the correct response for a successful request, and the response if the customer cannot be deleted. See [HTTP Response Codes and Errors](#) for further details on the possible codes that this operation can return.

### Response

HTTP code	200
HTTP message	Success

### Response

HTTP code	404
HTTP message	Not Found

## Example

**Operation** The following operation deletes a particular customer:

```
DELETE /profiles/0004Va58A92T0018
```

---

## Delete Customer Profile

---

### Result

200 Success