

# **GENESYS**

This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

## **API** Reference

Update Record In Profile Extension

# Update Record In Profile Extension

PUT /profiles/\${customer_id}/extensions/\${ext_name}/by/unique
Available since: 8.0.200.00

#### Contents

- 1 Update Record In Profile Extension
  - 1.1 Description
  - 1.2 Operation
  - 1.3 Response
  - 1.4 Example

API Reference 2

### Description

Updates the content of a single record in a multi-valued extension. The attributes which are part of the 'unique' list specified at the Extension Schema creation are passed in the body and used to find the correct record to update. This update cannot change the values of the attributes which are part of the 'unique' list of the Extension Schema; 'unique' attributes are used as identifiers for the given record. Workaround: If you wish to update a value for an attribute stamped as unique, you must delete the concerned record, then recreate this record with its correct values.

#### Operation

#### **Prerequisites:** The extension record exists.

ID	CV.WS.PROF.6			
Method	PUT			
URL	/profiles/\${customer_id}/extensions/\${ext_name}/by/unique			
Parameter	Туре	Mandatory	Description	
URI Parameters				
\${customer_id}	string	yes	The unique ID of the given customer. Limited to 16 characters.	
\${ext_name}	string	yes	The name of the Profile Extension to update.	
Body <ref>Record for the Profile Extension.</ref>				
<attribute n=""></attribute>	<ul> <li>string</li> <li>integer</li> <li>long</li> <li>double</li> <li>date</li> <li>datetime</li> <li>currency</li> <li>boolean</li> </ul>	yes	Individual attributes defined in the Profile Extension Schema. <attribute n=""> corresponds to the attribute name defined in the schema.  • If the attribute is unique, its value is used to select the record to update. It is not updated.  • If the attribute is not unique, its value is updated.</attribute>	

<references />

API Reference 3

#### Response

The Context Management Service API answers with HTTP codes for every request. The following table shows the correct response for a successful request. See HTTP Response Codes and Errors for further details on the possible codes that this operation can return.

#### Response

HTTP code	204
HTTP message	No Content

#### Example

**Operation** The following operation updates the Phone record associated with the unique "PhoneNumber": "3145926535".

```
PUT /profiles/0000Sb5U97XE000Y/extensions/Phone/by/unique
{
    "PhoneType":0,
    "prefix":"+33",
    "PhoneNumber":"3145926535",
    "description":"family phone",
    "start_availabilty":"2009-12-18T18:30:00.000Z",
    "end_availabilty":"2009-12-18T21:40:00.000Z"
}
```

#### Result

204 No Content with empty body

API Reference 4