

# **GENESYS**

This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

## **API** Reference

**Query Interactions** 

## Query Interactions

## **Important**

Prerequisites: You need to enable profiles in UCS.

- GET /customers/\${customer\_id}/interactions
- **GET** /interactions/\${interaction\_id}

### Contents

- 1 Query Interactions
  - 1.1 Description
  - 1.2 Operation
  - 1.3 Response
  - 1.4 Example

## Description

Retrieves multimedia interactions and their data.

## Operation

#### **Queries Multimedia Interactions**

ID	CV.WS.IXN.2			
Method	GET			
URL	<ol> <li>By Customer: /customers/\${customer_id}/interactions</li> <li>By Interaction ID: /interactions/\${interaction_id}</li> </ol>			
Name	Туре	Mandatory	Description	
URI Parameters				
\${customer_id}	string	yes if query is by customer.	Customer ID, required for URI 1.	
\${service_id}	integer	yes if query is by service.	Service ID, required for URI 2.	
\${interaction_id}	integer	yes if query is by interaction.	Service ID, required for URI 3.	

## **Important**

The output sample shows a "structured\_text" parameter which provides a URL to the structured text content (which is not returned as part of the query): the user application performs a separate GET to the given URL.

Similarly, the following URLs are available for GETting interaction content:

- /interactions/\${interaction\_id}/plain\_text
- /interactions/\${interaction\_id}/structured\_text
- /interactions/\${interaction\_id}/binary\_content

## Response

The Context Management Service API answers with HTTP codes for every request. The following table

shows the correct response for a successful request. See HTTP Response Codes and Errors for further details on the possible codes that this operation can return.

#### Response

HTTP code	200	
HTTP message	OK	
Body	An array of one or more Interaction Resources.	

## Example

#### **Operation**

GET http://ucshost:8080/interactions/00001a57JGQ00BW8

#### Result

```
"external_id" : "00AF4A7951D60009",
"established date" : "2009-08-05T09:33:15.000Z",
"text" : "http://ucshost:8080/interactions/00001a57JGQ00BW8/plain_text",
 "media_type" : "chat",
"udata" : {
    "RTargetTypeSelected" : "2",
   "RRequestedSkillCombination": "",
"ChatServerHost": "SUITE80",
"CustomerSegment": "default",
    "RTargetObjectSelected" : "Agent Group Everybody",
"RTargetRuleSelected" : "",
   "RTargetPlaceSelected": "Place_1002",
"RTargetAgentGroup": "Agent Group Everybody",
"RTargetObjSelDBID": "123",
    "ServiceType" : "default",
"_smsSrcNumber" : "+33298143456",
    "RTargetAgentSelected" : "1002",
    "RTenant" : "defaultTenant",
"RVQID" : "",
    "CBR-contract_DBIDs" : ""
    "CBR-Interaction_cost" : "",
    "ChatServerPort": "23874",
    "_smsDestNumber" : "+33298143322",
    "RTargetRequested" : "Agent Group Everybody",
"CBR-IT-path_DBIDs" : "",
    "RStrategyDBID" : "480",
    "CBR-actual_volume" : "",
    "RStrategyName" : "sms-session-inbound"
},
"binary_content" : "http://ucshost:8080/interactions/00001a57JGQ00BW8/binary_content",
"structured_text" : "http://ucshost:8080/interactions/00001a57JGQ00BW8/structured_text",
 "status" : 3,
"subject" : "SMS chat",
 "timeshift" : 1,
"type": "Inbound",
"interaction_id": "00001a57JGQ00BW8",
"allow_children": true,
 "end_date" : "2009-08-05T09:34:04.140Z",
 "owner_id" : 124,
```

```
"sub_type" : "InboundNew",
"released_date" : "2009-08-05T09:33:59.000Z",
"entity_type" : 2,
"creator_app_id" : 175,
"thread_id" : "00001a57JGQ00BW9",
"start_date" : "2009-08-05T09:33:10.000Z",
"structured_text_mime" : "text/xml",
"customer_id" : "00001a57JGQ00BVU"
}
```