



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

User's Guide

Configuration Options

12/14/2025

Configuration Options

Purpose: Lists the configuration options that your application can read in UCS.

Important

This configuration options do not apply to GMS. Refer to the [main options reference](#) for details.

Contents

- [1 Configuration Options](#)
 - [1.1 Description](#)
 - [1.2 \[cview\] Section](#)
 - [1.3 \[archiving\] Section](#)
 - [1.4 \[authentication\] Section](#)
 - [1.5 \[log-filter\] Section](#)
 - [1.6 \[log-filter-data\] Section](#)

Description

The tables in the following sections present the UCS configuration options that Context Services can read from the Configuration Layer:

- `cview` section—Options and values specific to Context Services.
- `archiving` section—Activates [set-based archiving](#).
- `authentication` section—Enables and configures authentication control.
- `log-filter` section—Implements security log filtering.
- `log-filter-data` section—Also relates to security log filtering.

You can modify all these option values in the Configuration Manager. However, the change may not be effective immediately. For some options you have to restart UCS for changes to take effect (see the tables below).

Important

In Configuration Manager and Genesys Administrator, you can see many options other than those described here. They relate to UCS's functioning in eServices (short description [here](#)), and are described in the [eServices Reference Manual](#).

Also, this page describes options that are displayed on the Options tab of the UCS Application object in Configuration Manager and Genesys Administrator. Some options that can be added to the Annex Tab in Configuration Manager, or to Advanced View (Annex) in Genesys Administrator, are described in [Using Configuration Options to Schedule Service Pruning](#) and [UCS Options for TLS](#).

[cview] Section

This section adjusts the overall configuration of Context Services.

cview Section		
Name	[+] Restart UCS This column indicates whether you must restart UCS for changes in the option value to take effect.	Description
enabled	Yes	• true to enable Context Services functionality in Universal Contact Server (UCS). • false (default) to disable Context Services.
base-url	Yes	The base URL used to deploy Context Services. Based on this configuration, the services are available at the following URL: http://\${ip-address}:\${port}/\${base-url}/\${operation} Where: • \${ip-address} is the IP address configured below. • \${port} is the port on which the web services are deployed (see above). • \${base-url} is the base URL used to deploy Context Services. For example, if the ip-address is 192.168.1.1, the port 8080, and the base URL cms, the Set Server Mode operation would be available at the following URL: http://192.168.1.1:8080/cms/server/mode
ip-address	Yes	IP address used to deploy Context Services (localhost by default).
data-validation	No	• true to enable data validation, which enforces additional checks on data provided by the connected clients. • false to disable data validation.
start-mode	Yes	Start-mode of the server mode:

Name	[+] Restart UCS This column indicates whether you must restart UCS for changes in the option value to take effect.	Description
		• maintenance • production
tenant-id	Yes	Defaults to 101. Specifies the numeric tenant ID associated with Context Services: subsequent customer/contact records created through your application are associated with this tenant.
metadata-cache	No	• true to enable the caching of metadata in the memory. • false to disable the metadata caching. In that case, each access to the metadata triggers a DB query. Important The cache contains metadata for contact attributes, identification keys, profiles, services, states and tasks extensions.

[archiving] Section

This section activates and deactivates **set-based archiving**. It is not present on the UCS template; you must create it. It contains just one option:

Name	[+] Restart UCS This column indicates whether you must restart UCS for changes in the option value to take effect.	Description
use-np	Yes	• true to enable set-based archiving. • false (default) to disable set-based archiving.


[authentication] Section

This section configures authentication for clients connecting to UCS. Authentication, available since release 8.0.300.02, applies to UCS/CS only. See also:

- The directly-related [Basic Access Authentication](#) page.
- [Authentication](#) on the Security and Authentication page.

authentication Section

Name	[+] Restart UCS This column indicates whether you must restart UCS for changes in the option value to take effect.	Description
enabled	Yes	• false to disable authentication (default). • true to enable authentication.
mode	Yes	Authentication mode: • single-user to authenticate using UCS options (default). • multi-users to authenticate using Persons from Configuration Server.
password	Yes	Password to check the identity of the specified user. Effective only if mode is set to single-user.
username	Yes	User name allowed to connect to the Context Services API. Effective only if mode is set to single-user.
use-role	Yes	• false to disable the use of roles in authentication (default). • true to enable the use of roles in authentication.



[log-filter] Section

This section contains general settings for how or whether user data keys appear in the logs. Its settings can be overridden for specified keys by options in the **log-filter-data** section.

log-filter Section

Name	[+] Restart UCS This column indicates whether you must restart UCS for changes in the option value to take effect.	Description
default-filter-type	No	Sets the default for filtering the output of user data keys to the UCS server log. Possible values: • skip—Does not output key-value pairs. • hide—Outputs the keys but hides their values. • copy (default)—Outputs both the keys and their values. This default filter applies to all user data keys, except that is is overridden by any settings for individual keys in the log-filter-data section.
filter-depth	No	Depth used while filtering nested key-value pairs. The default is 99. Any value greater than this is not checked. Using a high value can result in lower performance in the case of deeply nested key-values.

[log-filter-data] Section

This section enables you to override the log-filter section's setting for one or more specific data keys. You do this by creating options with the name <keyname> and the value <filtering mode>, where:

- <keyname> is the user data key affected.
- <filtering mode> is skip, hide, or copy, the same as the possible values of default-filter-type in the log-filter section.