



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

API Reference

[Change Metadata Cache](#)

Change Metadata Cache

Important

Prerequisites: You need to **enable** profiles in UCS.

PUT /metadata/cache/

Contents

- [1 Change Metadata Cache](#)
 - [1.1 Description](#)
 - [1.2 Operation](#)
 - [1.3 Response](#)
 - [1.4 Example](#)

Description

Enables the reload of metadata cache. Metadata cache holds information for the definition of identification keys.

Operation

ID	CV.WS.META.CACHE.PUT		
URI	/metadata/cache		
Method	PUT		
Parameter	Type	Mandatory	Description
reload	token	yes	Any value triggers a reload.

Response

The Context Management Service API answers with HTTP codes for every request. The following table shows the correct response for a successful request. See [HTTP Response Codes and Errors](#) for further details on the possible codes that this operation can return.

Response	
HTTP code	200
HTTP message	No Content

Example

The following operation reloads the metadata cache from the database.

Operation

```
PUT /cv/metadata/cache/  
{reload:true}
```

Result

HTTP/1.1 200 OK with an empty body.

<references />