



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

eServices Administrator's Guide

Specify Attributes To Check in Contact Identification

5/6/2025

Specify Attributes To Check in Contact Identification

1. In Configuration Manager, open the `Properties` window for the desired contact attribute.
2. On the `Annex` tab of the `Properties` window (to set Configuration Manager to show the `Annex` tab, see `Configuration Manager Help`), create a `settings` section if it does not already exist.
3. In the `settings` section, create an option called `is-searchable`. Set its value to `TRUE` to make UCS use this attribute in contact identification. Set its value to `FALSE` to keep UCS from using this attribute in contact identification.

(The default value depends on the attribute. The five attributes used in UCS's **default behavior** have the default value `TRUE`. All other attributes have the default value `FALSE`).

Important

This procedure affects the value of the desired attribute's `IsSearchable` attribute in the UCS database. You must use only this procedure to do this. Never edit any attribute or value directly in the database.

There is also a way to control which attributes are searchable from the agent desktop, described in the "Making an Attached Attribute Sortable" section of the "Interaction Package" chapter of the [Genesys Events and Models Reference Manual](#)