



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Web API API Guide

Update User Data

Update User Data

Overview

This operation is used to send a chat interaction.

This operation overwrites the specified UserData with new, specified values.

Request URL	/api/v2/chats/{chatId}
HTTP Method	POST
HTTP Header	Content-Type
Value	application/json

Parameters

Parameter Name	Sample Value	Description	Required/Optional
operationName	"UpdateUserData"	To identify the operation to be performed at this URL	Required
userId	"007553863DC30029"	User ID	Required
secureKey	"8b31761b2154884c"	Secure key	Required
alias	"117"	Host alias	Required
tenantName	"Environment"	Tenant name	Required
userData	["key":"value","key":"value"]	User data to be updated. Values are formatted as "key:value" pairs, with each pair separated by a colon (:) inside the JSON array, as shown in the Sample Value.	Required
text	"text..."	Text, if any	Optional

Example

Request

```
{
  "operationName" : "UpdateUserData",
  "alias" : "117",
  "secureKey" : "8b31761b2154884c",
  "userId" : "007553863DC30029",
  "tenantName": "Environment",
  "userData":{
    "key1":"value1",
    "key2":"value2"
  }
}
```

Response

```
{
  "statusCode":0,
  "alias":"117",
  "secureKey":"8b31761b2154884c",
  "userId":"007553863DC30029",
  "tenantName": "Environment"
}
```