



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

# Configurations Options Reference Manual

[dbclient] Section

5/9/2025

## [dbclient] Section

This section must be called **dbclient**.

### dbclientlimit

Default Value: 4096

Valid Values: any positive integer

Changes Take Effect: At startup

Specifies the maximum limit for the number of simultaneously running DB Client processes.

#### Important

Set this option in Genesys Administrator at the following location:

DB Access Point Application object > Options tab > Advanced View (Options)

The maximum DB limit can also be set via an environment variable GCTI\_DB\_MAX\_NO

### utf8-ucs2

Default Value: false

Valid Values: true, false

Changes Take Effect: At startup

This option applies only if you are working with an MS SQL Log Database that has been initialized as a multi-language database. MS SQL uses UCS-2 encoding instead of UTF-8. Setting this option to true forces the transcoding of UTF-8 to UCS-2 encoding before writing to the MS SQL database, and the transcoding of UCS-2 to UTF-8 encoding after reading from the database. Therefore, the MS SQL database is able to work with other components encoded using UTF-8.

#### Important

Set this option in Genesys Administrator, at the following location:

Database Access Point Application object > Configuration tab > UTF-8 for MSSQL field.