



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

# SIP Feature Server Administration Guide

Appendix: Remove a node from Feature Server deployed with Embedded Cassandra

# Appendix: Remove a node from Feature Server deployed with Embedded Cassandra

Prepare your environment to run node tool on Feature Server host as described in the [Running Nodetool on a Feature Server Host](#) page.

First, listing current nodes:

```
java -cp libthrift-0.7.0.jar:cassandra-thrift-1.1.6.jar:commons-cli-1.1.jar:cassandra-all-1.1.6.jar org.apache.cassandra.tools.NodeCmd -h localhost -p 9192 ring
```

| Address      | DC   | Rack | Status | State  | Load      | Owns   | Token                |
|--------------|------|------|--------|--------|-----------|--------|----------------------|
| Xx           | xx   | xx   | xx     | xx     | xx        |        | 83794128212295607812 |
| 10.52.86.38  | usw1 | RAC1 | Down   | Normal | ?         | 59.09% | 14189180876230654535 |
| 10.51.29.29  | usw1 | RAC2 | Up     | Normal | 547.84 KB | 3.45%  | 20055304209618966354 |
| 10.51.28.170 | usw1 | RAC1 | Up     | Normal | 498.49 KB | 37.46% | 83794128212295607812 |

When the node is up, you can run nodetool decommission in the node you want to remove. For example, node 10.51.29.29 is up so run the following command in this node to remove it.

```
java -cp libthrift-0.7.0.jar:cassandra-thrift-1.1.6.jar:commons-cli-1.1.jar:cassandra-all-1.1.6.jar org.apache.cassandra.tools.NodeCmd -h localhost -p 9192 decommission
```

If the node is down, it results in 'dead' Cassandra node situation if you add a node to the cluster and then delete the Virtual Machine.

To recover from this problem, you must remove the 'dead' node. There is no connection to Cassandra on the node being deleted, so you cannot use 'decommission' command. Use 'removetoken' instead. For example, node 10.52.86.38 is Down. Run the following command by using its token in the any other node to remove 10.52.86.38.

```
java -cp libthrift-0.7.0.jar:cassandra-thrift-1.1.6.jar:commons-cli-1.1.jar:cassandra-all-1.1.6.jar org.apache.cassandra.tools.NodeCmd -h localhost -p 9192
```

Note that this command takes a while to complete.