



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Genesys Administrator Extension Deployment Guide

asd Section

asd Section

Contents

- 1 asd Section
 - 1.1 local_ip_cache_dir
 - 1.2 local_template_dir
 - 1.3 repository_path
 - 1.4 silent_ini_path

This section must be called asd, and is configured in the Genesys Administrator Extension Server Application object of type Generic Genesys Server.

The options in this section are required for the Solution Deployment module in Genesys Administrator Extension.


local_ip_cache_dir

- Default Value: None
- Valid Values: Any valid folder
- Changes Take Effect: After Genesys Administrator Extension is restarted.

Specifies the folder where the IP used for the deployment is cached. Caching the IP reduces deployment time if the IP is reused. This option must be set to a UNC path or a local path that points to a directory that can be accessed (with read/write permissions) from the machine that is running the Genesys Administrator Extension server.


local_template_dir

- Default Value: {CATALINA_HOME}/webapps/gax/WEB-INF/classes/xmltemplates
- Valid Values: Any valid folder
- Changes Take Effect: After Genesys Administrator Extension is restarted.
- Specifies the local directory where component templates are stored. The default value is sufficient unless the directory has been changed after installing Genesys Administrator Extension.

 **Note:** This option is for users of Genesys Administrator Extension 8.1.2 only.

repository_path

- Default Value: /opt/gax/I
- Valid Values: Any valid path
- Changes Take Effect: After Genesys Administrator Extension is restarted.
- Specifies the path where the Genesys Administrator IP Repository can be accessed. It should point to the directory that contains the file repository.xml, as defined in [Step 3 of Installing Samba](#).

 **Note:** This option is for users of Genesys Administrator Extension 8.1.2 only.

silent_ini_path

- Default Value: {CATALINA_HOME}/webapps/gax/WEB-INF/classes/xmltemplates/ ga_default/ genesys_silent_ini.xml
- Valid Values: Any valid path and XML file name
- Changes Take Effect: After Genesys Administrator Extension is restarted.

Specifies the name of the silent installation folder used by ASD. The default value is sufficient unless the path or file has been changed after installing Genesys Administrator Extension.