



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Genesys Administrator Extension Developer's Guide

Configuration Object Manipulation Elements

12/12/2025

Configuration Object Manipulation Elements

Configuration Object Manipulation Elements enables all configuration objects within Configuration Server to be manipulated. The following high-level actions are supported:

- **<cfg:createObject>**: Create a configuration object. Note: If the object already exists, the action fails. If an object already exists or might exist, use the **<cfg:updateObject>** element with the following value: `createonupdate="true"`.
- **<cfg:readObject>**: Read a configuration object. The child element **<cfg:query>** can select which object to read. Note: This action implies that only one object is to be read. If more than one object is to be read or searched, then use the **<cfg:queryObjects>** element to return a list of configuration objects.
- **<cfg:updateObject>**: Update a configuration object.
- **<cfg:deleteObject>**: Delete a configuration object.
- **<cfg:queryObjects>**: Query for a list of configuration objects by using filter or query criteria that is specified in the **<cfg:query>** element.

Contents

- **1 Configuration Object Manipulation Elements**
 - **1.1 <cfg:list>**
 - **1.2 <cfg:agentlogininfo>**
 - **1.3 <cfg:apprank>**
 - **1.4 <cfg:callinglistinfo>**
 - **1.5 <cfg:component>**
 - **1.6 <cfg:componentdefinition>**
 - **1.7 <cfg:conninfo>**
 - **1.8 <cfg:dnaccessnumber>**
 - **1.9 <cfg:dninfo>**
 - **1.10 <cfg:id>**
 - **1.11 <cfg:idtype>**
 - **1.12 <cfg:objectivetablerecord>**
 - **1.13 <cfg:permission>**
 - **1.14 <cfg:portinfo>**
 - **1.15 <cfg:property>**

- 1.16 <cfg:resource>
- 1.17 <cfg:skilllevel>
- 1.18 <cfg:statinterval>
- 1.19 <cfg:subcode>
- 1.20 <cfg:switchaccesscode>
- 1.21 <cfg:parameter>
- 1.22 <cfg:query>
- 1.23 <cfg:createObject>
- 1.24 <cfg:readObject>
- 1.25 <cfg:updateObject>
- 1.26 <cfg:deleteObject>
- 1.27 <cfg:queryObjects>
- 1.28 <cfg:kvitem>
- 1.29 <cfg:updateAppLogOnAs>

<cfg:list>

Child Elements

- <cfg:agentlogininfo>
- <cfg:apprank>
- <cfg:callinglistinfo>
- <cfg:component>
- <cfg:componentdefinition>
- <cfg:conninfo>
- <cfg:dnaccessnumber>
- <cfg:dninfo>
- <cfg:id>
- <cfg:idtype>
- <cfg:objectivetablerecord>
- <cfg:permission>
- <cfg:portinfo>
- <cfg:property>
- <cfg:resource>
- <cfg:skilllevel>
- <cfg:statinterval>
- <cfg:subcode>
- <cfg:switchaccesscode>

Attributes

Name	Type	Description	Default	Values
name	string (required)	—	—	—
mode	string	—	—	clear, merge

<cfg:agentlogininfo>

Attributes

Name	Type	Description	Default	Values
agentlogindbid	integer	—	—	—
data	object	—	—	—
result	string	—	—	—
wrapuptime	integer	—	—	—

<cfg:apprank>

Attributes

Name	Type	Description	Default	Values
apprank	string	—	—	CfgRank
apptype	string	—	—	CfgAppType
data	object	—	—	—
result	string	—	—	—

<cfg:callinglistinfo>

Attributes

Name	Type	Description	Default	Values
callinglistdbid	integer	—	—	—
data	object	—	—	—
isactive	string	—	—	CfgFlag
result	string	—	—	—
share	integer	—	—	—

<cfg:component>

Attributes

Name	Type	Description	Default	Values
appdbid	integer (required)	—	—	—
data	object	—	—	—
isoptional	string	—	—	CfgFlag
result	string	—	—	—
startuppriority	integer	—	—	—

<cfg:componentdefinition>

Attributes

Name	Type	Description	Default	Values
type	string	—	—	CfgAppType
data	object	—	—	—
isoptional	string	—	—	CfgFlag
result	string	—	—	—
startuppriority	integer	—	—	—
version	string	—	—	—

<cfg:conninfo>

Attributes

Name	Type	Description	Default	Values
appparams	string	—	—	—
appserverdbid	integer	—	—	—
charfield1	string	—	—	—
charfield2	string	—	—	—
charfield3	string	—	—	—
charfield4	string	—	—	—
connprotocol	string	—	—	—
data	object	—	—	—
description	string	—	—	—
id	string	—	—	—
longfield1	integer	—	—	—
longfield2	integer	—	—	—
longfield3	integer	—	—	—
longfield4	integer	—	—	—
mode	string	—	—	CfgTraceMode
proxyparams	string	—	—	—
result	string	—	—	—
timeoutlocal	integer	—	—	—
timeoutremote	integer	—	—	—

Name	Type	Description	Default	Values
transportparams	string	—	—	—

<cfg:dnaccessnumber>

Attributes

Name	Type	Description	Default	Values
data	object	—	—	—
number	string (required)	—	—	—
result	string	—	—	—
switchdbid	integer (required)	—	—	—

<cfg:dninfo>

Attributes

Name	Type	Description	Default	Values
data	object	—	—	—
dndbid	integer	—	—	—
result	string	—	—	—
trunks	integer	—	—	—

<cfg:id>

Attributes

Name	Type	Description	Default	Values
data	object	—	—	—

Name	Type	Description	Default	Values
dbid	integer (required)	—	—	—
result	string	—	—	—

<cfg:idtype>

Attributes

Name	Type	Description	Default	Values
type	string	—	—	CfgObjectType
data	object	—	—	—
dbid	integer (required)	—	—	—
result	string	—	—	—

<cfg:objectivetablerecord>

Attributes

Name	Type	Description	Default	Values
contractdbid	integer	—	—	—
customersegmentdbid	integer	—	—	—
data	object	—	—	—
mediatypedbid	integer	—	—	—
objectivedelta	integer	—	—	—
objectivethreshold	integer	—	—	—
result	string	—	—	—

Name	Type	Description	Default	Values
servicetypedbid	integer	—	—	—

<cfg:permission>

Attributes

Name	Type	Description	Default	Values
data	object	—	—	—
grant	string (multiple)	—	—	CfgPermissions
id	integer (required)	—	—	—
recursive	Boolean	—	—	—
result	string	—	—	—
revoke	string (multiple)	—	—	CfgPermissions

<cfg:portinfo>

Attributes

Name	Type	Description	Default	Values
appparams	string	—	—	—
charfield1	string	—	—	—
charfield2	string	—	—	—
charfield3	string	—	—	—
charfield4	string	—	—	—
connprotocol	string	—	—	—

Name	Type	Description	Default	Values
data	object	—	—	—
description	string	—	—	—
id	string (required)	—	—	—
longfield1	integer	—	—	—
longfield2	integer	—	—	—
longfield3	integer	—	—	—
longfield4	integer	—	—	—
port	string (required)	—	—	—
result	string	—	—	—
transportparams	string	—	—	—

<cfg:property>

Attributes

Name	Type	Description	Default	Values
type	string	—	—	string, int, binary
data	object	—	—	—
key	string (required)	—	—	—
result	string	—	—	—
section	string (required)	—	—	—
value	string (required)	—	—	—

<cfg:resource>**Attributes**

Name	Type	Description	Default	Values
charfield1	string	—	—	—
charfield2	string	—	—	—
charfield3	string	—	—	—
charfield4	string	—	—	—
data	object	—	—	—
description	string	—	—	—
longfield1	integer	—	—	—
longfield2	integer	—	—	—
longfield3	integer	—	—	—
longfield4	integer	—	—	—
objectdbid	integer	—	—	—
objecttype	string	—	—	CfgObjectType
resourcetype	string (required)	—	—	CfgResourceType
result	string	—	—	—

<cfg:skilllevel>**Attributes**

Name	Type	Description	Default	Values
data	object	—	—	—
level	integer	—	—	—
result	string	—	—	—
skilldbid	integer	—	—	—

<cfg:statinterval>

Attributes

Name	Type	Description	Default	Values
data	object	—	—	—
intervalcount	integer	—	—	—
result	string	—	—	—
statvalue1	integer	—	—	—
statvalue2	integer	—	—	—
statvalue3	integer	—	—	—
statvalue4	integer	—	—	—

<cfg:subcode>

Attributes

Name	Type	Description	Default	Values
name	string	—	—	—
data	object	—	—	—

Name	Type	Description	Default	Values
result	string	—	—	—

<cfg:switchaccesscode>

Attributes

Name	Type	Description	Default	Values
accesscode	string (required)	—	—	—
data	object	—	—	—
destinationsource	string	—	—	—
dnissource	string	—	—	—
dnsource	string	—	—	—
extensionsource	string	—	—	—
locationsource	string	—	—	—
reasonsource	string	—	—	—
result	string	—	—	—
routhtype	string (required)	—	—	CfgRouteType
switchdbid	integer (required)	—	—	—
targettype	string (required)	—	—	CfgTargetType

<cfg:parameter>

Attributes

Name	Type	Description	Default	Values
name	string (required)	—	—	—
value	string (required)	—	—	—

<cfg:query>

Attributes

Name	Type	Description	Default	Values
name	string (required)	—	—	—
value	string (required)	—	—	—

<cfg:createObject>

Child Elements

- <cfg:list>
- <cfg:parameter>
- <cfg:query>

<cfg:createObject> with type="CfgActionCode"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
name	string	—	—	—
subtype	string	—	—	CfgActionCodeType

Supported List Names

Name	Type	Description	Default	Values
userproperties	<cfg:property>	—	—	—
subcodes	<cfg:subcode>	—	—	—
accountpermissions	<cfg:permission>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
state	string	—	—	CfgObjectState

<cfg:createObject>with type="CfgAccessGroup"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
name	string	—	—	—
subtype	string	—	—	CfgAccessGroupType

Supported List Names

Name	Type	Description	Default	Values
managerdbids	<cfg:id>	—	—	—

Name	Type	Description	Default	Values
userproperties	<cfg:property>	—	—	—
routednbbids	<cfg:id>	—	—	—
accountpermissions	<cfg:permission>	—	—	—
memberids	<cfg:idtype>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
sitedbid	integer	—	—	—
quotatabledbid	integer	—	—	—
contractdbid	integer	—	—	—
capacityruledbid	integer	—	—	—
capacitytabledbid	integer	—	—	—

<cfg:createObject>with type="CfgAgentGroup"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—

Name	Type	Description	Default	Values
name	string	—	—	—

Supported List Names

Name	Type	Description	Default	Values
agentdbids	<cfg:id>	—	—	—
managerdbids	<cfg:id>	—	—	—
userproperties	<cfg:property>	—	—	—
routednids	<cfg:id>	—	—	—
accountpermissions	<cfg:permission>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
sitedbid	integer	—	—	—
quotatabledbid	integer	—	—	—
contractdbid	integer	—	—	—
capacityruledbid	integer	—	—	—
capacitytabledbid	integer	—	—	—

<cfg:createObject>with type="CfgAgentLogin"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—

Supported List Names

Name	Type	Description	Default	Values
accountpermissions	<cfg:permission>	—	—	—
userproperties	<cfg:property>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
switchdbid	integer	—	—	—
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
password	string	—	—	—
switchspecificity	integer	—	—	—
override	string	—	—	—
logincode	string	—	—	—
useoverride	string	—	—	CfgFlag

<cfg:createObject>with type="CfgAlarmCondition"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—

Supported List Names

Name	Type	Description	Default	Values
reactionscripddbids	<cfg:id>	—	—	—
accountpermissions	<cfg:permission>	—	—	—
clearancescripddbids	<cfg:id>	—	—	—
userproperties	<cfg:property>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
appdbid	integer	—	—	—
apptype	string	—	—	CfgAppType
selectionmode	string	—	—	CfgSelectionMode
alarmdetectlogeventid	integer	—	—	—
alarmdetectscripddbids	integer	—	—	—
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
clearancetimeout	integer	—	—	—

Name	Type	Description	Default	Values
category	string	—	—	CfgAlarmCategory
description	string	—	—	—
ismasked	string	—	—	CfgFlag
alarmremovallogeventid	integer	—	—	—

<cfg:createObject>with type="CfgApplication"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
subtype	string	—	—	CfgAppType
name	string	—	—	—

Supported List Names

Name	Type	Description	Default	Values
resources	<cfg:resource>	—	—	—
appservers	<cfg:conninfo>	—	—	—
portinfos	<cfg:portinfo>	—	—	—
userproperties	<cfg:property>	—	—	—
tenantdbids	<cfg:id>	—	—	—
options	<cfg:property>	—	—	—

Name	Type	Description	Default	Values
accountpermissions	<cfg:permission>	—	—	—
flexibleproperties	<cfg:property>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
port	string	—	—	—
backupserverdbid	integer	—	—	—
attempts	integer	—	—	—
hostdbid	integer	—	—	—
timeout	integer	—	—	—
commandline	string	—	—	—
state	string	—	—	CfgObjectState
appprototypedbid	integer	—	—	—
password	string	—	—	—
shutdowntimeout	integer	—	—	—
version	string	—	—	—
workdirectory	string	—	—	—
redundancytype	string	—	—	CfgHAType
componenttype	string	—	—	CfgAppComponentType
folderid	integer	—	—	—

Name	Type	Description	Default	Values
isprimary	string	—	—	CfgFlag
startuptimeout	integer	—	—	—
commandlinearguments	string	—	—	—
autorestart	string	—	—	CfgFlag

<cfg:createObject>with type="CfgAppPrototype"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
subtype	string	—	—	CfgAppType

Supported List Names

Name	Type	Description	Default	Values
userproperties	<cfg:property>	—	—	—
accountpermissions	<cfg:permission>	—	—	—
options	<cfg:property>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—

Name	Type	Description	Default	Values
state	string	—	—	CfgObjectState
version	string	—	—	—

<cfg:createObject>with type="CfgCallingList"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
name	string	—	—	—

Supported List Names

Name	Type	Description	Default	Values
accountpermissions	<cfg:permission>	—	—	—
treatmentdbids	<cfg:id>	—	—	—
userproperties	<cfg:property>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
maxattempts	integer	—	—	—
filterdbid	integer	—	—	—
folderid	integer	—	—	—

Name	Type	Description	Default	Values
scriptdbid	integer	—	—	—
timeuntil	integer	—	—	—
state	string	—	—	CfgObjectState
tableaccessdbid	integer	—	—	—
description	string	—	—	—
logtableaccessdbid	integer	—	—	—
timefrom	integer	—	—	—

<cfg:createObject>with type="CfgCampaign"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
name	string	—	—	—

Supported List Names

Name	Type	Description	Default	Values
callinglists	<cfg:callinglistinfo>	—	—	—
accountpermissions	<cfg:permission>	—	—	—
userproperties	<cfg:property>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
scriptdbid	integer	—	—	—
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
description	string	—	—	—

<cfg:createObject>with type="CfgCampaignGroup"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
tenantdbid	integer	—	—	—
subtype	string	—	—	CfgObjectType

Supported List Names

Name	Type	Description	Default	Values
userproperties	<cfg:property>	—	—	—
serverdbids	<cfg:id>	—	—	—
accountpermissions	<cfg:permission>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
scriptdbid	integer	—	—	—
state	string	—	—	CfgObjectState
optmethodvalue	integer	—	—	—
numofchannels	integer	—	—	—
interactionqueuedbid	integer	—	—	—
description	string	—	—	—
minrecbufsize	integer	—	—	—
groupdbid	integer	—	—	—
optmethod	string	—	—	CfgOptimizationMethod
origdndbid	integer	—	—	—
folderid	integer	—	—	—
dialmode	string	—	—	CfgDialMode
operationmode	string	—	—	CfgOperationMode
optrecbufsize	integer	—	—	—
ivrprofiledbid	integer	—	—	—
campaigndbid	integer	—	—	—
trunkgroupdndbid	integer	—	—	—
maxqueuesize	integer	—	—	—

<cfg:createObject>with type="CfgDN"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
subtype	string	—	—	CfgDNType
name	string	—	—	—
tenantdbid	integer	—	—	—

Supported List Names

Name	Type	Description	Default	Values
userproperties	<cfg:property>	—	—	—
destdnbids	<cfg:id>	—	—	—
accountpermissions	<cfg:permission>	—	—	—
accessnumbers	<cfg:dnaccessnumber>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
registerall	string	—	—	CfgDNRegisterFlag
state	string	—	—	CfgObjectState
contractdbid	integer	—	—	—
routhtype	string	—	—	CfgRouteType
trunks	integer	—	—	—
groupdbid	integer	—	—	—

Name	Type	Description	Default	Values
switchdbid	integer	—	—	—
folderid	integer	—	—	—
association	string	—	—	—
number	string	—	—	—
sitedbid	integer	—	—	—
switchspecificitytype	integer	—	—	—
override	string	—	—	—
useoverride	string	—	—	CfgFlag
dnloginid	string	—	—	—

<cfg:createObject>with type="CfgDNGroup"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
name	string	—	—	—
subtype	string	—	—	CfgDNGroupType

Supported List Names

Name	Type	Description	Default	Values
dns	<code><cfg:dninfo></code>	—	—	—
managerdbids	<code><cfg:id></code>	—	—	—
userproperties	<code><cfg:property></code>	—	—	—
routednbbids	<code><cfg:id></code>	—	—	—
accountpermissions	<code><cfg:permission></code>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
state	string	—	—	<code>CfgObjectState</code>
sitedbid	integer	—	—	—
quotatabledbid	integer	—	—	—
contractdbid	integer	—	—	—
capacityruledbid	integer	—	—	—
capacitytabledbid	integer	—	—	—

`<cfg:createObject>` with `type="CfgEnumerator"`

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—

Name	Type	Description	Default	Values
tenantdbid	integer	—	—	—
name	string	—	—	—
subtype	string	—	—	CfgEnumeratorType

Supported List Names

Name	Type	Description	Default	Values
userproperties	<cfg:property>	—	—	—
accountpermissions	<cfg:permission>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
description	string	—	—	—
state	string	—	—	CfgObjectState
displayname	string	—	—	—

<cfg:createObject>with type="CfgEnumeratorValue"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—

Name	Type	Description	Default	Values
name	string	—	—	—

Supported List Names

Name	Type	Description	Default	Values
accountpermissions	<cfg:permission>	—	—	—
userproperties	<cfg:property>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
enumeratordbid	integer	—	—	—
isdefault	string	—	—	CfgFlag
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
description	string	—	—	—
displayname	string	—	—	—

<cfg:createObject>with type="CfgField"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—

<cfg:createObject>with type="CfgFilter"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
name	string	—	—	—

Supported List Names

Name	Type	Description	Default	Values
userproperties	<cfg:property>	—	—	—
accountpermissions	<cfg:permission>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
description	string	—	—	—
state	string	—	—	CfgObjectState
formatdbid	integer	—	—	—

<cfg:createObject>with type="CfgFolder"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—

Name	Type	Description	Default	Values
data	object	—	—	—
subtype	string	—	—	CfgObjectType
name	string	—	—	—

Supported List Names

Name	Type	Description	Default	Values
resources	<cfg:resource>	—	—	—
accountpermissions	<cfg:permission>	—	—	—
userproperties	<cfg:property>	—	—	—
objectids	<cfg:idtype>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
ownerdbid	integer	—	—	—
ownertype	string	—	—	CfgObjectType
customtype	integer	—	—	—
description	string	—	—	—
folderclass	string	—	—	CfgFolderClass

<cfg:createObject>with type="CfgFormat"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
name	string	—	—	—

Supported List Names

Name	Type	Description	Default	Values
userproperties	<cfg:property>	—	—	—
accountpermissions	<cfg:permission>	—	—	—
fielddbids	<cfg:id>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
description	string	—	—	—
state	string	—	—	CfgObjectState

<cfg:createObject>with type="CfgGVPIVRProfile"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—

Name	Type	Description	Default	Values
data	object	—	—	—
tenantdbid	integer	—	—	—
subtype	string	—	—	CfgIVRProfileType
name	string	—	—	—

Supported List Names

Name	Type	Description	Default	Values
resources	<cfg:resource>	—	—	—
diddbids	<cfg:id>	—	—	—
accountpermissions	<cfg:permission>	—	—	—
userproperties	<cfg:property>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
description	string	—	—	—
notes	string	—	—	—
displayname	string	—	—	—

<cfg:createObject>with type="CfgHost"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
subtype	string	—	—	CfgHostType
name	string	—	—	—

Supported List Names

Name	Type	Description	Default	Values
resources	<cfg:resource>	—	—	—
accountpermissions	<cfg:permission>	—	—	—
userproperties	<cfg:property>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
lcaport	string	—	—	—
state	string	—	—	CfgObjectState
ipaddress	string	—	—	—
ostype	string	—	—	CfgOSType
osversion	string	—	—	—
scsdbid	integer	—	—	—

<cfg:createObject>with type="CfgIVR"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
subtype	string	—	—	CfgIVRType
name	string	—	—	—

Supported List Names

Name	Type	Description	Default	Values
accountpermissions	<cfg:permission>	—	—	—
userproperties	<cfg:property>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
ivrserverdbid	integer	—	—	—
version	string	—	—	—
description	string	—	—	—

<cfg:createObject>with type="CfgIVRPort"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—

Supported List Names

Name	Type	Description	Default	Values
accountpermissions	<cfg:permission>	—	—	—
userproperties	<cfg:property>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
dndbid	integer	—	—	—
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
ivrdbid	integer	—	—	—
portnumber	string	—	—	—
description	string	—	—	—

<cfg:createObject>with type="CfgObjectiveTable"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—

Name	Type	Description	Default	Values
data	object	—	—	—
tenantdbid	integer	—	—	—
subtype	string	—	—	CfgObjectiveTableType
name	string	—	—	—

Supported List Names

Name	Type	Description	Default	Values
accountpermissions	<cfg:permission>	—	—	—
objectiverecords	<cfg:objectivetablerecord>	—	—	—
userproperties	<cfg:property>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
timezonedbid	integer	—	—	—
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
prepaidcost	integer	—	—	—
description	string	—	—	—

<cfg:createObject>with type="CfgPerson"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—

Supported List Names

Name	Type	Description	Default	Values
accountpermissions	<cfg:permission>	—	—	—
userproperties	<cfg:property>	—	—	—
skilllevels	<cfg:skilllevel>	—	—	—
agentlogins	<cfg:agentlogininfo>	—	—	—
appranks	<cfg:apprank>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
employeeid	string	—	—	—
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
lastname	string	—	—	—
firstname	string	—	—	—
password	string	—	—	—
isagent	string	—	—	CfgFlag

Name	Type	Description	Default	Values
placedbid	integer	—	—	—
capacityruledbid	integer	—	—	—
sitedbid	integer	—	—	—
contractdbid	integer	—	—	—
username	string	—	—	—
externalid	string	—	—	—
emailaddress	string	—	—	—
isexternalauth	string	—	—	CfgFlag

<cfg:createObject>with type="CfgPhysicalSwitch"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
subtype	string	—	—	CfgSwitchType

Supported List Names

Name	Type	Description	Default	Values
userproperties	<cfg:property>	—	—	—
accountpermissions	<cfg:permission>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
state	string	—	—	CfgObjectState

<cfg:createObject>with type="CfgPlace"**Attributes**

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
name	string	—	—	—

Supported List Names

Name	Type	Description	Default	Values
dndbids	<cfg:id>	—	—	—
accountpermissions	<cfg:permission>	—	—	—
userproperties	<cfg:property>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
state	string	—	—	CfgObjectState

Name	Type	Description	Default	Values
sitedbid	integer	—	—	—
contractdbid	integer	—	—	—
capacityruledbid	integer	—	—	—

<cfg:createObject>with type="CfgPlaceGroup"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
name	string	—	—	—

Supported List Names

Name	Type	Description	Default	Values
placedbids	<cfg:id>	—	—	—
managerdbids	<cfg:id>	—	—	—
userproperties	<cfg:property>	—	—	—
routedn dbids	<cfg:id>	—	—	—
accountpermissions	<cfg:permission>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
sitedbid	integer	—	—	—
quotatablebid	integer	—	—	—
contractdbid	integer	—	—	—
capacityruledbid	integer	—	—	—
capacitytablebid	integer	—	—	—

<cfg:createObject>with type="CfgRole"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
name	string	—	—	—

Supported List Names

Name	Type	Description	Default	Values
userproperties	<cfg:property>	—	—	—
accountpermissions	<cfg:permission>	—	—	—
members	<cfg:idtype>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
description	string	—	—	—
state	string	—	—	CfgObjectState

<cfg:createObject>with type="CfgScript"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
name	string	—	—	—
subtype	string	—	—	CfgScriptType

Supported List Names

Name	Type	Description	Default	Values
userproperties	<cfg:property>	—	—	—
resources	<cfg:resource>	—	—	—
accountpermissions	<cfg:permission>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
index	integer	—	—	—
folderid	integer	—	—	—
state	string	—	—	CfgObjectState

<cfg:createObject>with type="CfgService"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
subtype	string	—	—	CfgSolutionType
name	string	—	—	—

Supported List Names

Name	Type	Description	Default	Values
resources	<cfg:resource>	—	—	—
accountpermissions	<cfg:permission>	—	—	—
componentdefinitions	<cfg:componentdefinition>	—	—	—
userproperties	<cfg:property>	—	—	—
components	<cfg:component>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
assignedtenantdbid	integer	—	—	—
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
startuptype	string	—	—	CfgStartupType
version	string	—	—	—
scsdbid	integer	—	—	—

<cfg:createObject>with type="CfgSkill"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
name	string	—	—	—

Supported List Names

Name	Type	Description	Default	Values
userproperties	<cfg:property>	—	—	—
accountpermissions	<cfg:permission>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
state	string	—	—	CfgObjectState

<cfg:createObject>with type="CfgStatDay"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
subtype	string	—	—	CfgStatDayType
name	string	—	—	—

Supported List Names

Name	Type	Description	Default	Values
accountpermissions	<cfg:permission>	—	—	—
userproperties	<cfg:property>	—	—	—
statintervals	<cfg:statinterval>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
endtime	integer	—	—	—
minvalue	integer	—	—	—

Name	Type	Description	Default	Values
starttime	integer	—	—	—
folderid	integer	—	—	—
targetvalue	integer	—	—	—
maxvalue	integer	—	—	—
state	string	—	—	CfgObjectState
intervallength	integer	—	—	—
flatrate	integer	—	—	—
useflatrate	string	—	—	CfgFlag
isdayofweek	string	—	—	CfgFlag
day	integer	—	—	—

<cfg:createObject>with type="CfgStatTable"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
subtype	string	—	—	CfgStatTableType
name	string	—	—	—

Supported List Names

Name	Type	Description	Default	Values
accountpermissions	<cfg:permission>	—	—	—
statdaydbids	<cfg:id>	—	—	—
userproperties	<cfg:property>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
agenthourlyrate	integer	—	—	—
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
flatrate	integer	—	—	—
waitthreshold	integer	—	—	—
useflatrate	string	—	—	CfgFlag

<cfg:createObject>with type="CfgSwitch"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
name	string	—	—	—

Supported List Names

Name	Type	Description	Default	Values
accountpermissions	<cfg:permission>	—	—	—
userproperties	<cfg:property>	—	—	—
switchaccesscodes	<cfg:switchaccesscode>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
dnrange	string	—	—	—
state	string	—	—	CfgObjectState
tserverdbid	integer	—	—	—
physswitchdbid	integer	—	—	—
linktype	string	—	—	CfgLinkType

<cfg:createObject>with type="CfgTableAccess"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
subtype	string	—	—	CfgTableType
name	string	—	—	—

Supported List Names

Name	Type	Description	Default	Values
accountpermissions	<cfg:permission>	—	—	—
userproperties	<cfg:property>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
updatetimeout	integer	—	—	—
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
iscachable	string	—	—	CfgFlag
formatdbid	integer	—	—	—
dbtablename	string	—	—	—
description	string	—	—	—
dbaccessdbid	integer	—	—	—

<cfg:createObject>with type="CfgTenant"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—

Supported List Names

Name	Type	Description	Default	Values
accountpermissions	<cfg:permission>	—	—	—
userproperties	<cfg:property>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
isserviceprovider	string	—	—	CfgFlag
defaultcapacityruledbid	integer	—	—	—
chargeablenumber	string	—	—	—
defaultcontractdbid	integer	—	—	—
state	string	—	—	CfgObjectState
password	string	—	—	—
parenttenantdbid	integer	—	—	—

<cfg:createObject>with type="CfgTimeZone"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
name	string	—	—	—

Supported List Names

Name	Type	Description	Default	Values
accountpermissions	<cfg:permission>	—	—	—
userproperties	<cfg:property>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
dstoffset	integer	—	—	—
state	string	—	—	CfgObjectState
namenetscape	string	—	—	—
namemsexplorer	string	—	—	—
description	string	—	—	—
isdstobserved	string	—	—	CfgFlag
offset	integer	—	—	—

<cfg:createObject>with type="CfgTransaction"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—

Name	Type	Description	Default	Values
subtype	string	—	—	CfgTransactionType
name	string	—	—	—

Supported List Names

Name	Type	Description	Default	Values
accountpermissions	<cfg:permission>	—	—	—
userproperties	<cfg:property>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
alias	string	—	—	—
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
recordperiod	integer	—	—	—
description	string	—	—	—

<cfg:createObject>with type="CfgTreatment"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—

Name	Type	Description	Default	Values
subtype	string	—	—	CfgCallActionCode
name	string	—	—	—

Supported List Names

Name	Type	Description	Default	Values
accountpermissions	<cfg:permission>	—	—	—
userproperties	<cfg:property>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
increment	integer	—	—	—
range	integer	—	—	—
interval	integer	—	—	—
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
cycleattempt	integer	—	—	—
reactioncode	string	—	—	CfgRecActionCode
description	string	—	—	—
attempts	integer	—	—	—
destdndbid	integer	—	—	—
callresult	string	—	—	[1]

<cfg:createObject>with type="CfgVoicePrompt"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
name	string	—	—	—

Supported List Names

Name	Type	Description	Default	Values
accountpermissions	<cfg:permission>	—	—	—
userproperties	<cfg:property>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
switchdbid	integer	—	—	—
scriptdbid	integer	—	—	—
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
description	string	—	—	—

<cfg:readObject>

Child Elements

<cfg:list><cfg:parameter><cfg:query>

<cfg:readObject>with type="CfgAccessGroup"**Attributes**

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
name	string	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
persondbid	integer	—	—	—
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—
dbid	integer	—	—	—
name	string	—	—	—

<cfg:readObject>with type="CfgActionCode"**Attributes**

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
name	string	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
tenantdbid	integer	—	—	—
dbid	integer	—	—	—
name	string	—	—	—
state	string	—	—	CfgObjectState

<cfg:readObject>with type="CfgAgentGroup"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
persondbid	integer	—	—	—
folderid	integer	—	—	—

Name	Type	Description	Default	Values
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
state	string	—	—	CfgObjectState
name	string	—	—	—
tenantdbid	integer	—	—	—
dbid	integer	—	—	—

<cfg:readObject>with type="CfgAgentLogin"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
nopersondbid	integer	—	—	—

Name	Type	Description	Default	Values
logincode	string	—	—	—
state	string	—	—	CfgObjectState
switchdbid	integer	—	—	—
tenantdbid	integer	—	—	—

<cfg:readObject>with type="CfgAlarmCondition"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
name	string	—	—	—
state	string	—	—	CfgObjectState

<cfg:readObject>with type="CfgApplication"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
subtype	string	—	—	CfgAppType
name	string	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
accountdbid	integer	—	—	—
accounttype	string	—	—	CfgObjectType
appprototypedbid	integer	—	—	—
subtype	string	—	—	CfgAppType
backupserverdbid	integer	—	—	—
dbid	integer	—	—	—
hostdbid	integer	—	—	—
isserver	string	—	—	CfgFlag
name	string	—	—	—

Name	Type	Description	Default	Values
noclientdbid	integer	—	—	—
noswitchdbid	integer	—	—	—
port	integer	—	—	—
primaryserverdbid	integer	—	—	—
samehostandport	integer	—	—	—
serverdbid	integer	—	—	—
startuptype	string	—	—	CfgStartupType
state	string	—	—	CfgObjectState
switchdbid	integer	—	—	—
tenantdbid	integer	—	—	—
version	string	—	—	—

<cfg:readObject>with type="CfgAppPrototype"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
subtype	string	—	—	CfgAppType
name	string	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
subtype	string	—	—	CfgAppType
dbid	integer	—	—	—
name	string	—	—	—
state	string	—	—	CfgObjectState
version	string	—	—	—

<cfg:readObject>with type="CfgCallingList"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—

Name	Type	Description	Default	Values
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
filterdbid	integer	—	—	—
logtableaccessdbid	integer	—	—	—
name	string	—	—	—
scriptdbid	integer	—	—	—
state	string	—	—	CfgObjectState
tableaccessdbid	integer	—	—	—
tenantdbid	integer	—	—	—
treatmentdbid	integer	—	—	—

<cfg:readObject>with type="CfgCampaignGroup"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
campaigndbid	integer	—	—	—
dbid	integer	—	—	—
groupdbid	integer	—	—	—
name	string	—	—	—
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—

<cfg:readObject>with type="CfgCampaign"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
name	string	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—

Name	Type	Description	Default	Values
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
callinglistdbid	integer	—	—	—
dbid	integer	—	—	—
groupdbid	integer	—	—	—
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—
name	string	—	—	—

<cfg:readObject>with type="CfgDNGroup"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
subtype	string	—	—	CfgDNGroupType
name	string	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—

Name	Type	Description	Default	Values
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
dndbid	integer	—	—	—
subtype	string	—	—	CfgDNGroupType
name	string	—	—	—
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—

<cfg:readObject>with type="CfgDN"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
subtype	string	—	—	CfgDNType
name	string	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
association	string	—	—	—

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
number	string	—	—	—
subtype	string	—	—	CfgDNType
groupdbid	integer	—	—	—
ivrdbid	integer	—	—	—
name	string	—	—	—
noplacedbid	integer	—	—	—
placedbid	integer	—	—	—
state	string	—	—	CfgObjectState
switchdbid	integer	—	—	—
tenantdbid	integer	—	—	—

<cfg:readObject>with type="CfgEnumerator"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—

Name	Type	Description	Default	Values
subtype	string	—	—	CfgEnumeratorType
name	string	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
displayname	string	—	—	—
subtype	string	—	—	CfgEnumeratorType
name	string	—	—	—
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—

<cfg:readObject>with type="CfgEnumeratorValue"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—

Name	Type	Description	Default	Values
name	string	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
defaultvalue	string	—	—	CfgFlag
displayname	string	—	—	—
enumeratordbid	integer	—	—	—
name	string	—	—	—
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—

<cfg:readObject>with type="CfgField"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—

Name	Type	Description	Default	Values
name	string	—	—	—
tenantdbid	integer	—	—	—
subtype	string	—	—	CfgDataType

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
fieldtype	string	—	—	CfgFieldType
formatdbid	integer	—	—	—
name	string	—	—	—
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—
subtype	string	—	—	CfgDataType

<cfg:readObject>with type="CfgFilter"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—

Name	Type	Description	Default	Values
name	string	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
formatdbid	integer	—	—	—
name	string	—	—	—
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—

<cfg:readObject>with type="CfgFolder"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
subtype	string	—	—	CfgObjectType
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
defaultfolder	string	—	—	CfgFolderClass
folderclass	string	—	—	CfgFolderClass
name	string	—	—	—
objectdbid	integer	—	—	—
objecttype	string	—	—	CfgObjectType
ownerdbid	integer	—	—	—
ownertype	string	—	—	CfgObjectType
state	string	—	—	CfgObjectState
subtype	string	—	—	CfgObjectType
tenantdbid	integer	—	—	—

<cfg:readObject>with type="CfgFormat"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—

Name	Type	Description	Default	Values
data	object	—	—	—
name	string	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
fielddbid	integer	—	—	—
name	string	—	—	—
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—

<cfg:readObject>with type="CfgGVPIVRProfile"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—

Name	Type	Description	Default	Values
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
dbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
name	string	—	—	—
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—

<cfg:readObject>with type="CfgHost"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
subtype	string	—	—	CfgHostType
name	string	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
subtype	string	—	—	CfgHostType
name	string	—	—	—
ostype	string	—	—	CfgOSType
scsdbid	integer	—	—	—
state	string	—	—	CfgObjectState

<cfg:readObject>with type="CfgIVRPort"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—

Name	Type	Description	Default	Values
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
dndbid	integer	—	—	—
ivrdbid	integer	—	—	—
portnumber	string	—	—	—
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—

<cfg:readObject>with type="CfgIVR"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
tenantdbid	integer	—	—	—
subtype	string	—	—	CfgIVRType

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—

Name	Type	Description	Default	Values
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
ivrserverdbid	integer	—	—	—
name	string	—	—	—
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—
subtype	string	—	—	CfgIVRType

<cfg:readObject>with type="CfgObjectiveTable"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType

Name	Type	Description	Default	Values
dbid	integer	—	—	—
name	string	—	—	—
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—

<cfg:readObject>with type="CfgPerson"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
name	string	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
employeeid	string	—	—	—
firstname	string	—	—	—

Name	Type	Description	Default	Values
isagent	string	—	—	CfgFlag
lastname	string	—	—	—
logindbid	integer	—	—	—
nologindbid	integer	—	—	—
noplacedbid	integer	—	—	—
skilldbid	integer	—	—	—
state	string	—	—	CfgObjectState
switchdbid	integer	—	—	—
tenantdbid	integer	—	—	—
username	string	—	—	—
name	string	—	—	—

<cfg:readObject>with type="CfgPhysicalSwitch"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
folderdbid	integer	—	—	—
name	string	—	—	—
state	string	—	—	CfgObjectState

<cfg:readObject>with type="CfgPlaceGroup"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType

Name	Type	Description	Default	Values
dbid	integer	—	—	—
name	string	—	—	—
placedbid	integer	—	—	—
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—

<cfg:readObject>with type="CfgPlace"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
dndbid	integer	—	—	—

Name	Type	Description	Default	Values
groupdbid	integer	—	—	—
name	string	—	—	—
nodndbid	integer	—	—	—
persondbid	integer	—	—	—
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—

<cfg:readObject>with type="CfgRole"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—

Name	Type	Description	Default	Values
name	string	—	—	—
state	string	—	—	CfgObjectState
rbacappns	string	—	—	—
tenantdbid	integer	—	—	—

<cfg:readObject>with type="CfgScript"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
subtype	string	—	—	CfgScriptType
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
capacityagentdbid	integer	—	—	—
capacityagentgroupdbid	integer	—	—	—

Name	Type	Description	Default	Values
capacityplacedbid	integer	—	—	—
capacityplacegroupdbid	integer	—	—	—
capacitytenantdbid	integer	—	—	—
dbid	integer	—	—	—
excludebytecode	string	—	—	CfgFlag
excludelongstrings	string	—	—	CfgFlag
name	string	—	—	—
subtype	string	—	—	CfgScriptType
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—

<cfg:readObject>with type="CfgService"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
tenantdbid	integer	—	—	—
subtype	string	—	—	CfgSolutionType

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
folderdbid	integer	—	—	—
name	string	—	—	—
scsdbid	integer	—	—	—
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—
subtype	string	—	—	CfgSolutionType

<cfg:readObject>with type="CfgSkill"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
name	string	—	—	—
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—

<cfg:readObject>with type="CfgStatDay"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
subtype	string	—	—	CfgStatDayType
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—

Name	Type	Description	Default	Values
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
name	string	—	—	—
subtype	string	—	—	CfgStatDayType
state	string	—	—	CfgObjectState
tabledbid	integer	—	—	—
tenantdbid	integer	—	—	—

<cfg:readObject>with type="CfgStatTable"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
subtype	string	—	—	CfgStatTableType
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—

Name	Type	Description	Default	Values
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
groupdbid	integer	—	—	—
name	string	—	—	—
statdaydbid	integer	—	—	—
state	string	—	—	CfgObjectState
subtype	string	—	—	CfgStatTableType
tenantdbid	integer	—	—	—

<cfg:readObject>with type="CfgSwitch"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—

Name	Type	Description	Default	Values
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
name	string	—	—	—
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—
tserverdbid	integer	—	—	—

<cfg:readObject>with type="CfgTableAccess"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
tenantdbid	integer	—	—	—
subtype	string	—	—	CfgTableType

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType

Name	Type	Description	Default	Values
dbaccessdbid	integer	—	—	—
dbid	integer	—	—	—
dbtablename	string	—	—	—
formatdbid	integer	—	—	—
name	string	—	—	—
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—
subtype	string	—	—	CfgTableType

<cfg:readObject>with type="CfgTenant"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType

Name	Type	Description	Default	Values
alltenants	string	If included, regardless of value, returns the root tenant in the resultset. If excluded, the root tenant is not returned in the resultset.	—	CfgFlag
dbid	integer	—	—	—
name	string	—	—	—
state	string	—	—	CfgObjectState

<cfg:readObject>with type="CfgTimeZone"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—

Name	Type	Description	Default	Values
name	string	—	—	—
namemsexplorer	string	—	—	—
namenetscape	string	—	—	—
offset	integer	—	—	—
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—

<cfg:readObject>with type="CfgTransaction"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
subtype	string	—	—	CfgTransactionType
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType

Name	Type	Description	Default	Values
dbid	integer	—	—	—
name	string	—	—	—
subtype	string	—	—	CfgTransactionType
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—

<cfg:readObject>with type="CfgTreatment"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
callactioncode	string	—	—	CfgCallActionCode
callresult	string	—	—	—

Name	Type	Description	Default	Values
dbid	integer	—	—	—
destdndbid	integer	—	—	—
name	string	—	—	—
reactioncode	string	—	—	CfgRecActionCode
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—

<cfg:readObject>with type="CfgVoicePrompt"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—

Name	Type	Description	Default	Values
name	string	—	—	—
scriptdbid	integer	—	—	—
state	string	—	—	CfgObjectState
switchdbid	integer	—	—	—
tenantdbid	integer	—	—	—

<cfg:updateObject>

This is the HTML documentation for the `<cfg:updateObject>` element.

Child Elements

`<cfg:list>` `<cfg:parameter>` `<cfg:query>`

<cfg:updateObject> with type="CfgActionCode"

This is the HTML documentation for the `<cfg:updateObject>` element when the **type** attribute is CfgActionCode.

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
name	string	—	—	—
subtype	string	—	—	CfgActionCodeType
createonupdate	Boolean	—	—	—
mode	string	—	—	merge, clear

Supported List Names

Name	Type	Description	Default	Values
userproperties	<code><cfg:property></code>	—	—	—
subcodes	<code><cfg:subcode></code>	—	—	—
accountpermissions	<code><cfg:permission></code>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
state	string	—	—	CfgObjectState

Supported Query Names

Name	Type	Description	Default	Values
type	string	—	—	[2]
folderid	integer	—	—	—
tenantdbid	integer	—	—	—
name	string	—	—	—
state	string	—	—	CfgObjectState
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—

`<cfg:updateObject>` with `type="CfgAccessGroup"`

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
name	string	—	—	—
subtype	string	—	—	CfgAccessGroupType
createonupdate	Boolean	—	—	—
mode	string	—	—	merge, clear

Supported List Names

Name	Type	Description	Default	Values
managerdbids	<cfg:id>	—	—	—
userproperties	<cfg:property>	—	—	—
routednbbids	<cfg:id>	—	—	—
accountpermissions	<cfg:permission>	—	—	—
memberids	<cfg:idtype>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
sitedbid	integer	—	—	—

Name	Type	Description	Default	Values
quotatabledbid	integer	—	—	—
contractdbid	integer	—	—	—
capacityruledbid	integer	—	—	—
capacitytabledbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
type	string	—	—	[3]
tenantdbid	integer	—	—	—
state	string	—	—	CfgObjectState
name	string	—	—	—
persondbid	integer	—	—	—
dbid	integer	—	—	—

<cfg:updateObject>with type="CfgAgentGroup"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
name	string	—	—	—

Name	Type	Description	Default	Values
createonupdate	Boolean	—	—	—
mode	string	—	—	merge, clear

Supported List Names

Name	Type	Description	Default	Values
agentdbids	<cfg:id>	—	—	—
managerdbids	<cfg:id>	—	—	—
userproperties	<cfg:property>	—	—	—
routednids	<cfg:id>	—	—	—
accountpermissions	<cfg:permission>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
sitedbid	integer	—	—	—
quotatabledbid	integer	—	—	—
contractdbid	integer	—	—	—
capacityruledbid	integer	—	—	—
capacitytabledbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
type	string	—	—	[4]
folderid	integer	—	—	—
tenantdbid	integer	—	—	—
state	string	—	—	CfgObjectState
name	string	—	—	—
persondbid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—

<cfg:updateObject>with type="CfgAgentLogin"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
createonupdate	Boolean	—	—	—
mode	string	—	—	merge, clear

Supported List Names

Name	Type	Description	Default	Values
accountpermissions	<cfg:permission>	—	—	—
userproperties	<cfg:property>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
switchdbid	integer	—	—	—
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
password	string	—	—	—
switchspecificity	integer	—	—	—
override	string	—	—	—
logincode	string	—	—	—
useoverride	string	—	—	CfgFlag

Supported Query Names

Name	Type	Description	Default	Values
type	string	—	—	[5]
switchdbid	integer	—	—	—
tenantdbid	integer	—	—	—
folderid	integer	—	—	—
state	string	—	—	CfgObjectState

Name	Type	Description	Default	Values
logincode	string	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
nopersondbid	integer	—	—	—

<cfg:updateObject>with type="CfgAlarmCondition"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
createonupdate	Boolean	—	—	—
mode	string	—	—	merge, clear

Supported List Names

Name	Type	Description	Default	Values
reactionscripddbids	<cfg:id>	—	—	—
accountpermissions	<cfg:permission>	—	—	—
clearancescripddbids	<cfg:id>	—	—	—
userproperties	<cfg:property>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
appdbid	integer	—	—	—
apptype	string	—	—	CfgAppType
selectionmode	string	—	—	CfgSelectionMode
alarmdetectlogeventid	integer	—	—	—
alarmdetectscriptdbid	integer	—	—	—
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
clearancetimeout	integer	—	—	—
category	string	—	—	CfgAlarmCategory
description	string	—	—	—
ismasked	string	—	—	CfgFlag
alarmremovallogeventid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
type	string	—	—	[6]
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
name	string	—	—	—

Name	Type	Description	Default	Values
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—

<cfg:updateObject>with type="CfgApplication"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
subtype	string	—	—	CfgAppType
name	string	—	—	—
tenantdbid	integer	—	—	—
createonupdate	Boolean	—	—	—
mode	string	—	—	merge, clear

Supported List Names

Name	Type	Description	Default	Values
resources	<cfg:resource>	—	—	—
appservers	<cfg:conninfo>	—	—	—
portinfos	<cfg:portinfo>	—	—	—
userproperties	<cfg:property>	—	—	—

Name	Type	Description	Default	Values
tenantdbids	<cfg:id>	—	—	—
options	<cfg:property>	—	—	—
accountpermissions	<cfg:permission>	—	—	—
flexibleproperties	<cfg:property>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
port	string	—	—	—
backupserverdbid	integer	—	—	—
attempts	integer	—	—	—
hostdbid	integer	—	—	—
timeout	integer	—	—	—
commandline	string	—	—	—
state	string	—	—	CfgObjectState
appprototypedbid	integer	—	—	—
password	string	—	—	—
shutdowntimeout	integer	—	—	—
version	string	—	—	—
workdirectory	string	—	—	—
redundancytype	string	—	—	CfgHAType

Name	Type	Description	Default	Values
componenttype	string	—	—	CfgAppComponentType
folderid	integer	—	—	—
isprimary	string	—	—	CfgFlag
startuptimeout	integer	—	—	—
commandlinearguments	string	—	—	—
autorestart	string	—	—	CfgFlag

Supported Query Names

Name	Type	Description	Default	Values
type	string	—	—	[7]
port	string	—	—	—
backupserverdbid	integer	—	—	—
hostdbid	integer	—	—	—
state	string	—	—	CfgObjectState
appprototypedbid	integer	—	—	—
subtype	string	—	—	CfgAppType
version	string	—	—	—
name	string	—	—	—
folderid	integer	—	—	—
delegatedbid	integer	—	—	—

Name	Type	Description	Default	Values
delegatetype	string	—	—	CfgObjectType
accountdbid	integer	—	—	—
accounttype	string	—	—	CfgObjectType
dbid	integer	—	—	—
isserver	string	—	—	CfgFlag
noclientdbid	integer	—	—	—
noswitchdbid	integer	—	—	—
primaryserverdbid	integer	—	—	—
samehostandport	integer	—	—	—
serverdbid	integer	—	—	—
startuptype	string	—	—	CfgStartupType
switchdbid	integer	—	—	—
tenantdbid	integer	—	—	—

<cfg:updateObject>with type="CfgAppPrototype"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—

Name	Type	Description	Default	Values
subtype	string	—	—	CfgAppType
createonupdate	Boolean	—	—	—
mode	string	—	—	merge, clear

Supported List Names

Name	Type	Description	Default	Values
userproperties	<cfg:property>	—	—	—
accountpermissions	<cfg:permission>	—	—	—
options	<cfg:property>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
version	string	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
type	string	—	—	[8]
folderid	integer	—	—	—
name	string	—	—	—
state	string	—	—	CfgObjectState

Name	Type	Description	Default	Values
subtype	string	—	—	CfgAppType
version	string	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—

<cfg:updateObject>with type="CfgCallingList"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
name	string	—	—	—
createonupdate	Boolean	—	—	—
mode	string	—	—	merge, clear

Supported List Names

Name	Type	Description	Default	Values
accountpermissions	<cfg:permission>	—	—	—
treatmentdbids	<cfg:id>	—	—	—
userproperties	<cfg:property>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
maxattempts	integer	—	—	—
filterdbid	integer	—	—	—
folderid	integer	—	—	—
scriptdbid	integer	—	—	—
timeuntil	integer	—	—	—
state	string	—	—	CfgObjectState
tableaccessdbid	integer	—	—	—
description	string	—	—	—
logtableaccessdbid	integer	—	—	—
timefrom	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
type	string	—	—	[9]
filterdbid	integer	—	—	—
folderid	integer	—	—	—
scriptdbid	integer	—	—	—
tenantdbid	integer	—	—	—
state	string	—	—	CfgObjectState

Name	Type	Description	Default	Values
tableaccessdbid	integer	—	—	—
name	string	—	—	—
logtableaccessdbid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
treatmentdbid	integer	—	—	—

<cfg:updateObject> with type="CfgCampaign"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
name	string	—	—	—
createonupdate	Boolean	—	—	—
mode	string	—	—	merge, clear

Supported List Names

Name	Type	Description	Default	Values
callinglists	<cfg:callinglistinfo>	—	—	—

Name	Type	Description	Default	Values
accountpermissions	<cfg:permission>	—	—	—
userproperties	<cfg:property>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
scriptdbid	integer	—	—	—
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
description	string	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
type	string	—	—	[10]
tenantdbid	integer	—	—	—
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
name	string	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
callinglistdbid	integer	—	—	—
dbid	integer	—	—	—

Name	Type	Description	Default	Values
groupdbid	integer	—	—	—

<cfg:updateObject>with type="CfgCampaignGroup"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
tenantdbid	integer	—	—	—
subtype	string	—	—	CfgObjectType
createonupdate	Boolean	—	—	—
mode	string	—	—	merge, clear

Supported List Names

Name	Type	Description	Default	Values
userproperties	<cfg:property>	—	—	—
serverdbids	<cfg:id>	—	—	—
accountpermissions	<cfg:permission>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
scriptdbid	integer	—	—	—

Name	Type	Description	Default	Values
state	string	—	—	CfgObjectState
optmethodvalue	integer	—	—	—
numofchannels	integer	—	—	—
interactionqueuedbid	integer	—	—	—
description	string	—	—	—
minrecbuffsize	integer	—	—	—
groupdbid	integer	—	—	—
optmethod	string	—	—	CfgOptimizationMethod
origdndbid	integer	—	—	—
folderid	integer	—	—	—
dialmode	string	—	—	CfgDialMode
operationmode	string	—	—	CfgOperationMode
optrecbuffsize	integer	—	—	—
ivrprofiledbid	integer	—	—	—
campaigndbid	integer	—	—	—
trunkgroupdndbid	integer	—	—	—
maxqueue size	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
type	string	—	—	[11]
state	string	—	—	CfgObjectState
name	string	—	—	—
groupdbid	integer	—	—	—
folderid	integer	—	—	—
tenantdbid	integer	—	—	—
campaigndbid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—

<cfg:updateObject>with type="CfgDN"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
subtype	string	—	—	CfgDNType
name	string	—	—	—
tenantdbid	integer	—	—	—
createonupdate	Boolean	—	—	—

Name	Type	Description	Default	Values
mode	string	—	—	merge, clear

Supported List Names

Name	Type	Description	Default	Values
userproperties	<cfg:property>	—	—	—
destdnbids	<cfg:id>	—	—	—
accountpermissions	<cfg:permission>	—	—	—
accessnumbers	<cfg:dnaccessnumber>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
registerall	string	—	—	CfgDNRegisterFlag
state	string	—	—	CfgObjectState
contractdbid	integer	—	—	—
routrtype	string	—	—	CfgRouteType
trunks	integer	—	—	—
groupdbid	integer	—	—	—
switchdbid	integer	—	—	—
folderid	integer	—	—	—
association	string	—	—	—
number	string	—	—	—

Name	Type	Description	Default	Values
sitedbid	integer	—	—	—
switchspecificitytype	integer	—	—	—
override	string	—	—	—
useoverride	string	—	—	CfgFlag
dnloginid	string	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
type	string	—	—	[12]
state	string	—	—	CfgObjectState
subtype	string	—	—	CfgDNTYPE
name	string	—	—	—
groupdbid	integer	—	—	—
switchdbid	integer	—	—	—
folderid	integer	—	—	—
association	string	—	—	—
tenantdbid	integer	—	—	—
number	string	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType

Name	Type	Description	Default	Values
dbid	integer	—	—	—
ivrdbid	integer	—	—	—
noplacedbid	integer	—	—	—
placedbid	integer	—	—	—

<cfg:updateObject>with type="CfgDNGroup"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
name	string	—	—	—
subtype	string	—	—	CfgDNGroupType
createonupdate	Boolean	—	—	—
mode	string	—	—	merge, clear

Supported List Names

Name	Type	Description	Default	Values
dns	<cfg:dninfo>	—	—	—
managerdbids	<cfg:id>	—	—	—
userproperties	<cfg:property>	—	—	—

Name	Type	Description	Default	Values
routednrbids	<cfg:id>	—	—	—
accountpermissions	<cfg:permission>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
sitedbid	integer	—	—	—
quotatabledbid	integer	—	—	—
contractdbid	integer	—	—	—
capacityruledbid	integer	—	—	—
capacitytabledbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
type	string	—	—	[13]
folderid	integer	—	—	—
tenantdbid	integer	—	—	—
state	string	—	—	CfgObjectState
name	string	—	—	—
subtype	string	—	—	CfgDNGroupType

Name	Type	Description	Default	Values
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
dndbid	integer	—	—	—

<cfg:updateObject>with type="CfgEnumerator"**Attributes**

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
name	string	—	—	—
subtype	string	—	—	CfgEnumeratorType
createonupdate	Boolean	—	—	—
mode	string	—	—	merge, clear

Supported List Names

Name	Type	Description	Default	Values
userproperties	<cfg:property>	—	—	—
accountpermissions	<cfg:permission>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
description	string	—	—	—
state	string	—	—	CfgObjectState
displayname	string	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
type	string	—	—	[14]
folderid	integer	—	—	—
tenantdbid	integer	—	—	—
name	string	—	—	—
state	string	—	—	CfgObjectState
subtype	string	—	—	CfgEnumeratorType
displayname	string	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—

<cfg:updateObject>with type="CfgEnumeratorValue"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
name	string	—	—	—
createonupdate	Boolean	—	—	—
mode	string	—	—	merge, clear

Supported List Names

Name	Type	Description	Default	Values
accountpermissions	<cfg:permission>	—	—	—
userproperties	<cfg:property>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
enumeratordbid	integer	—	—	—
isdefault	string	—	—	CfgFlag
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
description	string	—	—	—
displayname	string	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
type	string	—	—	[15]
enumeratordbid	integer	—	—	—
tenantdbid	integer	—	—	—
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
name	string	—	—	—
displayname	string	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
defaultvalue	string	—	—	CfgFlag

<cfg:updateObject>with type="CfgField"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—

<cfg:updateObject>with type="CfgFilter"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
name	string	—	—	—
createonupdate	Boolean	—	—	—
mode	string	—	—	merge, clear

Supported List Names

Name	Type	Description	Default	Values
userproperties	<cfg:property>	—	—	—
accountpermissions	<cfg:permission>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
description	string	—	—	—
state	string	—	—	CfgObjectState
formatdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
type	string	—	—	[16]

Name	Type	Description	Default	Values
folderid	integer	—	—	—
tenantdbid	integer	—	—	—
name	string	—	—	—
state	string	—	—	CfgObjectState
formatdbid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType

<cfg:updateObject>with type="CfgFolder"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
subtype	string	—	—	CfgObjectType
name	string	—	—	—
tenantdbid	integer	—	—	—
createonupdate	Boolean	—	—	—
mode	string	—	—	merge, clear

Supported List Names

Name	Type	Description	Default	Values
resources	<cfg:resource>	—	—	—
accountpermissions	<cfg:permission>	—	—	—
userproperties	<cfg:property>	—	—	—
objectids	<cfg:idtype>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
ownerdbid	integer	—	—	—
ownertype	string	—	—	CfgObjectType
customtype	integer	—	—	—
description	string	—	—	—
folderclass	string	—	—	CfgFolderClass

Supported Query Names

Name	Type	Description	Default	Values
type	string	—	—	[17]
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
ownerdbid	integer	—	—	—

Name	Type	Description	Default	Values
ownertype	string	—	—	CfgObjectType
subtype	string	—	—	CfgObjectType
name	string	—	—	—
folderclass	string	—	—	CfgFolderClass
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
defaultfolder	string	—	—	CfgFolderClass
objectdbid	integer	—	—	—
objecttype	string	—	—	CfgObjectType
tenantdbid	integer	—	—	—

<cfg:updateObject>with type="CfgFormat"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
name	string	—	—	—
createonupdate	Boolean	—	—	—

Name	Type	Description	Default	Values
mode	string	—	—	merge, clear

Supported List Names

Name	Type	Description	Default	Values
userproperties	<cfg:property>	—	—	—
accountpermissions	<cfg:permission>	—	—	—
fielddbids	<cfg:id>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
description	string	—	—	—
state	string	—	—	CfgObjectState

Supported Query Names

Name	Type	Description	Default	Values
type	string	—	—	[18]
folderid	integer	—	—	—
tenantdbid	integer	—	—	—
name	string	—	—	—
state	string	—	—	CfgObjectState
delegatedbid	integer	—	—	—

Name	Type	Description	Default	Values
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
fielddbid	integer	—	—	—

<cfg:updateObject>with type="CfgGVPIVRProfile"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
subtype	string	—	—	CfgIVRProfileType
name	string	—	—	—
createonupdate	Boolean	—	—	—
mode	string	—	—	merge, clear

Supported List Names

Name	Type	Description	Default	Values
resources	<cfg:resource>	—	—	—
diddbids	<cfg:id>	—	—	—
accountpermissions	<cfg:permission>	—	—	—
userproperties	<cfg:property>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
description	string	—	—	—
notes	string	—	—	—
displayname	string	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
type	string	—	—	[19]
folderid	integer	—	—	—
tenantdbid	integer	—	—	—
state	string	—	—	CfgObjectState
name	string	—	—	—
delegatedbid	integer	—	—	—
dbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType

<cfg:updateObject>with type="CfgHost"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
subtype	string	—	—	CfgHostType
name	string	—	—	—
createonupdate	Boolean	—	—	—
mode	string	—	—	merge, clear

Supported List Names

Name	Type	Description	Default	Values
resources	<cfg:resource>	—	—	—
accountpermissions	<cfg:permission>	—	—	—
userproperties	<cfg:property>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
lcaport	string	—	—	—
state	string	—	—	CfgObjectState
ipaddress	string	—	—	—
ostype	string	—	—	CfgOSType
osversion	string	—	—	—

Name	Type	Description	Default	Values
scsdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
type	string	—	—	[20]
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
subtype	string	—	—	CfgHostType
ostype	string	—	—	CfgOSType
scsdbid	integer	—	—	—
name	string	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—

<cfg:updateObject>with type="CfgIVR"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—

Name	Type	Description	Default	Values
subtype	string	—	—	CfgIVRType
name	string	—	—	—
createonupdate	Boolean	—	—	—
mode	string	—	—	merge, clear

Supported List Names

Name	Type	Description	Default	Values
accountpermissions	<cfg:permission>	—	—	—
userproperties	<cfg:property>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
ivrserverdbid	integer	—	—	—
version	string	—	—	—
description	string	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
type	string	—	—	[21]
tenantdbid	integer	—	—	—

Name	Type	Description	Default	Values
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
subtype	string	—	—	CfgIVRType
ivrserverdbid	integer	—	—	—
name	string	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—

<cfg:updateObject>with type="CfgIVRPort"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
createonupdate	Boolean	—	—	—
mode	string	—	—	merge, clear

Supported List Names

Name	Type	Description	Default	Values
accountpermissions	<cfg:permission>	—	—	—

Name	Type	Description	Default	Values
userproperties	<cfg:property>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
dndbid	integer	—	—	—
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
ivrdbid	integer	—	—	—
portnumber	string	—	—	—
description	string	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
type	string	—	—	[22]
tenantdbid	integer	—	—	—
dndbid	integer	—	—	—
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
ivrdbid	integer	—	—	—
portnumber	string	—	—	—
delegatedbid	integer	—	—	—

Name	Type	Description	Default	Values
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—

<cfg:updateObject>with type="CfgObjectiveTable"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
subtype	string	—	—	CfgObjectiveTableType
name	string	—	—	—
createonupdate	Boolean	—	—	—
mode	string	—	—	merge, clear

Supported List Names

Name	Type	Description	Default	Values
accountpermissions	<cfg:permission>	—	—	—
objectiverecords	<cfg:objectivetablerecord>	—	—	—
userproperties	<cfg:property>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
timezonedbid	integer	—	—	—
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
prepaidcost	integer	—	—	—
description	string	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
type	string	—	—	[23]
folderid	integer	—	—	—
tenantdbid	integer	—	—	—
state	string	—	—	CfgObjectState
name	string	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—

<cfg:updateObject>with type="CfgPerson"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—

Name	Type	Description	Default	Values
data	object	—	—	—
tenantdbid	integer	—	—	—
name	string	—	—	—
createonupdate	Boolean	—	—	—
mode	string	—	—	merge, clear

Supported List Names

Name	Type	Description	Default	Values
accountpermissions	<cfg:permission>	—	—	—
userproperties	<cfg:property>	—	—	—
skilllevels	<cfg:skilllevel>	—	—	—
agentlogins	<cfg:agentlogininfo>	—	—	—
appranks	<cfg:apprank>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
employeeid	string	—	—	—
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
lastname	string	—	—	—
firstname	string	—	—	—

Name	Type	Description	Default	Values
password	string	—	—	—
isagent	string	—	—	CfgFlag
placedbid	integer	—	—	—
capacityruledbid	integer	—	—	—
sitedbid	integer	—	—	—
contractdbid	integer	—	—	—
username	string	—	—	—
externalid	string	—	—	—
emailaddress	string	—	—	—
isexternalauth	string	—	—	CfgFlag

Supported Query Names

Name	Type	Description	Default	Values
type	string	—	—	[24]
employeeid	string	—	—	—
folderid	integer	—	—	—
tenantdbid	integer	—	—	—
state	string	—	—	CfgObjectState
lastname	string	—	—	—
firstname	string	—	—	—

Name	Type	Description	Default	Values
isagent	string	—	—	CfgFlag
username	string	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
logindbid	integer	—	—	—
nologindbid	integer	—	—	—
noplacedbid	integer	—	—	—
skilldbid	integer	—	—	—
switchdbid	integer	—	—	—
name	string	—	—	—

<cfg:updateObject>with type="CfgPhysicalSwitch"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
subtype	string	—	—	CfgSwitchType
createonupdate	Boolean	—	—	—

Name	Type	Description	Default	Values
mode	string	—	—	merge, clear

Supported List Names

Name	Type	Description	Default	Values
userproperties	<cfg:property>	—	—	—
accountpermissions	<cfg:permission>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
state	string	—	—	CfgObjectState

Supported Query Names

Name	Type	Description	Default	Values
type	string	—	—	[25]
folderid	integer	—	—	—
name	string	—	—	—
state	string	—	—	CfgObjectState
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
folderdbid	integer	—	—	—

<cfg:updateObject>with type="CfgPlace"**Attributes**

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
name	string	—	—	—
createonupdate	Boolean	—	—	—
mode	string	—	—	merge, clear

Supported List Names

Name	Type	Description	Default	Values
dndbids	<cfg:id>	—	—	—
accountpermissions	<cfg:permission>	—	—	—
userproperties	<cfg:property>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
sitedbid	integer	—	—	—
contractdbid	integer	—	—	—

Name	Type	Description	Default	Values
capacityruledbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
type	string	—	—	[26]
folderid	integer	—	—	—
tenantdbid	integer	—	—	—
state	string	—	—	CfgObjectState
name	string	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
dndbid	integer	—	—	—
groupdbid	integer	—	—	—
nodndbid	integer	—	—	—
persondbid	integer	—	—	—

<cfg:updateObject>with type="CfgPlaceGroup"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—

Name	Type	Description	Default	Values
data	object	—	—	—
tenantdbid	integer	—	—	—
name	string	—	—	—
createonupdate	Boolean	—	—	—
mode	string	—	—	merge, clear

Supported List Names

Name	Type	Description	Default	Values
placedbids	<cfg:id>	—	—	—
managerdbids	<cfg:id>	—	—	—
userproperties	<cfg:property>	—	—	—
routedn dbids	<cfg:id>	—	—	—
accountpermissions	<cfg:permission>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
sitedbid	integer	—	—	—
quotatabledbid	integer	—	—	—
contractdbid	integer	—	—	—

Name	Type	Description	Default	Values
capacityruledbid	integer	—	—	—
capacitytabledbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
type	string	—	—	[27]
folderid	integer	—	—	—
tenantdbid	integer	—	—	—
state	string	—	—	CfgObjectState
name	string	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
placedbid	integer	—	—	—

<cfg:updateObject>with type="CfgRole"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—

Name	Type	Description	Default	Values
name	string	—	—	—
createonupdate	Boolean	—	—	—
mode	string	—	—	merge, clear

Supported List Names

Name	Type	Description	Default	Values
userproperties	<cfg:property>	—	—	—
accountpermissions	<cfg:permission>	—	—	—
members	<cfg:idtype>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
description	string	—	—	—
state	string	—	—	CfgObjectState

Supported Query Names

Name	Type	Description	Default	Values
type	string	—	—	[28]
folderid	integer	—	—	—
tenantdbid	integer	—	—	—
name	string	—	—	—

Name	Type	Description	Default	Values
state	string	—	—	CfgObjectState
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
rbacappns	string	—	—	—

<cfg:updateObject>with type="CfgScript"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
name	string	—	—	—
subtype	string	—	—	CfgScriptType
createonupdate	Boolean	—	—	—
mode	string	—	—	merge, clear

Supported List Names

Name	Type	Description	Default	Values
userproperties	<cfg:property>	—	—	—
resources	<cfg:resource>	—	—	—

Name	Type	Description	Default	Values
accountpermissions	<cfg:permission>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
index	integer	—	—	—
folderid	integer	—	—	—
state	string	—	—	CfgObjectState

Supported Query Names

Name	Type	Description	Default	Values
type	string	—	—	[29]
folderid	integer	—	—	—
tenantdbid	integer	—	—	—
name	string	—	—	—
state	string	—	—	CfgObjectState
subtype	string	—	—	CfgScriptType
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
capacityagentdbid	integer	—	—	—
capacityagentgroupdbid	integer	—	—	—
capacityplacedbid	integer	—	—	—

Name	Type	Description	Default	Values
capacityplacegroupdbid	integer	—	—	—
capacitytenantdbid	integer	—	—	—
dbid	integer	—	—	—
excludebytecode	string	—	—	CfgFlag
excludelongstrings	string	—	—	CfgFlag

<cfg:updateObject>with type="CfgService"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
subtype	string	—	—	CfgSolutionType
name	string	—	—	—
tenantdbid	integer	—	—	—
createonupdate	Boolean	—	—	—
mode	string	—	—	merge, clear

Supported List Names

Name	Type	Description	Default	Values
resources	<cfg:resource>	—	—	—
accountpermissions	<cfg:permission>	—	—	—

Name	Type	Description	Default	Values
componentdefinitions	<code><cfg:componentdefinition></code>	—	—	—
userproperties	<code><cfg:property></code>	—	—	—
components	<code><cfg:component></code>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
assignedtenantdbid	integer	—	—	—
folderid	integer	—	—	—
state	string	—	—	<code>CfgObjectState</code>
startuptype	string	—	—	<code>CfgStartupType</code>
version	string	—	—	—
scsdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
type	string	—	—	<code>[30]</code>
subtype	string	—	—	<code>CfgSolutionType</code>
folderid	integer	—	—	—
state	string	—	—	<code>CfgObjectState</code>
scsdbid	integer	—	—	—
name	string	—	—	—

Name	Type	Description	Default	Values
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
folderdbid	integer	—	—	—
tenantdbid	integer	—	—	—

<cfg:updateObject>with type="CfgSkill"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
name	string	—	—	—
createonupdate	Boolean	—	—	—
mode	string	—	—	merge, clear

Supported List Names

Name	Type	Description	Default	Values
userproperties	<cfg:property>	—	—	—
accountpermissions	<cfg:permission>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
state	string	—	—	CfgObjectState

Supported Query Names

Name	Type	Description	Default	Values
type	string	—	—	[31]
folderid	integer	—	—	—
tenantdbid	integer	—	—	—
name	string	—	—	—
state	string	—	—	CfgObjectState
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—

<cfg:updateObject>with type="CfgStatDay"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
subtype	string	—	—	CfgStatDayType

Name	Type	Description	Default	Values
name	string	—	—	—
createonupdate	Boolean	—	—	—
mode	string	—	—	merge, clear

Supported List Names

Name	Type	Description	Default	Values
accountpermissions	<cfg:permission>	—	—	—
userproperties	<cfg:property>	—	—	—
statintervals	<cfg:statinterval>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
endtime	integer	—	—	—
minvalue	integer	—	—	—
starttime	integer	—	—	—
folderid	integer	—	—	—
targetvalue	integer	—	—	—
maxvalue	integer	—	—	—
state	string	—	—	CfgObjectState
intervallength	integer	—	—	—
flatrate	integer	—	—	—

Name	Type	Description	Default	Values
useflatrate	string	—	—	CfgFlag
isdayofweek	string	—	—	CfgFlag
day	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
type	string	—	—	[32]
folderid	integer	—	—	—
tenantdbid	integer	—	—	—
state	string	—	—	CfgObjectState
subtype	string	—	—	CfgStatDayType
name	string	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
tabledbid	integer	—	—	—

<cfg:updateObject>with type="CfgStatTable"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—

Name	Type	Description	Default	Values
data	object	—	—	—
tenantdbid	integer	—	—	—
subtype	string	—	—	CfgStatTableType
name	string	—	—	—
createonupdate	Boolean	—	—	—
mode	string	—	—	merge, clear

Supported List Names

Name	Type	Description	Default	Values
accountpermissions	<cfg:permission>	—	—	—
statdaydbids	<cfg:id>	—	—	—
userproperties	<cfg:property>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
agenthourlyrate	integer	—	—	—
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
flatrate	integer	—	—	—
waitthreshold	integer	—	—	—
useflatrate	string	—	—	CfgFlag

Supported Query Names

Name	Type	Description	Default	Values
type	string	—	—	[33]
folderid	integer	—	—	—
tenantdbid	integer	—	—	—
state	string	—	—	CfgObjectState
subtype	string	—	—	CfgStatTableType
name	string	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
groupdbid	integer	—	—	—
statdaydbid	integer	—	—	—

<cfg:updateObject>with type="CfgSwitch"**Attributes**

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
name	string	—	—	—

Name	Type	Description	Default	Values
createonupdate	Boolean	—	—	—
mode	string	—	—	merge, clear

Supported List Names

Name	Type	Description	Default	Values
accountpermissions	<cfg:permission>	—	—	—
userproperties	<cfg:property>	—	—	—
switchaccesscodes	<cfg:switchaccesscode>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
dnrange	string	—	—	—
state	string	—	—	CfgObjectState
tserverdbid	integer	—	—	—
physswitchdbid	integer	—	—	—
linktype	string	—	—	CfgLinkType

Supported Query Names

Name	Type	Description	Default	Values
type	string	—	—	[34]
folderid	integer	—	—	—

Name	Type	Description	Default	Values
tenantdbid	integer	—	—	—
state	string	—	—	CfgObjectState
tserverdbid	integer	—	—	—
name	string	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—

<cfg:updateObject>with type="CfgTableAccess"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
subtype	string	—	—	CfgTableType
name	string	—	—	—
createonupdate	Boolean	—	—	—
mode	string	—	—	merge, clear

Supported List Names

Name	Type	Description	Default	Values
accountpermissions	<cfg:permission>	—	—	—
userproperties	<cfg:property>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
updatetimeout	integer	—	—	—
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
iscachable	string	—	—	CfgFlag
formatdbid	integer	—	—	—
dbtablename	string	—	—	—
description	string	—	—	—
dbaccessdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
type	string	—	—	[35]
folderid	integer	—	—	—
tenantdbid	integer	—	—	—
state	string	—	—	CfgObjectState
subtype	string	—	—	CfgTableType

Name	Type	Description	Default	Values
formatdbid	integer	—	—	—
dbtablename	string	—	—	—
name	string	—	—	—
dbaccessdbid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—

<cfg:updateObject> with type="CfgTenant"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
createonupdate	Boolean	—	—	—
mode	string	—	—	merge, clear

Supported List Names

Name	Type	Description	Default	Values
accountpermissions	<cfg:permission>	—	—	—
userproperties	<cfg:property>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
isserviceprovider	string	—	—	CfgFlag
defaultcapacityruledbid	integer	—	—	—
chargeablenumber	string	—	—	—
defaultcontractdbid	integer	—	—	—
state	string	—	—	CfgObjectState
password	string	—	—	—
parenttenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
type	string	—	—	[36]
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
name	string	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
alltenants	string	If included, regardless of value, returns the root tenant in the resultset. If excluded, the root tenant is not returned in the	—	CfgFlag

Name	Type	Description	Default	Values
		resultset.		
dbid	integer	—	—	—

<cfg:updateObject>with type="CfgTimeZone"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
name	string	—	—	—
createonupdate	Boolean	—	—	—
mode	string	—	—	merge, clear

Supported List Names

Name	Type	Description	Default	Values
accountpermissions	<cfg:permission>	—	—	—
userproperties	<cfg:property>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
dstoffset	integer	—	—	—

Name	Type	Description	Default	Values
state	string	—	—	CfgObjectState
namenetscape	string	—	—	—
namemsexplorer	string	—	—	—
description	string	—	—	—
isdstobserved	string	—	—	CfgFlag
offset	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
type	string	—	—	[37]
folderid	integer	—	—	—
tenantdbid	integer	—	—	—
state	string	—	—	CfgObjectState
namenetscape	string	—	—	—
namemsexplorer	string	—	—	—
name	string	—	—	—
offset	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—

<cfg:updateObject>with type="CfgTransaction"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
subtype	string	—	—	CfgTransactionType
name	string	—	—	—
createonupdate	Boolean	—	—	—
mode	string	—	—	merge, clear

Supported List Names

Name	Type	Description	Default	Values
accountpermissions	<cfg:permission>	—	—	—
userproperties	<cfg:property>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
alias	string	—	—	—
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
recordperiod	integer	—	—	—

Name	Type	Description	Default	Values
description	string	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
type	string	—	—	[38]
tenantdbid	integer	—	—	—
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
subtype	string	—	—	CfgTransactionType
name	string	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—

<cfg:updateObject>with type="CfgTreatment"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
subtype	string	—	—	CfgCallActionCode

Name	Type	Description	Default	Values
name	string	—	—	—
createonupdate	Boolean	—	—	—
mode	string	—	—	merge, clear

Supported List Names

Name	Type	Description	Default	Values
accountpermissions	<cfg:permission>	—	—	—
userproperties	<cfg:property>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
increment	integer	—	—	—
range	integer	—	—	—
interval	integer	—	—	—
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
cycleattempt	integer	—	—	—
reactioncode	string	—	—	CfgRecActionCode
description	string	—	—	—
attempts	integer	—	—	—
destdndbid	integer	—	—	—

Name	Type	Description	Default	Values
callresult	string	—	—	[39]

Supported Query Names

Name	Type	Description	Default	Values
type	string	—	—	[40]
folderid	integer	—	—	—
tenantdbid	integer	—	—	—
state	string	—	—	CfgObjectState
reactioncode	string	—	—	CfgRecActionCode
name	string	—	—	—
destdndbid	integer	—	—	—
callresult	string	—	—	[41]
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
callactioncode	string	—	—	CfgCallActionCode
dbid	integer	—	—	—

<cfg:updateObject>with type="CfgVoicePrompt"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—

Name	Type	Description	Default	Values
data	object	—	—	—
tenantdbid	integer	—	—	—
name	string	—	—	—
createonupdate	Boolean	—	—	—
mode	string	—	—	merge, clear

Supported List Names

Name	Type	Description	Default	Values
accountpermissions	<cfg:permission>	—	—	—
userproperties	<cfg:property>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
switchdbid	integer	—	—	—
scriptdbid	integer	—	—	—
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
description	string	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
type	string	—	—	[42]

Name	Type	Description	Default	Values
switchdbid	integer	—	—	—
tenantdbid	integer	—	—	—
scriptdbid	integer	—	—	—
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
name	string	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—

<cfg:deleteObject>

Child Elements

<cfg:list><cfg:parameter><cfg:query>

<cfg:deleteObject>with type="CfgAccessGroup"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
name	string	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
persondbid	integer	—	—	—
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—
dbid	integer	—	—	—
name	string	—	—	—

<cfg:deleteObject>with type="CfgActionCode"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
name	string	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
tenantdbid	integer	—	—	—
dbid	integer	—	—	—

Name	Type	Description	Default	Values
name	string	—	—	—
state	string	—	—	CfgObjectState

<cfg:deleteObject>with type="CfgAgentGroup"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
persondbid	integer	—	—	—
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
state	string	—	—	CfgObjectState
name	string	—	—	—
tenantdbid	integer	—	—	—
dbid	integer	—	—	—

<cfg:deleteObject>with type="CfgAgentLogin"**Attributes**

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
nopersondbid	integer	—	—	—
logincode	string	—	—	—
state	string	—	—	CfgObjectState
switchdbid	integer	—	—	—
tenantdbid	integer	—	—	—

<cfg:deleteObject>with type="CfgAlarmCondition"**Attributes**

Name	Type	Description	Default	Values
result	string	—	—	—

Name	Type	Description	Default	Values
data	object	—	—	—
name	string	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
name	string	—	—	—
state	string	—	—	CfgObjectState

<cfg:deleteObject>with type="CfgApplication"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
subtype	string	—	—	CfgAppType
name	string	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
accountdbid	integer	—	—	—
accounttype	string	—	—	CfgObjectType
appprototypedbid	integer	—	—	—
subtype	string	—	—	CfgAppType
backupserverdbid	integer	—	—	—
dbid	integer	—	—	—
hostdbid	integer	—	—	—
isserver	string	—	—	CfgFlag
name	string	—	—	—
noclientdbid	integer	—	—	—
noswitchdbid	integer	—	—	—
port	integer	—	—	—
primaryserverdbid	integer	—	—	—
samehostandport	integer	—	—	—
serverdbid	integer	—	—	—
startuptype	string	—	—	CfgStartupType

Name	Type	Description	Default	Values
state	string	—	—	CfgObjectState
switchdbid	integer	—	—	—
tenantdbid	integer	—	—	—
version	string	—	—	—

<cfg:deleteObject>with type="CfgAppPrototype"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
subtype	string	—	—	CfgAppType
name	string	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
subtype	string	—	—	CfgAppType
dbid	integer	—	—	—
name	string	—	—	—

Name	Type	Description	Default	Values
state	string	—	—	CfgObjectState
version	string	—	—	—

<cfg:deleteObject>with type="CfgCallingList"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
filterdbid	integer	—	—	—
logtableaccessdbid	integer	—	—	—
name	string	—	—	—
scriptdbid	integer	—	—	—

Name	Type	Description	Default	Values
state	string	—	—	CfgObjectState
tableaccessdbid	integer	—	—	—
tenantdbid	integer	—	—	—
treatmentdbid	integer	—	—	—

<cfg:deleteObject>with type="CfgCampaignGroup"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
campaigndbid	integer	—	—	—
dbid	integer	—	—	—
groupdbid	integer	—	—	—

Name	Type	Description	Default	Values
name	string	—	—	—
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—

<cfg:deleteObject>with type="CfgCampaign"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
name	string	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
callinglistdbid	integer	—	—	—
dbid	integer	—	—	—
groupdbid	integer	—	—	—
state	string	—	—	CfgObjectState

Name	Type	Description	Default	Values
tenantdbid	integer	—	—	—
name	string	—	—	—

<cfg:deleteObject>with type="CfgDNGroup"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
subtype	string	—	—	CfgDNGroupType
name	string	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
dndbid	integer	—	—	—
subtype	string	—	—	CfgDNGroupType
name	string	—	—	—

Name	Type	Description	Default	Values
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—

<cfg:deleteObject>with type="CfgDN"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
subtype	string	—	—	CfgDNType
name	string	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
association	string	—	—	—
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
number	string	—	—	—
subtype	string	—	—	CfgDNType

Name	Type	Description	Default	Values
groupdbid	integer	—	—	—
ivrdbid	integer	—	—	—
name	string	—	—	—
noplacedbid	integer	—	—	—
placedbid	integer	—	—	—
state	string	—	—	CfgObjectState
switchdbid	integer	—	—	—
tenantdbid	integer	—	—	—

<cfg:deleteObject>with type="CfgEnumerator"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
subtype	string	—	—	CfgEnumeratorType
name	string	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—

Name	Type	Description	Default	Values
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
displayname	string	—	—	—
subtype	string	—	—	CfgEnumeratorType
name	string	—	—	—
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—

<cfg:deleteObject>with type="CfgEnumeratorValue"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—

Name	Type	Description	Default	Values
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
defaultvalue	string	—	—	CfgFlag
displayname	string	—	—	—
enumeratordbid	integer	—	—	—
name	string	—	—	—
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—

<cfg:deleteObject>with type="CfgField"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
tenantdbid	integer	—	—	—
subtype	string	—	—	CfgDataType

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—

Name	Type	Description	Default	Values
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
fieldtype	string	—	—	CfgFieldType
formatdbid	integer	—	—	—
name	string	—	—	—
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—
subtype	string	—	—	CfgDataType

<cfg:deleteObject>with type="CfgFilter"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—

Name	Type	Description	Default	Values
delegatetype	string	—	—	CfgObjectType
formatdbid	integer	—	—	—
name	string	—	—	—
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—

<cfg:deleteObject>with type="CfgFolder"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
subtype	string	—	—	CfgObjectType
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—

Name	Type	Description	Default	Values
defaultfolder	string	—	—	CfgFolderClass
folderclass	string	—	—	CfgFolderClass
name	string	—	—	—
objectdbid	integer	—	—	—
objecttype	string	—	—	CfgObjectType
ownerdbid	integer	—	—	—
ownertype	string	—	—	CfgObjectType
state	string	—	—	CfgObjectState
subtype	string	—	—	CfgObjectType
tenantdbid	integer	—	—	—

<cfg:deleteObject>with type="CfgFormat"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
fielddbid	integer	—	—	—
name	string	—	—	—
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—

<cfg:deleteObject>with type="CfgGVPIVRProfile"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—

Name	Type	Description	Default	Values
dbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
name	string	—	—	—
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—

<cfg:deleteObject>with type="CfgHost"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
subtype	string	—	—	CfgHostType
name	string	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
subtype	string	—	—	CfgHostType

Name	Type	Description	Default	Values
name	string	—	—	—
ostype	string	—	—	CfgOSType
scsdbid	integer	—	—	—
state	string	—	—	CfgObjectState

<cfg:deleteObject>with type="CfgIVRPort"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
dndbid	integer	—	—	—
ivrdbid	integer	—	—	—
portnumber	string	—	—	—

Name	Type	Description	Default	Values
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—

<cfg:deleteObject>with type="CfgIVR"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
tenantdbid	integer	—	—	—
subtype	string	—	—	CfgIVRType

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
ivrserverdbid	integer	—	—	—
name	string	—	—	—
state	string	—	—	CfgObjectState

Name	Type	Description	Default	Values
tenantdbid	integer	—	—	—
subtype	string	—	—	CfgIVRType

<cfg:deleteObject>with type="CfgObjectiveTable"**Attributes**

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
name	string	—	—	—
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—

<cfg:deleteObject>with type="CfgPerson"**Attributes**

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
name	string	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
employeeid	string	—	—	—
firstname	string	—	—	—
isagent	string	—	—	CfgFlag
lastname	string	—	—	—
logindbid	integer	—	—	—
nologindbid	integer	—	—	—
noplacedbid	integer	—	—	—
skilldbid	integer	—	—	—
state	string	—	—	CfgObjectState

Name	Type	Description	Default	Values
switchdbid	integer	—	—	—
tenantdbid	integer	—	—	—
username	string	—	—	—
name	string	—	—	—

<cfg:deleteObject>with type="CfgPhysicalSwitch"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
folderdbid	integer	—	—	—
name	string	—	—	—
state	string	—	—	CfgObjectState

<cfg:deleteObject>with type="CfgPlaceGroup"**Attributes**

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
name	string	—	—	—
placedbid	integer	—	—	—
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—

<cfg:deleteObject>with type="CfgPlace"**Attributes**

Name	Type	Description	Default	Values
result	string	—	—	—

Name	Type	Description	Default	Values
data	object	—	—	—
name	string	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
dndbid	integer	—	—	—
groupdbid	integer	—	—	—
name	string	—	—	—
nodndbid	integer	—	—	—
persondbid	integer	—	—	—
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—

<cfg:deleteObject>with type="CfgRole"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
name	string	—	—	—
state	string	—	—	CfgObjectState
rbacappns	string	—	—	—
tenantdbid	integer	—	—	—

<cfg:deleteObject>with type="CfgScript"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—

Name	Type	Description	Default	Values
name	string	—	—	—
subtype	string	—	—	CfgScriptType
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
capacityagentdbid	integer	—	—	—
capacityagentgroupdbid	integer	—	—	—
capacityplacedbid	integer	—	—	—
capacityplacegroupdbid	integer	—	—	—
capacitytenantdbid	integer	—	—	—
dbid	integer	—	—	—
excludebytecode	string	—	—	CfgFlag
excludelongstrings	string	—	—	CfgFlag
name	string	—	—	—
subtype	string	—	—	CfgScriptType
state	string	—	—	CfgObjectState

Name	Type	Description	Default	Values
tenantdbid	integer	—	—	—

<cfg:deleteObject>with type="CfgService"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
tenantdbid	integer	—	—	—
subtype	string	—	—	CfgSolutionType

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
folderdbid	integer	—	—	—
name	string	—	—	—
scsdbid	integer	—	—	—
state	string	—	—	CfgObjectState

Name	Type	Description	Default	Values
tenantdbid	integer	—	—	—
subtype	string	—	—	CfgSolutionType

<cfg:deleteObject>with type="CfgSkill"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
name	string	—	—	—
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—

<cfg:deleteObject>with type="CfgStatDay"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
subtype	string	—	—	CfgStatDayType
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
name	string	—	—	—
subtype	string	—	—	CfgStatDayType
state	string	—	—	CfgObjectState
tabledbid	integer	—	—	—
tenantdbid	integer	—	—	—

<cfg:deleteObject>with type="CfgStatTable"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
subtype	string	—	—	CfgStatTableType
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
groupdbid	integer	—	—	—
name	string	—	—	—
statdaydbid	integer	—	—	—
state	string	—	—	CfgObjectState
subtype	string	—	—	CfgStatTableType
tenantdbid	integer	—	—	—

<cfg:deleteObject>with type="CfgSwitch"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
name	string	—	—	—
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—
tserverdbid	integer	—	—	—

<cfg:deleteObject>with type="CfgTableAccess"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—

Name	Type	Description	Default	Values
name	string	—	—	—
tenantdbid	integer	—	—	—
subtype	string	—	—	CfgTableType

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbaccessdbid	integer	—	—	—
dbid	integer	—	—	—
dbtablename	string	—	—	—
formatdbid	integer	—	—	—
name	string	—	—	—
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—
subtype	string	—	—	CfgTableType

<cfg:deleteObject>with type="CfgTenant"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
alltenants	string	If included, regardless of value, returns the root tenant in the resultset. If excluded, the root tenant is not returned in the resultset.	—	CfgFlag
dbid	integer	—	—	—
name	string	—	—	—
state	string	—	—	CfgObjectState

<cfg:deleteObject>with type="CfgTimeZone"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—

Name	Type	Description	Default	Values
name	string	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
name	string	—	—	—
namemsexplorer	string	—	—	—
namenetscape	string	—	—	—
offset	integer	—	—	—
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—

<cfg:deleteObject>with type="CfgTransaction"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—

Name	Type	Description	Default	Values
name	string	—	—	—
subtype	string	—	—	CfgTransactionType
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
name	string	—	—	—
subtype	string	—	—	CfgTransactionType
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—

<cfg:deleteObject>with type="CfgTreatment"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—

Name	Type	Description	Default	Values
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
callactioncode	string	—	—	CfgCallActionCode
callresult	string	—	—	—
dbid	integer	—	—	—
destdndbid	integer	—	—	—
name	string	—	—	—
reactioncode	string	—	—	CfgRecActionCode
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—

<cfg:deleteObject>with type="CfgVoicePrompt"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—

Name	Type	Description	Default	Values
name	string	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
name	string	—	—	—
scriptdbid	integer	—	—	—
state	string	—	—	CfgObjectState
switchdbid	integer	—	—	—
tenantdbid	integer	—	—	—

<cfg:queryObjects>

Child Elements

<cfg:list> <cfg:parameter> <cfg:query>

<cfg:queryObjects> with type="CfgAccessGroup"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—

Name	Type	Description	Default	Values
data	object	—	—	—
tenantdbid	integer	—	—	—
name	string	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
persondbid	integer	—	—	—
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—
dbid	integer	—	—	—
name	string	—	—	—

<cfg:queryObjects>with type="CfgActionCode"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
name	string	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
tenantdbid	integer	—	—	—
dbid	integer	—	—	—
name	string	—	—	—
state	string	—	—	CfgObjectState

<cfg:queryObjects>with type="CfgAgentGroup"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
persondbid	integer	—	—	—
folderid	integer	—	—	—
delegatedbid	integer	—	—	—

Name	Type	Description	Default	Values
delegatetype	string	—	—	CfgObjectType
state	string	—	—	CfgObjectState
name	string	—	—	—
tenantdbid	integer	—	—	—
dbid	integer	—	—	—

<cfg:queryObjects>with type="CfgAgentLogin"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
nopersondbid	integer	—	—	—
logincode	string	—	—	—

Name	Type	Description	Default	Values
state	string	—	—	CfgObjectState
switchdbid	integer	—	—	—
tenantdbid	integer	—	—	—

<cfg:queryObjects>with type="CfgAlarmCondition"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
name	string	—	—	—
state	string	—	—	CfgObjectState

<cfg:queryObjects>with type="CfgApplication"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
subtype	string	—	—	CfgAppType
name	string	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
accountdbid	integer	—	—	—
accounttype	string	—	—	CfgObjectType
appprototypedbid	integer	—	—	—
subtype	string	—	—	CfgAppType
backupserverdbid	integer	—	—	—
dbid	integer	—	—	—
hostdbid	integer	—	—	—
isserver	string	—	—	CfgFlag
name	string	—	—	—

Name	Type	Description	Default	Values
noclientdbid	integer	—	—	—
noswitchdbid	integer	—	—	—
port	integer	—	—	—
primaryserverdbid	integer	—	—	—
samehostandport	integer	—	—	—
serverdbid	integer	—	—	—
startuptype	string	—	—	CfgStartupType
state	string	—	—	CfgObjectState
switchdbid	integer	—	—	—
tenantdbid	integer	—	—	—
version	string	—	—	—

<cfg:queryObjects>with type="CfgAppPrototype"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
subtype	string	—	—	CfgAppType
name	string	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
subtype	string	—	—	CfgAppType
dbid	integer	—	—	—
name	string	—	—	—
state	string	—	—	CfgObjectState
version	string	—	—	—

<cfg:queryObjects>with type="CfgCallingList"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—

Name	Type	Description	Default	Values
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
filterdbid	integer	—	—	—
logtableaccessdbid	integer	—	—	—
name	string	—	—	—
scriptdbid	integer	—	—	—
state	string	—	—	CfgObjectState
tableaccessdbid	integer	—	—	—
tenantdbid	integer	—	—	—
treatmentdbid	integer	—	—	—

<cfg:queryObjects>with type="CfgCampaignGroup"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
campaigndbid	integer	—	—	—
dbid	integer	—	—	—
groupdbid	integer	—	—	—
name	string	—	—	—
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—

<cfg:queryObjects>with type="CfgCampaign"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
name	string	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—

Name	Type	Description	Default	Values
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
callinglistdbid	integer	—	—	—
dbid	integer	—	—	—
groupdbid	integer	—	—	—
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—
name	string	—	—	—

<cfg:queryObjects>with type="CfgDNGroup"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
subtype	string	—	—	CfgDNGroupType
name	string	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—

Name	Type	Description	Default	Values
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
dndbid	integer	—	—	—
subtype	string	—	—	CfgDNGroupType
name	string	—	—	—
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—

<cfg:queryObjects>with type="CfgDN"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
subtype	string	—	—	CfgDNType
name	string	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
association	string	—	—	—

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
number	string	—	—	—
subtype	string	—	—	CfgDNType
groupdbid	integer	—	—	—
ivrdbid	integer	—	—	—
name	string	—	—	—
noplacedbid	integer	—	—	—
placedbid	integer	—	—	—
state	string	—	—	CfgObjectState
switchdbid	integer	—	—	—
tenantdbid	integer	—	—	—

<cfg:queryObjects>with type="CfgEnumerator"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—

Name	Type	Description	Default	Values
subtype	string	—	—	CfgEnumeratorType
name	string	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
displayname	string	—	—	—
subtype	string	—	—	CfgEnumeratorType
name	string	—	—	—
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—

<cfg:queryObjects>with type="CfgEnumeratorValue"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—

Name	Type	Description	Default	Values
name	string	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
defaultvalue	string	—	—	CfgFlag
displayname	string	—	—	—
enumeratordbid	integer	—	—	—
name	string	—	—	—
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—

<cfg:queryObjects>with type="CfgField"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—

Name	Type	Description	Default	Values
name	string	—	—	—
tenantdbid	integer	—	—	—
subtype	string	—	—	CfgDataType

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
fieldtype	string	—	—	CfgFieldType
formatdbid	integer	—	—	—
name	string	—	—	—
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—
subtype	string	—	—	CfgDataType

<cfg:queryObjects>with type="CfgFilter"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—

Name	Type	Description	Default	Values
name	string	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
formatdbid	integer	—	—	—
name	string	—	—	—
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—

<cfg:queryObjects>with type="CfgFolder"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
subtype	string	—	—	CfgObjectType
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
defaultfolder	string	—	—	CfgFolderClass
folderclass	string	—	—	CfgFolderClass
name	string	—	—	—
objectdbid	integer	—	—	—
objecttype	string	—	—	CfgObjectType
ownerdbid	integer	—	—	—
ownertype	string	—	—	CfgObjectType
state	string	—	—	CfgObjectState
subtype	string	—	—	CfgObjectType
tenantdbid	integer	—	—	—

<cfg:queryObjects>with type="CfgFormat"**Attributes**

Name	Type	Description	Default	Values
result	string	—	—	—

Name	Type	Description	Default	Values
data	object	—	—	—
name	string	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
fielddbid	integer	—	—	—
name	string	—	—	—
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—

<cfg:queryObjects>with type="CfgGVPIVRProfile"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—

Name	Type	Description	Default	Values
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
dbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
name	string	—	—	—
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—

<cfg:queryObjects>with type="CfgHost"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
subtype	string	—	—	CfgHostType
name	string	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
subtype	string	—	—	CfgHostType
name	string	—	—	—
ostype	string	—	—	CfgOSType
scsdbid	integer	—	—	—
state	string	—	—	CfgObjectState

<cfg:queryObjects>with type="CfgIVRPort"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—

Name	Type	Description	Default	Values
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
dndbid	integer	—	—	—
ivrdbid	integer	—	—	—
portnumber	string	—	—	—
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—

<cfg:queryObjects>with type="CfgIVR"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
tenantdbid	integer	—	—	—
subtype	string	—	—	CfgIVRType

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—

Name	Type	Description	Default	Values
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
ivrserverdbid	integer	—	—	—
name	string	—	—	—
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—
subtype	string	—	—	CfgIVRType

<cfg:queryObjects>with type="CfgObjectiveTable"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType

Name	Type	Description	Default	Values
dbid	integer	—	—	—
name	string	—	—	—
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—

<cfg:queryObjects>with type="CfgPerson"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
name	string	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
employeeid	string	—	—	—
firstname	string	—	—	—

Name	Type	Description	Default	Values
isagent	string	—	—	CfgFlag
lastname	string	—	—	—
logindbid	integer	—	—	—
nologindbid	integer	—	—	—
noplacedbid	integer	—	—	—
skilldbid	integer	—	—	—
state	string	—	—	CfgObjectState
switchdbid	integer	—	—	—
tenantdbid	integer	—	—	—
username	string	—	—	—
name	string	—	—	—

<cfg:queryObjects>with type="CfgPhysicalSwitch"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
folderdbid	integer	—	—	—
name	string	—	—	—
state	string	—	—	CfgObjectState

<cfg:queryObjects>with type="CfgPlaceGroup"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType

Name	Type	Description	Default	Values
dbid	integer	—	—	—
name	string	—	—	—
placedbid	integer	—	—	—
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—

<cfg:queryObjects>with type="CfgPlace"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
dndbid	integer	—	—	—

Name	Type	Description	Default	Values
groupdbid	integer	—	—	—
name	string	—	—	—
nodndbid	integer	—	—	—
persondbid	integer	—	—	—
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—

<cfg:queryObjects>with type="CfgRole"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—

Name	Type	Description	Default	Values
name	string	—	—	—
state	string	—	—	CfgObjectState
rbacappns	string	—	—	—
tenantdbid	integer	—	—	—

<cfg:queryObjects>with type="CfgScript"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
subtype	string	—	—	CfgScriptType
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
capacityagentdbid	integer	—	—	—
capacityagentgroupdbid	integer	—	—	—

Name	Type	Description	Default	Values
capacityplacedbid	integer	—	—	—
capacityplacegroupdbid	integer	—	—	—
capacitytenantdbid	integer	—	—	—
dbid	integer	—	—	—
excludebytecode	string	—	—	CfgFlag
excludelongstrings	string	—	—	CfgFlag
name	string	—	—	—
subtype	string	—	—	CfgScriptType
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—

<cfg:queryObjects>with type="CfgService"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
tenantdbid	integer	—	—	—
subtype	string	—	—	CfgSolutionType

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
folderdbid	integer	—	—	—
name	string	—	—	—
scsdbid	integer	—	—	—
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—
subtype	string	—	—	CfgSolutionType

<cfg:queryObjects>with type="CfgSkill"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
name	string	—	—	—
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—

<cfg:queryObjects>with type="CfgStatDay"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
subtype	string	—	—	CfgStatDayType
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—

Name	Type	Description	Default	Values
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
name	string	—	—	—
subtype	string	—	—	CfgStatDayType
state	string	—	—	CfgObjectState
tabledbid	integer	—	—	—
tenantdbid	integer	—	—	—

<cfg:queryObjects>with type="CfgStatTable"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
subtype	string	—	—	CfgStatTableType
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—

Name	Type	Description	Default	Values
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
groupdbid	integer	—	—	—
name	string	—	—	—
statdaydbid	integer	—	—	—
state	string	—	—	CfgObjectState
subtype	string	—	—	CfgStatTableType
tenantdbid	integer	—	—	—

<cfg:queryObjects>with type="CfgSwitch"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—

Name	Type	Description	Default	Values
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
name	string	—	—	—
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—
tserverdbid	integer	—	—	—

<cfg:queryObjects>with type="CfgTableAccess"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
tenantdbid	integer	—	—	—
subtype	string	—	—	CfgTableType

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType

Name	Type	Description	Default	Values
dbaccessdbid	integer	—	—	—
dbid	integer	—	—	—
dbtablename	string	—	—	—
formatdbid	integer	—	—	—
name	string	—	—	—
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—
subtype	string	—	—	CfgTableType

<cfg:queryObjects>with type="CfgTenant"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType

Name	Type	Description	Default	Values
alltenants	string	If included, regardless of value, returns the root tenant in the resultset. If excluded, the root tenant is not returned in the resultset.	—	CfgFlag
dbid	integer	—	—	—
name	string	—	—	—
state	string	—	—	CfgObjectState

<cfg:queryObjects>with type="CfgTimeZone"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—

Name	Type	Description	Default	Values
name	string	—	—	—
namemsexplorer	string	—	—	—
namenetscape	string	—	—	—
offset	integer	—	—	—
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—

<cfg:queryObjects>with type="CfgTransaction"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
subtype	string	—	—	CfgTransactionType
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType

Name	Type	Description	Default	Values
dbid	integer	—	—	—
name	string	—	—	—
subtype	string	—	—	CfgTransactionType
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—

<cfg:queryObjects>with type="CfgTreatment"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
callactioncode	string	—	—	CfgCallActionCode
callresult	string	—	—	—

Name	Type	Description	Default	Values
dbid	integer	—	—	—
destdndbid	integer	—	—	—
name	string	—	—	—
reactioncode	string	—	—	CfgRecActionCode
state	string	—	—	CfgObjectState
tenantdbid	integer	—	—	—

<cfg:queryObjects>with type="CfgVoicePrompt"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
tenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—

Name	Type	Description	Default	Values
name	string	—	—	—
scriptdbid	integer	—	—	—
state	string	—	—	CfgObjectState
switchdbid	integer	—	—	—
tenantdbid	integer	—	—	—

<cfg:kvitem>

Attributes

Name	Type	Description	Default	Values
data	object	—	—	—
key	string (required)	—	—	—
result	string	—	—	—
value	string (required)	—	—	—

<cfg:updateAppLogOnAs>

Attributes

Name	Type	Description	Default	Values
appdbid	integer (required)	—	—	—
data	object	—	—	—
persondbid	integer (required)	—	—	—
result	string	—	—	—