



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Genesys Administrator Extension Deployment Guide

[clog Section](#)

clog Section

Contents

- [1 clog Section](#)
 - [1.1 maxlogs](#)
 - [1.2 minlogs](#)

This section contains configuration options for configuring the display of log records from the Centralized log.

maxlogs

Default Value: 5000

Valid Values: Any positive integer starting at 5000

Changes Take Effect: After the browser page is refreshed

Specifies the maximum number of log records that can be displayed in GAX. When the user scrolls down or pages through to the end of the list, GAX displays a message suggesting that the user refine the search criteria to get better results. If this option is not set or set to a value less than 5000 (the default), the default is used. When used with the **minlogs** option, the rules in the following table might apply:

Configured Values	Value used for maxlogs	Value used for minlogs
minlogs < 5000 maxlogs < 5000 minlogs > maxlogs	5000 or the configured value of maxlogs , whichever is greater	100 or the configured value of minlogs , whichever is greater
minlogs >= 5000 maxlogs >= 5000 minlogs > maxlogs	Configured value of minlogs	Configured value of minlogs

minlogs

Default Value: 100

Valid Values: Any positive integer starting at 100

Changes Take Effect: After the browser page is refreshed

Specifies the number of log records that are to be retrieved from the Centralized Log Database when the user scrolls down or pages through the list of logs. If not set or set to a value less than 100 (the default), the default is used. When used with the **maxlogs** option, the rules in the **table** above might apply.