



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Genesys Administrator Extension Developer's Guide

<cfg:updateObject>

<cfg:updateObject>

Use <cfg:updateObject> to update a configuration object. If you are not sure that the object you want to update already exists, use attribute createonupdate="true".

Contents

- 1 <cfg:updateObject>
 - 1.1 Child Elements
 - 1.2 <cfg:updateObject> with type="CfgActionCode"
 - 1.3 <cfg:updateObject> with type="CfgAccessGroup"
 - 1.4 <cfg:updateObject> with type="CfgAgentGroup"
 - 1.5 <cfg:updateObject> with type="CfgAgentLogin"
 - 1.6 <cfg:updateObject> with type="CfgAlarmCondition"
 - 1.7 <cfg:updateObject> with type="CfgApplication"
 - 1.8 <cfg:updateObject> with type="CfgAppPrototype"
 - 1.9 <cfg:updateObject> with type="CfgCallingList"
 - 1.10 <cfg:updateObject> with type="CfgCampaign"
 - 1.11 <cfg:updateObject> with type="CfgCampaignGroup"
 - 1.12 <cfg:updateObject> with type="CfgDN"
 - 1.13 <cfg:updateObject> with type="CfgDNGroup"
 - 1.14 <cfg:updateObject> with type="CfgEnumerator"
 - 1.15 <cfg:updateObject> with type="CfgEnumeratorValue"
 - 1.16 <cfg:updateObject> with type="CfgField"
 - 1.17 <cfg:updateObject> with type="CfgFilter"
 - 1.18 <cfg:updateObject> with type="CfgFolder"
 - 1.19 <cfg:updateObject> with type="CfgFormat"
 - 1.20 <cfg:updateObject> with type="CfgGVPIVRProfile"
 - 1.21 <cfg:updateObject> with type="CfgHost"
 - 1.22 <cfg:updateObject> with type="CfgIVR"
 - 1.23 <cfg:updateObject> with type="CfgIVRPort"
 - 1.24 <cfg:updateObject> with type="CfgObjectiveTable"
 - 1.25 <cfg:updateObject> with type="CfgPerson"

- 1.26 <cfg:updateObject> with type="CfgPhysicalSwitch"
- 1.27 <cfg:updateObject> with type="CfgPlace"
- 1.28 <cfg:updateObject> with type="CfgPlaceGroup"
- 1.29 <cfg:updateObject> with type="CfgRole"
- 1.30 <cfg:updateObject> with type="CfgScript"
- 1.31 <cfg:updateObject> with type="CfgService"
- 1.32 <cfg:updateObject> with type="CfgSkill"
- 1.33 <cfg:updateObject> with type="CfgStatDay"
- 1.34 <cfg:updateObject> with type="CfgStatTable"
- 1.35 <cfg:updateObject> with type="CfgSwitch"
- 1.36 <cfg:updateObject> with type="CfgTableAccess"
- 1.37 <cfg:updateObject> with type="CfgTenant"
- 1.38 <cfg:updateObject> with type="CfgTimeZone"
- 1.39 <cfg:updateObject> with type="CfgTransaction"
- 1.40 <cfg:updateObject> with type="CfgTreatment"
- 1.41 <cfg:updateObject> with type="CfgVoicePrompt" </t>

<cfg:updateObject>

Child Elements

- <cfg:list>
- <cfg:parameter>
- <cfg:query>

<cfg:updateObject> with **type="CfgActionCode"**

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
name	string	—	—	—
subtype	string	—	—	CfgActionCodeType
createonupdate	Boolean	—	—	—
mode	string	—	—	merge, clear

Supported List Names

Name	Type	Description	Default	Values
userproperties	<cfg:property>	—	—	—
subcodes	<cfg:subcode>	—	—	—
accountpermissions	<cfg:permission>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
state	string	—	—	CfgObjectState

Supported Query Names

Name	Type	Description	Default	Values
type	string	—	—	SupportedTypes
folderid	integer	—	—	—
tenantdbid	integer	—	—	—

<cfg:updateObject>

Name	Type	Description	Default	Values
name	string	—	—	—
state	string	—	—	CfgObjectState
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—

<cfg:updateObject> with type="CfgAccessGroup"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
name	string	—	—	—
subtype	string	—	—	CfgAccessGroupType
createonupdate	Boolean	—	—	—
mode	string	—	—	merge, clear

Supported List Names

Name	Type	Description	Default	Values
managerdbids	<cfg:id>	—	—	—
userproperties	<cfg:property>	—	—	—
routednbbids	<cfg:id>	—	—	—
accountpermissions	<cfg:permission>	—	—	—
memberids	<cfg:idtype>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
sitedbid	integer	—	—	—
quotatabledbid	integer	—	—	—
contractdbid	integer	—	—	—
capacityruledbid	integer	—	—	—
capacitytabledbid	integer	—	—	—

<cfg:updateObject>

Supported Query Names

Name	Type	Description	Default	Values
type	string	—	—	SupportedTypes
tenantdbid	integer	—	—	—
state	string	—	—	CfgObjectState
name	string	—	—	—
persondbid	integer	—	—	—
dbid	integer	—	—	—

<cfg:updateObject> with **type="CfgAgentGroup"**

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
name	string	—	—	—
createonupdate	Boolean	—	—	—
mode	string	—	—	merge, clear

Supported List Names

Name	Type	Description	Default	Values
agentdbids	<cfg:id>	—	—	—
managerdbids	<cfg:id>	—	—	—
userproperties	<cfg:property>	—	—	—
routednbids	<cfg:id>	—	—	—
accountpermissions	<cfg:permission>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
sitedbid	integer	—	—	—
quotatabdbid	integer	—	—	—
contractdbid	integer	—	—	—
capacityruledbid	integer	—	—	—

<cfg:updateObject>

Name	Type	Description	Default	Values
capacitytabledbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
type	string	—	—	SupportedTypes
folderid	integer	—	—	—
tenantdbid	integer	—	—	—
state	string	—	—	CfgObjectState
name	string	—	—	—
persondbid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—

<cfg:updateObject> with type="CfgAgentLogin"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
createonupdate	Boolean	—	—	—
mode	string	—	—	merge, clear

Supported List Names

Name	Type	Description	Default	Values
accountpermissions	<cfg:permission>	—	—	—
userproperties	<cfg:property>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
switchdbid	integer	—	—	—
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
password	string	—	—	—

<cfg:updateObject>

Name	Type	Description	Default	Values
switchspecificitytype	integer	—	—	—
override	string	—	—	—
logincode	string	—	—	—
useoverride	string	—	—	CfgFlag

Supported Query Names

Name	Type	Description	Default	Values
type	string	—	—	SupportedTypes
switchdbid	integer	—	—	—
tenantdbid	integer	—	—	—
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
logincode	string	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
nopersondbid	integer	—	—	—

<cfg:updateObject> with type="CfgAlarmCondition"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
createonupdate	Boolean	—	—	—
mode	string	—	—	merge, clear

Supported List Names

Name	Type	Description	Default	Values
reactionscripodbids	<cfg:id>	—	—	—
accountpermissions	<cfg:permission>	—	—	—
clearancescripodbids	<cfg:id>	—	—	—
userproperties	<cfg:property>	—	—	—

Supported Parameter Names

<cfg:updateObject>

Name	Type	Description	Default	Values
appdbid	integer	—	—	—
apptype	string	—	—	CfgAppType
selectionmode	string	—	—	CfgSelectionMode
alarmdetectlogeventid	integer	—	—	—
alarmdetectscriptdbid	integer	—	—	—
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
clearancetimeout	integer	—	—	—
category	string	—	—	CfgAlarmCategory
description	string	—	—	—
ismasked	string	—	—	CfgFlag
alarmremovallogeventid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
type	string	—	—	SupportedTypes
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
name	string	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—

<cfg:updateObject> with type="CfgApplication"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
subtype	string	—	—	CfgAppType
name	string	—	—	—
tenantdbid	integer	—	—	—
createonupdate	Boolean	—	—	—
mode	string	—	—	merge, clear

Supported List Names

<cfg:updateObject>

Name	Type	Description	Default	Values
resources	<cfg:resource>	—	—	—
appservers	<cfg:conninfo>	—	—	—
portinfos	<cfg:portinfo>	—	—	—
userproperties	<cfg:property>	—	—	—
tenantdbids	<cfg:id>	—	—	—
options	<cfg:property>	—	—	—
accountpermissions	<cfg:permission>	—	—	—
flexibleproperties	<cfg:property>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
port	string	—	—	—
backupserverdbid	integer	—	—	—
attempts	integer	—	—	—
hostdbid	integer	—	—	—
timeout	integer	—	—	—
commandline	string	—	—	—
state	string	—	—	CfgObjectState
appprototypedbid	integer	—	—	—
password	string	—	—	—
shutdowntimeout	integer	—	—	—
version	string	—	—	—
workdirectory	string	—	—	—
redundancytype	string	—	—	CfgHAType
componenttype	string	—	—	CfgAppComponentType
folderid	integer	—	—	—
isprimary	string	—	—	CfgFlag
startuptimeout	integer	—	—	—
commandlinearguments	string	—	—	—
autorestart	string	—	—	CfgFlag

Supported Query Names

Name	Type	Description	Default	Values
type	string	—	—	SupportedTypes
port	string	—	—	—
backupserverdbid	integer	—	—	—
hostdbid	integer	—	—	—

<cfg:updateObject>

Name	Type	Description	Default	Values
state	string	—	—	CfgObjectState
appprototypedbid	integer	—	—	—
subtype	string	—	—	CfgAppType
version	string	—	—	—
name	string	—	—	—
folderid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
accountdbid	integer	—	—	—
accounttype	string	—	—	CfgObjectType
dbid	integer	—	—	—
isserver	string	—	—	CfgFlag
noclientdbid	integer	—	—	—
noswitchdbid	integer	—	—	—
primaryserverdbid	integer	—	—	—
samehostandport	integer	—	—	—
serverdbid	integer	—	—	—
startuptype	string	—	—	CfgStartupType
switchdbid	integer	—	—	—
tenantdbid	integer	—	—	—

<cfg:updateObject> with **type="CfgAppPrototype"**

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
subtype	string	—	—	CfgAppType
createonupdate	Boolean	—	—	—
mode	string	—	—	merge, clear

Supported List Names

Name	Type	Description	Default	Values
userproperties	<cfg:property>	—	—	—
accountpermissions	<cfg:permission>	—	—	—

<cfg:updateObject>

Name	Type	Description	Default	Values
options	<cfg:property>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
version	string	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
type	string	—	—	SupportedTypes
folderid	integer	—	—	—
name	string	—	—	—
state	string	—	—	CfgObjectState
subtype	string	—	—	CfgAppType
version	string	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—

<cfg:updateObject> with type="CfgCallingList"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
name	string	—	—	—
createonupdate	Boolean	—	—	—
mode	string	—	—	merge, clear

Supported List Names

Name	Type	Description	Default	Values
accountpermissions	<cfg:permission>	—	—	—
treatmentdbids	<cfg:id>	—	—	—

<cfg:updateObject>

Name	Type	Description	Default	Values
userproperties	<cfg:property>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
maxattempts	integer	—	—	—
filterdbid	integer	—	—	—
folderid	integer	—	—	—
scriptdbid	integer	—	—	—
timeuntil	integer	—	—	—
state	string	—	—	CfgObjectState
tableaccessdbid	integer	—	—	—
description	string	—	—	—
logtableaccessdbid	integer	—	—	—
timefrom	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
type	string	—	—	SupportedTypes
filterdbid	integer	—	—	—
folderid	integer	—	—	—
scriptdbid	integer	—	—	—
tenantdbid	integer	—	—	—
state	string	—	—	CfgObjectState
tableaccessdbid	integer	—	—	—
name	string	—	—	—
logtableaccessdbid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
treatmentdbid	integer	—	—	—

<cfg:updateObject> with **type**="CfgCampaign"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—

<cfg:updateObject>

Name	Type	Description	Default	Values
data	object	—	—	—
tenantdbid	integer	—	—	—
name	string	—	—	—
createonupdate	Boolean	—	—	—
mode	string	—	—	merge, clear

Supported List Names

Name	Type	Description	Default	Values
callinglists	<cfg:callinglistinfo>	—	—	—
accountpermissions	<cfg:permission>	—	—	—
userproperties	<cfg:property>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
scriptdbid	integer	—	—	—
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
description	string	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
type	string	—	—	SupportedTypes
tenantdbid	integer	—	—	—
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
name	string	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
callinglistdbid	integer	—	—	—
dbid	integer	—	—	—
groupdbid	integer	—	—	—

<cfg:updateObject> with **type**="CfgCampaignGroup"

Attributes

<cfg:updateObject>

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
tenantdbid	integer	—	—	—
subtype	string	—	—	CfgObjectType
createonupdate	Boolean	—	—	—
mode	string	—	—	merge, clear

Supported List Names

Name	Type	Description	Default	Values
userproperties	<cfg:property>	—	—	—
serverdbids	<cfg:id>	—	—	—
accountpermissions	<cfg:permission>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
scriptdbid	integer	—	—	—
state	string	—	—	CfgObjectState
optmethodvalue	integer	—	—	—
numofchannels	integer	—	—	—
interactionqueuedbid	integer	—	—	—
description	string	—	—	—
minrecbuffsize	integer	—	—	—
groupdbid	integer	—	—	—
optmethod	string	—	—	CfgOptimizationMethod
origdndbid	integer	—	—	—
folderid	integer	—	—	—
dialmode	string	—	—	CfgDialMode
operationmode	string	—	—	CfgOperationMode
optrecbuffsize	integer	—	—	—
ivrprofiledbid	integer	—	—	—
campaigndbid	integer	—	—	—
trunkgroupdndbid	integer	—	—	—
maxqueue size	integer	—	—	—

Supported Query Names

<cfg:updateObject>

Name	Type	Description	Default	Values
type	string	—	—	SupportedTypes
state	string	—	—	CfgObjectState
name	string	—	—	—
groupdbid	integer	—	—	—
folderid	integer	—	—	—
tenantdbid	integer	—	—	—
campaigndbid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—

<cfg:updateObject> with type="CfgDN"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
subtype	string	—	—	CfgDNType
name	string	—	—	—
tenantdbid	integer	—	—	—
createonupdate	Boolean	—	—	—
mode	string	—	—	merge, clear

Supported List Names

Name	Type	Description	Default	Values
userproperties	<cfg:property>	—	—	—
destdndbids	<cfg:id>	—	—	—
accountpermissions	<cfg:permission>	—	—	—
accessnumbers	<cfg:dnaccessnumber>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
registerall	string	—	—	CfgDNRegisterFlag
state	string	—	—	CfgObjectState
contractdbid	integer	—	—	—
routetype	string	—	—	CfgRouteType

<cfg:updateObject>

Name	Type	Description	Default	Values
trunks	integer	—	—	—
groupdbid	integer	—	—	—
switchdbid	integer	—	—	—
folderid	integer	—	—	—
association	string	—	—	—
number	string	—	—	—
sitedbid	integer	—	—	—
switchspecificitytype	integer	—	—	—
override	string	—	—	—
useoverride	string	—	—	CfgFlag
dnloginid	string	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
type	string	—	—	SupportedTypes
state	string	—	—	CfgObjectState
subtype	string	—	—	CfgDNType
name	string	—	—	—
groupdbid	integer	—	—	—
switchdbid	integer	—	—	—
folderid	integer	—	—	—
association	string	—	—	—
tenantdbid	integer	—	—	—
number	string	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
ivrbid	integer	—	—	—
noplacedbid	integer	—	—	—
placedbid	integer	—	—	—

<cfg:updateObject> with **type="CfgDNGroup"**

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—

<cfg:updateObject>

Name	Type	Description	Default	Values
data	object	—	—	—
tenantdbid	integer	—	—	—
name	string	—	—	—
subtype	string	—	—	CfgDNGroupType
createonupdate	Boolean	—	—	—
mode	string	—	—	merge, clear

Supported List Names

Name	Type	Description	Default	Values
dns	<cfg:dninfo>	—	—	—
managerdbids	<cfg:id>	—	—	—
userproperties	<cfg:property>	—	—	—
routednbbids	<cfg:id>	—	—	—
accountpermissions	<cfg:permission>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
sitedbid	integer	—	—	—
quotatabledbid	integer	—	—	—
contractdbid	integer	—	—	—
capacityruledbid	integer	—	—	—
capacitytabledbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
type	string	—	—	SupportedTypes
folderid	integer	—	—	—
tenantdbid	integer	—	—	—
state	string	—	—	CfgObjectState
name	string	—	—	—
subtype	string	—	—	CfgDNGroupType
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
dndbid	integer	—	—	—

<cfg:updateObject>

<cfg:updateObject> with **type**="CfgEnumerator"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
name	string	—	—	—
subtype	string	—	—	CfgEnumeratorType
createonupdate	Boolean	—	—	—
mode	string	—	—	merge, clear

Supported List Names

Name	Type	Description	Default	Values
userproperties	<cfg:property>	—	—	—
accountpermissions	<cfg:permission>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
description	string	—	—	—
state	string	—	—	CfgObjectState
displayname	string	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
type	string	—	—	SupportedTypes
folderid	integer	—	—	—
tenantdbid	integer	—	—	—
name	string	—	—	—
state	string	—	—	CfgObjectState
subtype	string	—	—	CfgEnumeratorType
displayname	string	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—

<cfg:updateObject>

<cfg:updateObject> with **type**="CfgEnumeratorValue"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
name	string	—	—	—
createonupdate	Boolean	—	—	—
mode	string	—	—	merge, clear

Supported List Names

Name	Type	Description	Default	Values
accountpermissions	<cfg:permission>	—	—	—
userproperties	<cfg:property>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
enumeratordbid	integer	—	—	—
isdefault	string	—	—	CfgFlag
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
description	string	—	—	—
displayname	string	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
type	string	—	—	SupportedTypes
enumeratordbid	integer	—	—	—
tenantdbid	integer	—	—	—
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
name	string	—	—	—
displayname	string	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—

<cfg:updateObject>

Name	Type	Description	Default	Values
defaultvalue	string	—	—	CfgFlag

<cfg:updateObject> with type="CfgField"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—

<cfg:updateObject> with type="CfgFilter"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
name	string	—	—	—
createonupdate	Boolean	—	—	—
mode	string	—	—	merge, clear

Supported List Names

Name	Type	Description	Default	Values
userproperties	<cfg:property>	—	—	—
accountpermissions	<cfg:permission>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
description	string	—	—	—
state	string	—	—	CfgObjectState
formatdbid	integer	—	—	—

Supported Query Names

<cfg:updateObject>

Name	Type	Description	Default	Values
type	string	—	—	SupportedTypes
folderid	integer	—	—	—
tenantdbid	integer	—	—	—
name	string	—	—	—
state	string	—	—	CfgObjectState
formatdbid	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType

<cfg:updateObject> with type="CfgFolder"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
subtype	string	—	—	CfgObjectType
name	string	—	—	—
tenantdbid	integer	—	—	—
createonupdate	Boolean	—	—	—
mode	string	—	—	merge, clear

Supported List Names

Name	Type	Description	Default	Values
resources	<cfg:resource>	—	—	—
accountpermissions	<cfg:permission>	—	—	—
userproperties	<cfg:property>	—	—	—
objectids	<cfg:idtype>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
ownerdbid	integer	—	—	—
ownertype	string	—	—	CfgObjectType
customtype	integer	—	—	—
description	string	—	—	—

<cfg:updateObject>

Name	Type	Description	Default	Values
folderclass	string	—	—	CfgFolderClass

Supported Query Names

Name	Type	Description	Default	Values
type	string	—	—	SupportedTypes
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
ownerdbid	integer	—	—	—
ownertype	string	—	—	CfgObjectType
subtype	string	—	—	CfgObjectType
name	string	—	—	—
folderclass	string	—	—	CfgFolderClass
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
defaultfolder	string	—	—	CfgFolderClass
objectdbid	integer	—	—	—
objecttype	string	—	—	CfgObjectType
tenantdbid	integer	—	—	—

<cfg:updateObject> with **type="CfgFormat"**

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
name	string	—	—	—
createonupdate	Boolean	—	—	—
mode	string	—	—	merge, clear

Supported List Names

Name	Type	Description	Default	Values
userproperties	<cfg:property>	—	—	—
accountpermissions	<cfg:permission>	—	—	—
fielddbids	<cfg:id>	—	—	—

<cfg:updateObject>

Supported Parameter Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
description	string	—	—	—
state	string	—	—	CfgObjectState

Supported Query Names

Name	Type	Description	Default	Values
type	string	—	—	SupportedTypes
folderid	integer	—	—	—
tenantdbid	integer	—	—	—
name	string	—	—	—
state	string	—	—	CfgObjectState
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
fielddbid	integer	—	—	—

<cfg:updateObject> with type="CfgGVPIVRProfile"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
subtype	string	—	—	CfgIVRProfileType
name	string	—	—	—
createonupdate	Boolean	—	—	—
mode	string	—	—	merge, clear

Supported List Names

Name	Type	Description	Default	Values
resources	<cfg:resource>	—	—	—
diddbids	<cfg:id>	—	—	—
accountpermissions	<cfg:permission>	—	—	—
userproperties	<cfg:property>	—	—	—

<cfg:updateObject>

Supported Parameter Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
description	string	—	—	—
notes	string	—	—	—
displayname	string	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
type	string	—	—	SupportedTypes
folderid	integer	—	—	—
tenantdbid	integer	—	—	—
state	string	—	—	CfgObjectState
name	string	—	—	—
delegatedbid	integer	—	—	—
dbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType

<cfg:updateObject> with type="CfgHost"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
subtype	string	—	—	CfgHostType
name	string	—	—	—
createonupdate	Boolean	—	—	—
mode	string	—	—	merge, clear

Supported List Names

Name	Type	Description	Default	Values
resources	<cfg:resource>	—	—	—
accountpermissions	<cfg:permission>	—	—	—
userproperties	<cfg:property>	—	—	—

Supported Parameter Names

<cfg:updateObject>

Name	Type	Description	Default	Values
folderid	integer	—	—	—
lcaport	string	—	—	—
state	string	—	—	CfgObjectState
ipaddress	string	—	—	—
ostype	string	—	—	CfgOSType
osversion	string	—	—	—
scsdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
type	string	—	—	SupportedTypes
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
subtype	string	—	—	CfgHostType
ostype	string	—	—	CfgOSType
scsdbid	integer	—	—	—
name	string	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—

<cfg:updateObject> with type="CfgIVR"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
subtype	string	—	—	CfgIVRType
name	string	—	—	—
createonupdate	Boolean	—	—	—
mode	string	—	—	merge, clear

Supported List Names

Name	Type	Description	Default	Values
accountpermissions	<cfg:permission>	—	—	—

<cfg:updateObject>

Name	Type	Description	Default	Values
userproperties	<cfg:property>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
ivrserverdbid	integer	—	—	—
version	string	—	—	—
description	string	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
type	string	—	—	SupportedTypes
tenantdbid	integer	—	—	—
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
subtype	string	—	—	CfgIVRType
ivrserverdbid	integer	—	—	—
name	string	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—

<cfg:updateObject> with **type**="CfgIVRPort"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
createonupdate	Boolean	—	—	—
mode	string	—	—	merge, clear

Supported List Names

<cfg:updateObject>

Name	Type	Description	Default	Values
accountpermissions	<cfg:permission>	—	—	—
userproperties	<cfg:property>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
dndbid	integer	—	—	—
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
ivrdbid	integer	—	—	—
portnumber	string	—	—	—
description	string	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
type	string	—	—	SupportedTypes
tenantdbid	integer	—	—	—
dndbid	integer	—	—	—
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
ivrdbid	integer	—	—	—
portnumber	string	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—

<cfg:updateObject> with **type="CfgObjectiveTable"**

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
subtype	string	—	—	CfgObjectiveTableType
name	string	—	—	—
createonupdate	Boolean	—	—	—
mode	string	—	—	merge, clear

<cfg:updateObject>

Supported List Names

Name	Type	Description	Default	Values
accountpermissions	<cfg:permission>	—	—	—
objectiverecords	<cfg:objectivetablerecord>	—	—	—
userproperties	<cfg:property>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
timezonedbid	integer	—	—	—
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
prepaidcost	integer	—	—	—
description	string	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
type	string	—	—	SupportedTypes
folderid	integer	—	—	—
tenantdbid	integer	—	—	—
state	string	—	—	CfgObjectState
name	string	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—

<cfg:updateObject> with type="CfgPerson"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
name	string	—	—	—
createonupdate	Boolean	—	—	—
mode	string	—	—	merge, clear

Supported List Names

<cfg:updateObject>

Name	Type	Description	Default	Values
accountpermissions	<cfg:permission>	—	—	—
userproperties	<cfg:property>	—	—	—
skilllevels	<cfg:skilllevel>	—	—	—
agentlogins	<cfg:agentlogininfo>	—	—	—
appranks	<cfg:apprank>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
employeeid	string	—	—	—
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
lastname	string	—	—	—
firstname	string	—	—	—
password	string	—	—	—
isagent	string	—	—	CfgFlag
placedbid	integer	—	—	—
capacityruledbid	integer	—	—	—
sitedbid	integer	—	—	—
contractdbid	integer	—	—	—
username	string	—	—	—
externalid	string	—	—	—
emailaddress	string	—	—	—
isexternalauth	string	—	—	CfgFlag

Supported Query Names

Name	Type	Description	Default	Values
type	string	—	—	SupportedTypes
employeeid	string	—	—	—
folderid	integer	—	—	—
tenantdbid	integer	—	—	—
state	string	—	—	CfgObjectState
lastname	string	—	—	—
firstname	string	—	—	—
isagent	string	—	—	CfgFlag
username	string	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType

<cfg:updateObject>

Name	Type	Description	Default	Values
dbid	integer	—	—	—
logindbid	integer	—	—	—
nologindbid	integer	—	—	—
noplacedbid	integer	—	—	—
skilldbdbid	integer	—	—	—
switchdbdbid	integer	—	—	—
name	string	—	—	—

<cfg:updateObject> with **type="CfgPhysicalSwitch"**

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
subtype	string	—	—	CfgSwitchType
createonupdate	Boolean	—	—	—
mode	string	—	—	merge, clear

Supported List Names

Name	Type	Description	Default	Values
userproperties	<cfg:property>	—	—	—
accountpermissions	<cfg:permission>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
state	string	—	—	CfgObjectState

Supported Query Names

Name	Type	Description	Default	Values
type	string	—	—	SupportedTypes
folderid	integer	—	—	—
name	string	—	—	—
state	string	—	—	CfgObjectState

<cfg:updateObject>

Name	Type	Description	Default	Values
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
folderdbid	integer	—	—	—

<cfg:updateObject> with type="CfgPlace"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
name	string	—	—	—
createonupdate	Boolean	—	—	—
mode	string	—	—	merge, clear

Supported List Names

Name	Type	Description	Default	Values
dndbids	<cfg:id>	—	—	—
accountpermissions	<cfg:permission>	—	—	—
userproperties	<cfg:property>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
sitedbid	integer	—	—	—
contractdbid	integer	—	—	—
capacityruledbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
type	string	—	—	SupportedTypes
folderid	integer	—	—	—
tenantdbid	integer	—	—	—

<cfg:updateObject>

Name	Type	Description	Default	Values
state	string	—	—	CfgObjectState
name	string	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
dndbid	integer	—	—	—
groupdbid	integer	—	—	—
nodndbid	integer	—	—	—
persondbid	integer	—	—	—

<cfg:updateObject> with type="CfgPlaceGroup"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
name	string	—	—	—
createonupdate	Boolean	—	—	—
mode	string	—	—	merge, clear

Supported List Names

Name	Type	Description	Default	Values
placedbids	<cfg:id>	—	—	—
managerdbids	<cfg:id>	—	—	—
userproperties	<cfg:property>	—	—	—
routedndbids	<cfg:id>	—	—	—
accountpermissions	<cfg:permission>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
sitedbid	integer	—	—	—
quotatablebid	integer	—	—	—
contractdbid	integer	—	—	—

<cfg:updateObject>

Name	Type	Description	Default	Values
capacityruledbid	integer	—	—	—
capacitytabledbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
type	string	—	—	SupportedTypes
folderid	integer	—	—	—
tenantdbid	integer	—	—	—
state	string	—	—	CfgObjectState
name	string	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
placedbid	integer	—	—	—

<cfg:updateObject> with type="CfgRole"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
name	string	—	—	—
createonupdate	Boolean	—	—	—
mode	string	—	—	merge, clear

Supported List Names

<cfg:updateObject>

Name	Type	Description	Default	Values
userproperties	<cfg:property>	—	—	—
accountpermissions	<cfg:permission>	—	—	—
members	<cfg:idtype>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
description	string	—	—	—
state	string	—	—	CfgObjectState

Supported Query Names

Name	Type	Description	Default	Values
type	string	—	—	SupportedTypes
folderid	integer	—	—	—
tenantdbid	integer	—	—	—
name	string	—	—	—
state	string	—	—	CfgObjectState
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
rbacappns	string	—	—	—

<cfg:updateObject>

<cfg:updateObject> with **type="CfgScript"**

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
name	string	—	—	—
subtype	string	—	—	CfgScriptType
createonupdate	Boolean	—	—	—
mode	string	—	—	merge, clear

Supported List Names

Name	Type	Description	Default	Values
userproperties	<cfg:property>	—	—	—
resources	<cfg:resource>	—	—	—
accountpermissions	<cfg:permission>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
index	integer	—	—	—
folderid	integer	—	—	—
state	string	—	—	CfgObjectState

<cfg:updateObject>

Supported Query Names

Name	Type	Description	Default	Values
type	string	—	—	SupportedTypes
folderid	integer	—	—	—
tenantdbid	integer	—	—	—
name	string	—	—	—
state	string	—	—	CfgObjectState
subtype	string	—	—	CfgScriptType
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
capacityagentdbid	integer	—	—	—
capacityagentgroupdbid	integer	—	—	—
capacityplacedbid	integer	—	—	—
capacityplacegroupdbid	integer	—	—	—
capacitytenantdbid	integer	—	—	—
dbid	integer	—	—	—
excludebytecode	string	—	—	CfgFlag
excludelongstrings	string	—	—	CfgFlag

<cfg:updateObject> with **type="CfgService"**

Attributes

<cfg:updateObject>

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
subtype	string	—	—	CfgSolutionType
name	string	—	—	—
tenantdbid	integer	—	—	—
createonupdate	Boolean	—	—	—
mode	string	—	—	merge, clear

Supported List Names

Name	Type	Description	Default	Values
resources	<cfg:resource>	—	—	—
accountpermissions	<cfg:permission>	—	—	—
componentdefinitions	<cfg:componentdefinition>	—	—	—
userproperties	<cfg:property>	—	—	—
components	<cfg:component>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
assignedtenantdbid	integer	—	—	—
folderid	integer	—	—	—
state	string	—	—	CfgObjectState

<cfg:updateObject>

Name	Type	Description	Default	Values
startuptype	string	—	—	CfgStartupType
version	string	—	—	—
scsdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
type	string	—	—	SupportedTypes
subtype	string	—	—	CfgSolutionType
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
scsdbid	integer	—	—	—
name	string	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
folderdbid	integer	—	—	—
tenantdbid	integer	—	—	—

<cfg:updateObject> with **type="CfgSkill"**

Attributes

<cfg:updateObject>

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
name	string	—	—	—
createonupdate	Boolean	—	—	—
mode	string	—	—	merge, clear

Supported List Names

Name	Type	Description	Default	Values
userproperties	<cfg:property>	—	—	—
accountpermissions	<cfg:permission>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
state	string	—	—	CfgObjectState

Supported Query Names

Name	Type	Description	Default	Values
type	string	—	—	SupportedTypes
folderid	integer	—	—	—
tenantdbid	integer	—	—	—

<cfg:updateObject>

Name	Type	Description	Default	Values
name	string	—	—	—
state	string	—	—	CfgObjectState
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—

<cfg:updateObject> with **type="CfgStatDay"**

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
subtype	string	—	—	CfgStatDayType
name	string	—	—	—
createonupdate	Boolean	—	—	—
mode	string	—	—	merge, clear

Supported List Names

Name	Type	Description	Default	Values
accountpermissions	<cfg:permission>	—	—	—

<cfg:updateObject>

Name	Type	Description	Default	Values
userproperties	<cfg:property>	—	—	—
statintervals	<cfg:statinterval>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
endtime	integer	—	—	—
minvalue	integer	—	—	—
starttime	integer	—	—	—
folderid	integer	—	—	—
targetvalue	integer	—	—	—
maxvalue	integer	—	—	—
state	string	—	—	CfgObjectState
intervallength	integer	—	—	—
flatrate	integer	—	—	—
useflatrate	string	—	—	CfgFlag
isdayofweek	string	—	—	CfgFlag
day	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
type	string	—	—	SupportedTypes

<cfg:updateObject>

Name	Type	Description	Default	Values
folderid	integer	—	—	—
tenantdbid	integer	—	—	—
state	string	—	—	CfgObjectState
subtype	string	—	—	CfgStatDayType
name	string	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
tabledbid	integer	—	—	—

<cfg:updateObject> with type="CfgStatTable"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
subtype	string	—	—	CfgStatTableType
name	string	—	—	—
createonupdate	Boolean	—	—	—

<cfg:updateObject>

Name	Type	Description	Default	Values
mode	string	—	—	merge, clear

Supported List Names

Name	Type	Description	Default	Values
accountpermissions	<cfg:permission>	—	—	—
statdaydbids	<cfg:id>	—	—	—
userproperties	<cfg:property>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
agenthourlyrate	integer	—	—	—
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
flatrate	integer	—	—	—
waitthreshold	integer	—	—	—
useflatrate	string	—	—	CfgFlag

Supported Query Names

Name	Type	Description	Default	Values
type	string	—	—	SupportedTypes
folderid	integer	—	—	—
tenantdbid	integer	—	—	—

<cfg:updateObject>

Name	Type	Description	Default	Values
state	string	—	—	CfgObjectState
subtype	string	—	—	CfgStatTableType
name	string	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—
groupdbid	integer	—	—	—
statdaydbid	integer	—	—	—

<cfg:updateObject> with type="CfgSwitch"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
name	string	—	—	—
createonupdate	Boolean	—	—	—
mode	string	—	—	merge, clear

Supported List Names

<cfg:updateObject>

Name	Type	Description	Default	Values
accountpermissions	<cfg:permission>	—	—	—
userproperties	<cfg:property>	—	—	—
switchaccesscodes	<cfg:switchaccesscode>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
dnrange	string	—	—	—
state	string	—	—	CfgObjectState
tserverdbid	integer	—	—	—
physswitchdbid	integer	—	—	—
linktype	string	—	—	CfgLinkType

Supported Query Names

Name	Type	Description	Default	Values
type	string	—	—	SupportedTypes
folderid	integer	—	—	—
tenantdbid	integer	—	—	—
state	string	—	—	CfgObjectState
tserverdbid	integer	—	—	—
name	string	—	—	—

<cfg:updateObject>

Name	Type	Description	Default	Values
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—

<cfg:updateObject> with **type="CfgTableAccess"**

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
subtype	string	—	—	CfgTableType
name	string	—	—	—
createonupdate	Boolean	—	—	—
mode	string	—	—	merge, clear

Supported List Names

Name	Type	Description	Default	Values
accountpermissions	<cfg:permission>	—	—	—
userproperties	<cfg:property>	—	—	—

Supported Parameter Names

<cfg:updateObject>

Name	Type	Description	Default	Values
updatetimeout	integer	—	—	—
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
iscachable	string	—	—	CfgFlag
formatdbid	integer	—	—	—
dbtablename	string	—	—	—
description	string	—	—	—
dbaccessdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
type	string	—	—	SupportedTypes
folderid	integer	—	—	—
tenantdbid	integer	—	—	—
state	string	—	—	CfgObjectState
subtype	string	—	—	CfgTableType
formatdbid	integer	—	—	—
dbtablename	string	—	—	—
name	string	—	—	—
dbaccessdbid	integer	—	—	—

<cfg:updateObject>

Name	Type	Description	Default	Values
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—

<cfg:updateObject> with **type="CfgTenant"**

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
name	string	—	—	—
createonupdate	Boolean	—	—	—
mode	string	—	—	merge, clear

Supported List Names

Name	Type	Description	Default	Values
accountpermissions	<cfg:permission>	—	—	—
userproperties	<cfg:property>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—

<cfg:updateObject>

Name	Type	Description	Default	Values
isserviceprovider	string	—	—	CfgFlag
defaultcapacityruledbid	integer	—	—	—
chargeablenumber	string	—	—	—
defaultcontractdbid	integer	—	—	—
state	string	—	—	CfgObjectState
password	string	—	—	—
parenttenantdbid	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
type	string	—	—	SupportedTypes
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
name	string	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
alltenants	string	If included, regardless of value, returns the root tenant in the resultset. If excluded, the root tenant is not returned in the resultset.	—	CfgFlag
dbid	integer	—	—	—

<cfg:updateObject>

<cfg:updateObject> with **type**="CfgTimeZone"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
name	string	—	—	—
createonupdate	Boolean	—	—	—
mode	string	—	—	merge, clear

Supported List Names

Name	Type	Description	Default	Values
accountpermissions	<cfg:permission>	—	—	—
userproperties	<cfg:property>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
folderid	integer	—	—	—
dstoffset	integer	—	—	—
state	string	—	—	CfgObjectState
namenetscape	string	—	—	—
namemsexplorer	string	—	—	—

<cfg:updateObject>

Name	Type	Description	Default	Values
description	string	—	—	—
isdstobserved	string	—	—	CfgFlag
offset	integer	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
type	string	—	—	SupportedTypes
folderid	integer	—	—	—
tenantdbid	integer	—	—	—
state	string	—	—	CfgObjectState
namenetscape	string	—	—	—
namemsexplorer	string	—	—	—
name	string	—	—	—
offset	integer	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—

<cfg:updateObject> with **type="CfgTransaction"**

Attributes

<cfg:updateObject>

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
subtype	string	—	—	CfgTransactionType
name	string	—	—	—
createonupdate	Boolean	—	—	—
mode	string	—	—	merge, clear

Supported List Names

Name	Type	Description	Default	Values
accountpermissions	<cfg:permission>	—	—	—
userproperties	<cfg:property>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
alias	string	—	—	—
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
recordperiod	integer	—	—	—
description	string	—	—	—

Supported Query Names

<cfg:updateObject>

Name	Type	Description	Default	Values
type	string	—	—	SupportedTypes
tenantdbid	integer	—	—	—
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
subtype	string	—	—	CfgTransactionType
name	string	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—

<cfg:updateObject> with type="CfgTreatment"

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—
subtype	string	—	—	CfgCallActionCode
name	string	—	—	—
createonupdate	Boolean	—	—	—

<cfg:updateObject>

Name	Type	Description	Default	Values
mode	string	—	—	merge, clear

Supported List Names

Name	Type	Description	Default	Values
accountpermissions	<cfg:permission>	—	—	—
userproperties	<cfg:property>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
increment	integer	—	—	—
range	integer	—	—	—
interval	integer	—	—	—
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
cycleattempt	integer	—	—	—
reactioncode	string	—	—	CfgRecActionCode
description	string	—	—	—
attempts	integer	—	—	—
destdndbid	integer	—	—	—
callresult	string	—	—	GctiCallState

Supported Query Names

<cfg:updateObject>

Name	Type	Description	Default	Values
type	string	—	—	SupportedTypes
folderid	integer	—	—	—
tenantdbid	integer	—	—	—
state	string	—	—	CfgObjectState
reactioncode	string	—	—	CfgRecActionCode
name	string	—	—	—
destdndbid	integer	—	—	—
callresult	string	—	—	GctiCallState
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
callactioncode	string	—	—	CfgCallActionCode
dbid	integer	—	—	—

<cfg:updateObject> with **type="CfgVoicePrompt"**</t>

Attributes

Name	Type	Description	Default	Values
result	string	—	—	—
data	object	—	—	—
tenantdbid	integer	—	—	—

<cfg:updateObject>

Name	Type	Description	Default	Values
name	string	—	—	—
createonupdate	Boolean	—	—	—
mode	string	—	—	merge, clear

Supported List Names

Name	Type	Description	Default	Values
accountpermissions	<cfg:permission>	—	—	—
userproperties	<cfg:property>	—	—	—

Supported Parameter Names

Name	Type	Description	Default	Values
switchdbid	integer	—	—	—
scriptdbid	integer	—	—	—
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
description	string	—	—	—

Supported Query Names

Name	Type	Description	Default	Values
type	string	—	—	SupportedTypes
switchdbid	integer	—	—	—
tenantdbid	integer	—	—	—

<cfg:updateObject>

Name	Type	Description	Default	Values
scriptdbid	integer	—	—	—
folderid	integer	—	—	—
state	string	—	—	CfgObjectState
name	string	—	—	—
delegatedbid	integer	—	—	—
delegatetype	string	—	—	CfgObjectType
dbid	integer	—	—	—