



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Deployment Guide

cobrowse Section

12/19/2025

cobrowse Section

Contents

- [1 cobrowse Section](#)
 - [1.1 url](#)
 - [1.2 disableCertificateValidation](#)
 - [1.3 useBrowserLogging](#)
 - [1.4 agentSessionsLimit](#)
 - [1.5 extendedAttachedData](#)
 - [1.6 password](#)

Important

The options below provide configuration for the Co-browse Plug-in for Workspace Desktop Edition. To use these options, you must add them to the cobrowse section of your Interaction Workspace application in Genesys Administrator.

url

Default Value: None

Valid Values: Valid HTTP(S) URL

Changes Take Effect: After Interaction Workspace restart

Specifies the HTTP(S) URL (such as `http://[host]:[port]/cobrowse`) of the Co-browse cluster. Typically, this value is the URL for the load balancer. Since Co-browse 8.5.0, you can set the url value to an HTTP or HTTPS based URL.

Tip

The `secureURL` and `useSecureConnection` options have been discontinued starting with Co-browse 8.5.0 because HTTPS URLs can now be configured from the `url` option.

disableCertificateValidation

Default Value: false

Valid Values: true, false

Changes Take Effect: After Interaction Workspace restart

Disables certificate validation for the connection between Interaction Workspace and the Co-browse Server.

useBrowserLogging

Default Value: false

Valid Values: true, false

Changes Take Effect: After Interaction Workspace restart

Enables the embedded Internet Explorer (agent web UI) logs to redirect into the Interaction Workspace log.

agentSessionsLimit

Default Value: 1

Valid Values: Positive integer or 0

Changes Take Effect: Immediately for co-browse sessions started after change

Added In: Co-browse Plug-in for Workspace Desktop Edition **8.5.003.04**.

If set to greater than 1, disables **one-session agent limitations** and configures the number of simultaneous co-browsing sessions an agent can participate in. A value of 0 sets an unlimited amount of simultaneous co-browse sessions for agents.

extendedAttachedData

Default Value: false

Valid Values: true, false

Changes Take Effect: Immediately for co-browse sessions started after change

Added In: Co-browse Plug-in for Workspace Desktop Edition **8.5.102.01**.

Setting the value to true enables **extended attached data** for the voice or chat interaction.

password

Default Value: None

Valid Values: String with 16 characters

Changes Take Effect: Immediately for co-browse sessions started after change

Added in: Co-browse Plug-in for Workspace Desktop Edition **8.5.102.01**

Specifies the token used to **authenticate** communication between Co-browse Server and Workspace Desktop Edition.