



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

## API Reference

### Server-Initiated CometD Channels (Notifications)

5/7/2025

# Server-Initiated CometD Channels (Notifications)

## Contents

- **1 Server-Initiated CometD Channels (Notifications)**
  - 1.1 Joined Session
  - 1.2 Activated Session
  - 1.3 Deactivated Session

### Joined Session

CometD Channel	/service/session/joined
Description	Notification to all users who are already in the session about a new joined user.

Notification:

```
{
  "userId": "2",
  "role": 2,
  "name": "Bob"
}
```

### Activated Session

CometD Channel	/service/session/activated
Description	Notification to all clients about session activation.

Notification:

```
{
  "activationTime": 1368722791040 // UTC time in ms
}
```

### Deactivated Session

CometD Channel	/service/session/deactivated
Description	Notification to all clients about session deactivation. When the client receives a session deactivated notification, it should disconnect from CometD. Sending the <b>exit session</b> command is not needed.

Notification:

```
{
  "activationTime": 1368722791040 // UTC time in ms
  "deactivationTime": 1368722820929 // UTC time in ms
}
```