



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

# Deployment Guide

cobrowse Section

12/16/2025

# cobrowse Section

## Contents

- [1 cobrowse Section](#)
  - [1.1 url](#)
  - [1.2 disableCertificateValidation](#)
  - [1.3 useBrowserLogging](#)
  - [1.4 agentSessionsLimit](#)
  - [1.5 extendedAttachedData](#)
  - [1.6 password](#)
  - [1.7 proxyLogin](#)
  - [1.8 proxyPassword](#)
  - [1.9 customInteractionId](#)

### Important

The options below provide configuration for the Co-browse Plug-in for Workspace Desktop Edition. To use these options, you must add them to the cobrowse section of your Workspace Desktop Edition application in Genesys Administrator.

#### url

Default Value: None

Valid Values: Valid HTTP(S) URL

Changes Take Effect: After Workspace Desktop Edition restart

Specifies the HTTP(S) URL (such as `http://[host]:[port]/cobrowse`) of the Co-browse cluster. Typically, this value is the URL for the load balancer. Since Co-browse 8.5.0, you can set the url value to an HTTP or HTTPS based URL.

### Tip

The `secureURL` and `useSecureConnection` options have been discontinued starting with Co-browse 8.5.0 because HTTPS URLs can now be configured from the `url` option.

#### disableCertificateValidation

Default Value: false

Valid Values: true, false

Changes Take Effect: After Workspace Desktop Edition restart

Disables certificate validation for the connection between Workspace Desktop Edition and the Co-browse Server.

#### useBrowserLogging

Default Value: false

Valid Values: true, false

Changes Take Effect: After Workspace Desktop Edition restart

Enables the embedded Internet Explorer (Agent side web UI) logs to redirect into the Workspace Desktop Edition log.

#### agentSessionsLimit

Default Value: 1

Valid Values: Positive integer or 0

Changes Take Effect: Immediately for co-browse sessions started after change

Added In: Co-browse Plug-in for Workspace Desktop Edition **8.5.003.04**.

If set to greater than 1, disables **one-session agent limitations** and configures the number of simultaneous co-browsing sessions an agent can participate in. A value of 0 sets an unlimited amount of simultaneous co-browse sessions for agents.

#### extendedAttachedData

Default Value: false

Valid Values: true, false

Changes Take Effect: Immediately for co-browse sessions started after change

Added In: Co-browse Plug-in for Workspace Desktop Edition **8.5.102.01**.

Setting the value to true enables **extended attached data** for the voice or chat interaction.

#### password

Default Value: None

Valid Values: String with 16 characters

Changes Take Effect: Immediately for co-browse sessions started after change

Added in: Co-browse Plug-in for Workspace Desktop Edition **8.5.102.01**

Specifies the token used to **authenticate** communication between Co-browse Server and Workspace Desktop Edition. This password is equal to the password option configured in the **slave section**.

#### proxyLogin

Default Value: None

Valid Values: String

Changes Take Effect: Immediately for co-browse sessions started after change

Added in: Co-browse Plug-in for Workspace Desktop Edition 9.0.005.48

Specifies a plain text login for proxy credentials, to support proxy with authentication.

#### proxyPassword

Default Value: None

Valid Values: String

Changes Take Effect: Immediately for co-browse sessions started after change

Added in: Co-browse Plug-in for Workspace Desktop Edition 9.0.005.48

Specifies a plain text password for proxy credentials, to support proxy with authentication.

#### customInteractionId

Default Value: None

Valid Values: <data field name>

Changes Take Effect: Immediately for co-browse sessions started after change

Added in: Co-browse Plug-in for Workspace Desktop Edition 9.0.005.48

Specifies a custom InteractionId field name in the user attached data. GCXI Reporting will extract this custom InteractionId instead of using the default InteractionId.