



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Deployment Guide

forward-proxy Section

12/12/2025

forward-proxy Section

Contents

- 1 forward-proxy Section
 - 1.1 host
 - 1.2 port
 - 1.3 user
 - 1.4 password

Configures forward proxy options to let the Co-browse server obtain public web resources in an environment where the Internet is accessed through a forward proxy (for example, DMZ or local intranet).

Important

The Co-browse server accesses public web resources when it proxies CSS and other co-browsed web site resources.

host

Default value:

Valid Values: Either a domain name or IP address (IPv4 or IPv6)

Changes Take Effect: After Co-browse server restart

The forward proxy host. If the host option is not specified (default), the Co-browse server makes direct connections to the target web servers.

port

Default value:

Valid Values: Valid TCP port

Changes Take Effect: After Co-browse server restart

The forward proxy port. If the host option is specified, the port **must also** be specified.

user

Default value:

Valid Values: Valid user name

Changes Take Effect: After Co-browse server restart

User name used in HTTP Basic authentication if the forward proxy requires authentication.

password

Default value:

Valid Values: Valid password

Changes Take Effect: After Co-browse server restart

Password used in HTTP Basic authentication if the forward proxy requires authentication. If the user option is specified, the password **must also** be specified.