



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

# Genesys Customer Experience Insights Project Guide

Outbound Contact Attributes

12/15/2025

# Outbound Contact Attributes

The Outbound Contact folder contains numerous attributes that you can use to build outbound-related reports.

Note the following:

- When creating attributes, any forms you create must have a one-is-to-one mapping relationship. For example, an attribute that represents the name of a customer can have only one phone number form associated with it.

## Important

Objects in each folder or subfolder are designed to be used together to create reports. Avoid mixing attributes and metrics from multiple folders into your reports. One exception to this rule is objects in the Time folder; Time attributes can be used in any report, and most reports include at least one attribute from the Time folder.

The following Attributes are available in this folder and are described on this page.

### Outbound Contact

- Campaign
- Campaign Group
- Campaign Group Key

### Outbound Contact > Agent Contact

- Agent Group
- Agent Name
- Business Result
- Campaign
- Campaign Group
- Customer Segment

- Interaction Subtype
- Interaction Type
- Media Type
- Service Subtype
- Service Type

### Outbound Contact > Agent Contact > Agent Contact User Data Example

- Dimension 1 - Dimension 5
- Dimension 6 - Dimension 10

### Outbound Contact > Contact Attempt

- Business Result
- Campaign
- Campaign Group
- Contact List
- Media Type
- Service Subtype
- Service Type

### Outbound Contact > Contact Attempt > Contact Attempt User Data Example

- Dimension 1 - Dimension 5
- Dimension 6 - Dimension 10

## Folder: Outbound Contact

<b>Attribute name: Campaign</b>	<b>Folder:</b> Outbound Contact
<b>Description:</b> Enables data to be organized by the name of the outbound campaign.	
<b>Database table:</b> CAMPAIGN.CAMPAIGN_NAME	
<a href="#">&gt;&gt; Back to list</a>	

  

<b>Attribute name: Campaign Group</b>	<b>Folder:</b> Outbound Contact
<b>Description:</b> Enables data to be organized by the group associated with the outbound campaign.	
<b>Database table:</b> CAMPAIGN.CAMPAIGN_NAME, GROUP_CA.GROUP_NAME	<b>Form(s):</b> Group Name
<b>Forms in this attribute:</b>	
<b>Form:</b> Group Name	
<b>Table.Column:</b> GROUP_CA.GROUP_NAME (WHERE GROUP_TYPE_CODE in ('NO_VALUE', 'UNKNOWN', 'AGENT', 'PLACE')) <b>Data type:</b> Character	<b>Description:</b> Enables data to be organized by the name of the agent (or place) group to which the agent (or place), processing the interaction, belongs.
<a href="#">&gt;&gt; Back to list</a>	

  

<b>Attribute name: Campaign Group Key</b>	<b>Folder:</b> Outbound Contact
<b>Description:</b> Reserved for internal calculations.	
<b>Database table:</b> AG2_AGENT_CAMPAIGN *.CAMPAIGN_GROUP_KEY, AG2_CAMPAIGN *.CAMPAIGN_GROUP_KEY, GROUP_CA.GROUP_KEY	
<a href="#">&gt;&gt; Back to list</a>	

## Folder: Outbound Contact &gt; Agent Contact

<b>Attribute name: Agent Group</b>	<b>Folder:</b> Outbound Contact > Agent Contact
<b>Description:</b> Enables data within the reporting interval to be organized by the groups to which agents belong. An agent can belong to more than one agent group.	
<b>Database table:</b> GROUP_A.GROUP_NAME (WHERE GROUP_.GROUP_TYPE_CODE in ('AGENT', 'UNKNOWN', 'NO_VALUE'))	

<a href="#">&gt;&gt; Back to list</a>	
<b>Attribute name: Agent Name</b>	<b>Folder:</b> Outbound Contact > Agent Contact
<b>Description:</b> Enables data to be organized by certain attributes of the agent who is associated with the interaction.	
<b>Database table:</b> RESOURCE_A.AGENT_NAME	<b>Form(s):</b> User Name, Last Name, First Name, Employee ID
<b>Forms in this attribute:</b>	
<b>Form:</b> Employee ID <b>Table.Column:</b> RESOURCE_A.EMPLOYEE_ID <b>Data type:</b> Text	<b>Description:</b> Enables data to be organized by the Employee ID of the agent who is associated with the interaction.
<b>Form:</b> First Name <b>Table.Column:</b> RESOURCE_A.AGENT_FIRST_NAME <b>Data type:</b> Text	<b>Description:</b> Enables data to be organized by the first name of the agent who is associated with the interaction.
<b>Form:</b> Last Name <b>Table.Column:</b> RESOURCE_A.AGENT_LAST_NAME <b>Data type:</b> Text	<b>Description:</b> Enables data to be organized by the last name of the agent who is associated with the interaction.
<b>Form:</b> User Name <b>Table.Column:</b> RESOURCE_A.RESOURCE_NAME <b>Data type:</b> Text	<b>Description:</b> Enables data to be organized by the user name of the agent who is associated with the interaction.
<a href="#">&gt;&gt; Back to list</a>	
<b>Attribute name: Business Result</b>	<b>Folder:</b> Outbound Contact > Agent Contact
<b>Description:</b> Enables data to be organized based on the configured business result. Displayed as Source Business Result in some reports.	
<b>Database table:</b> INTERACTION_DESCRIPTOR_GI2.BUSINESS_RESULT	
<a href="#">&gt;&gt; Back to list</a>	
<b>Attribute name: Campaign</b>	<b>Folder:</b> Outbound Contact > Agent Contact
<b>Description:</b> Enables data to be organized by the name of the outbound campaign.	
<b>Database table:</b> CAMPAIGN.CAMPAIGN_NAME	
<a href="#">&gt;&gt; Back to list</a>	
<b>Attribute name: Campaign Group</b>	<b>Folder:</b> Outbound Contact > Agent Contact
<b>Description:</b> Enables data to be organized by the group associated with the outbound campaign.	
<b>Database table:</b> CAMPAIGN.CAMPAIGN_NAME, GROUP_CA.GROUP_NAME	<b>Form(s):</b> Group Name

<b>Forms in this attribute:</b>	
<b>Form:</b> Group Name  <b>Table.Column:</b> GROUP_CA.GROUP_NAME (WHERE GROUP_TYPE_CODE in ('NO_VALUE', 'UNKNOWN', 'AGENT', 'PLACE')) <b>Data type:</b> Character	<b>Description:</b> Enables data to be organized by the name of the agent (or place) group to which the agent (or place), processing the interaction, belongs.
<a href="#">&gt;&gt; Back to list</a>	
<b>Attribute name: Customer Segment</b>	<b>Folder:</b> Outbound Contact > Agent Contact
<b>Description:</b> Enables data to be organized based on the configured customer segment. Displays as Source Customer Segment in some reports.	
<b>Database table:</b> INTERACTION_DESCRIPTOR_GI2.CUSTOMER_SEGMENT	
<a href="#">&gt;&gt; Back to list</a>	
<b>Attribute name: Interaction Subtype</b>	<b>Folder:</b> Outbound Contact > Agent Contact
<b>Description:</b> This Attribute enables data to be organized by the interaction's subtype; for example, InboundNew or Outbound Notification.	
<b>Database table:</b> INTERACTION_TYPE_GI2.INTERACTION_TYPE_SUBTYPE	
<a href="#">&gt;&gt; Back to list</a>	
<b>Attribute name: Interaction Type</b>	<b>Folder:</b> Outbound Contact > Agent Contact
<b>Description:</b> Enables data to be organized by the interaction's type—for example, Inbound, Outbound, and Internal.	
<b>Database table:</b> INTERACTION_TYPE_GI2.INTERACTION_TYPE	
<a href="#">&gt;&gt; Back to list</a>	
<b>Attribute name: Media Type</b>	<b>Folder:</b> Outbound Contact > Agent Contact
<b>Description:</b> Enables data to be organized by the media type of the interaction; for example, Voice, Email, and Chat.	
<b>Database table:</b> MEDIA_TYPE.MEDIA_NAME, MEDIA_TYPE.MEDIA_TYPE_KEY, MEDIA_TYPE.MEDIA_NAME, MEDIA_TYPE.MEDIA_NAME_CODE	<b>Form(s):</b> Media Type, Media Name Code
<b>Forms in this attribute:</b>	
<b>Form:</b> Media Name Code  <b>Table.Column:</b> <b>Data type:</b> Text	<b>Description:</b> Enables data to be organized by the Media Name Code associated with the interaction. One of NONE, VOICE, EMAIL, CHAT.
<b>Form:</b> Media Type	<b>Description:</b> Enables data to be organized by the media type

<b>Table.Column:</b> <b>Data type:</b> Text	associated with the interaction. For example, VOICE, EMAIL, or CHAT.
<a href="#">&gt;&gt; Back to list</a>	
<b>Attribute name: Service Subtype</b>	<b>Folder:</b> Outbound Contact > Agent Contact
<b>Description:</b> Enables data to be organized by the detailed type of service that the customer requested. Displays as Source Service Subtype in some reports.	
<b>Database table:</b> INTERACTION_DESCRIPTOR_GI2.SERVICE_TYPE_SUBTYPE	
<a href="#">&gt;&gt; Back to list</a>	
<b>Attribute name: Service Type</b>	<b>Folder:</b> Outbound Contact > Agent Contact
<b>Description:</b> Enables data to be organized by the type of service that was assigned to the interaction. Displays as Source Service Type in some reports.	
<b>Database table:</b> INTERACTION_DESCRIPTOR_GI2.SERVICE_TYPE	
<a href="#">&gt;&gt; Back to list</a>	

Folder: Outbound Contact > Agent Contact > Agent Contact User Data Example

<b>Attribute name: Dimension 1 - Dimension 5</b>	<b>Folder:</b> Outbound Contact > Agent Contact > Agent Contact User Data Example
<b>Description:</b> These 5 attributes enables data within the reporting interval to be organized by a particular user-data Attribute that is configured within your environment.	
<b>Database table:</b> USER_DATA_CUST_DIM_1.DIM_ATTRIBUTE_1, USER_DATA_CUST_DIM_1.DIM_ATTRIBUTE_2, USER_DATA_CUST_DIM_1.DIM_ATTRIBUTE_3, USER_DATA_CUST_DIM_1.DIM_ATTRIBUTE_4, USER_DATA_CUST_DIM_1.DIM_ATTRIBUTE_5	
<a href="#">&gt;&gt; Back to list</a>	
<b>Attribute name: Dimension 6 - Dimension 10</b>	<b>Folder:</b> Outbound Contact > Agent Contact > Agent Contact User Data Example
<b>Description:</b> These 5 attributes enables data within the reporting interval to be organized by a particular user-data Attribute that is configured within your environment.	
<b>Database table:</b> USER_DATA_CUST_DIM_2.DIM_ATTRIBUTE_1,	

USER\_DATA\_CUST\_DIM\_2.DIM\_ATTRIBUTE\_2,  
USER\_DATA\_CUST\_DIM\_2.DIM\_ATTRIBUTE\_3,  
USER\_DATA\_CUST\_DIM\_2.DIM\_ATTRIBUTE\_4,  
USER\_DATA\_CUST\_DIM\_2.DIM\_ATTRIBUTE\_5

[>> Back to list](#)

## Folder: Outbound Contact > Contact Attempt

### Attribute name: Business Result

**Folder:** Outbound Contact > Contact Attempt

**Description:** Enables data to be organized based on the configured business result. Displayed as Source Business Result in some reports.

**Database table:**

INTERACTION\_DESCRIPTOR\_GI2.BUSINESS\_RESULT

[>> Back to list](#)

### Attribute name: Campaign

**Folder:** Outbound Contact > Contact Attempt

**Description:** Enables data to be organized by the name of the outbound campaign.

**Database table:**

CAMPAIGN.CAMPAIGN\_NAME

[>> Back to list](#)

### Attribute name: Campaign Group

**Folder:** Outbound Contact > Contact Attempt

**Description:** Enables data to be organized by the group associated with the outbound campaign.

**Database table:**

CAMPAIGN.CAMPAIGN\_NAME,  
GROUP\_CA.GROUP\_NAME

**Form(s):** Group Name

**Forms in this attribute:**

**Form:** Group Name

**Table.Column:** GROUP\_CA.GROUP\_NAME (WHERE GROUP\_TYPE\_CODE in ('NO\_VALUE', 'UNKNOWN', 'AGENT', 'PLACE'))  
**Data type:** Character

**Description:** Enables data to be organized by the name of the agent (or place) group to which the agent (or place), processing the interaction, belongs.

[>> Back to list](#)

### Attribute name: Contact List

**Folder:** Outbound Contact > Contact Attempt

**Description:** Enables data to be organized by the contact list (that is, the calling list) that was used to run outbound campaigns.

**Database table:**

CALLING\_LIST.CALLING\_LIST\_NAME

<a href="#">&gt;&gt; Back to list</a>	
<b>Attribute name: Media Type</b>	<b>Folder:</b> Outbound Contact > Contact Attempt
<b>Description:</b> Enables data to be organized by the media type of the interaction; for example, Voice, Email, and Chat.	
<b>Database table:</b> MEDIA_TYPE.MEDIA_NAME, MEDIA_TYPE.MEDIA_TYPE_KEY, MEDIA_TYPE.MEDIA_NAME, MEDIA_TYPE.MEDIA_NAME_CODE	<b>Form(s):</b> Media Type, Media Name Code
<b>Forms in this attribute:</b>	
<b>Form:</b> Media Name Code <b>Table.Column:</b> <b>Data type:</b> Text	<b>Description:</b> Enables data to be organized by the Media Name Code associated with the interaction. One of NONE, VOICE, EMAIL, CHAT.
<b>Form:</b> Media Type <b>Table.Column:</b> <b>Data type:</b> Text	<b>Description:</b> Enables data to be organized by the media type associated with the interaction. For example, VOICE, EMAIL, or CHAT.
<a href="#">&gt;&gt; Back to list</a>	
<b>Attribute name: Service Subtype</b>	<b>Folder:</b> Outbound Contact > Contact Attempt
<b>Description:</b> Enables data to be organized by the detailed type of service that the customer requested. Displays as Source Service Subtype in some reports.	
<b>Database table:</b> INTERACTION_DESCRIPTOR_GI2.SERVICE_TYPE_SUBTYPE	
<a href="#">&gt;&gt; Back to list</a>	
<b>Attribute name: Service Type</b>	<b>Folder:</b> Outbound Contact > Contact Attempt
<b>Description:</b> Enables data to be organized by the type of service that was assigned to the interaction. Displays as Source Service Type in some reports.	
<b>Database table:</b> INTERACTION_DESCRIPTOR_GI2.SERVICE_TYPE	
<a href="#">&gt;&gt; Back to list</a>	

Folder: Outbound Contact > Contact Attempt > Contact Attempt  
User Data Example

<b>Attribute name: Dimension 1 - Dimension 5</b>	<b>Folder:</b> Outbound Contact > Contact Attempt > Contact Attempt User Data Example
--	---



**Description:** These 5 attributes enables data within the reporting interval to be organized by a particular user-data Attribute that is configured within your environment.

**Database table:**

USER\_DATA\_CUST\_DIM\_1.DIM\_ATTRIBUTE\_1,  
USER\_DATA\_CUST\_DIM\_1.DIM\_ATTRIBUTE\_2,  
USER\_DATA\_CUST\_DIM\_1.DIM\_ATTRIBUTE\_3,  
USER\_DATA\_CUST\_DIM\_1.DIM\_ATTRIBUTE\_4,  
USER\_DATA\_CUST\_DIM\_1.DIM\_ATTRIBUTE\_5

[>> Back to list](#)

**Attribute name: Dimension  
6 - Dimension 10**

**Folder:** Outbound Contact > Contact Attempt > Contact  
Attempt User Data Example

**Description:** These 5 attributes enables data within the reporting interval to be organized by a particular user-data Attribute that is configured within your environment.

**Database table:**

USER\_DATA\_CUST\_DIM\_2.DIM\_ATTRIBUTE\_1,  
USER\_DATA\_CUST\_DIM\_2.DIM\_ATTRIBUTE\_2,  
USER\_DATA\_CUST\_DIM\_2.DIM\_ATTRIBUTE\_3,  
USER\_DATA\_CUST\_DIM\_2.DIM\_ATTRIBUTE\_4,  
USER\_DATA\_CUST\_DIM\_2.DIM\_ATTRIBUTE\_5

[>> Back to list](#)