



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Genesys Info Mart Physical Data Model for a Microsoft SQL Server Database

Table CALLBACK_DIAL_RESULTS

Table CALLBACK_DIAL_RESULTS

Description

Introduced: 8.5.009.20

In partitioned databases, this table is not partitioned.

This dimension table allows callback facts to be described based on the results of up to five callback dialing attempts.

Tip

To assist you in preparing supplementary documentation, click the following link to download a comma-separated text file containing information such as the data types and descriptions for all columns in this table: [Download a CSV file](#).

Hint: For easiest viewing, open the downloaded CSV file in Excel and adjust settings for column widths, text wrapping, and so on as desired. Depending on your browser and other system settings, you might need to save the file to your desktop first.

Column List

Legend

Column	Data Type	P	M	F	DV
ID	int	X	X		
DIAL_1_RESULT	varchar(64)/nvarchar(64)		X		UNKNOWN
DIAL_2_RESULT	varchar(64)/nvarchar(64)		X		UNKNOWN
DIAL_3_RESULT	varchar(64)/nvarchar(64)		X		UNKNOWN
DIAL_4_RESULT	varchar(64)/nvarchar(64)		X		UNKNOWN
DIAL_5_RESULT	varchar(64)/nvarchar(64)		X		UNKNOWN

Table CALLBACK_DIAL_RESULTS

Column	Data Type	P	M	F	DV
CREATE_AUDIT_KEY	Numeric(19)		X	X	

ID

The primary key of this table. This ID is referenced from other tables as CALLBACK_DIAL_RESULTS_KEY.

DIAL_1_RESULT

Based on KVP: _CB_DIAL_1_RESULT

The result of the first dialing attempt. Possible values are:

- CREATE_CALL_ERROR
- BUSY
- NO_ANSWER
- ANSWERING_MACHINE
- ERROR_TONE
- FAX
- PERSON
- CONNECTED
- FAILED_TO_ESTABLISH_CUSTOMER_ORIGINATED_MEDIA
- PUSH_DELIVERY_CONFIRMED
- PUSH_SEND_ERROR
- PUSH_DELIVERY_NOT_CONFIRMED
- USERORIGINATED_CONNECTED
- UNKNOWN

DIAL_2_RESULT

Based on KVP: _CB_DIAL_2_RESULT

The result of the second dialing attempt. See [DIAL_1_RESULT](#) for the possible values.

DIAL_3_RESULT

Based on KVP: _CB_DIAL_3_RESULT

The result of the third dialing attempt. See [DIAL_1_RESULT](#) for the possible values.

DIAL_4_RESULT

Based on KVP: _CB_DIAL_4_RESULT

The result of the fourth dialing attempt. See [DIAL_1_RESULT](#) for the possible values.

DIAL_5_RESULT

Based on KVP: _CB_DIAL_5_RESULT

The result of the fifth dialing attempt. See [DIAL_1_RESULT](#) for the possible values.

CREATE_AUDIT_KEY

The surrogate key that is used to join to the CTL_AUDIT_LOG control table. The key specifies the lineage for data creation. This value can be useful for aggregation, enterprise application integration (EAI), and ETL tools--that is, applications that need to identify newly added data.

Index List

CODE	U	C	Description
I_CALLBACK_DIAL_RESULTS X			Ensures that the combinations of values that are stored in the dimension table are unique.

Index I_CALLBACK_DIAL_RESULTS

Field	Sort	Comment
DIAL_1_RESULT	Ascending	
DIAL_2_RESULT	Ascending	
DIAL_3_RESULT	Ascending	
DIAL_4_RESULT	Ascending	
DIAL_5_RESULT	Ascending	

Subject Areas

No subject area information available.