



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

# Genesys Info Mart Physical Data Model for an Oracle Database

Table TECHNICAL\_DESCRIPTOR

12/17/2025

# Table TECHNICAL\_DESCRIPTOR

## Description

**Modified:** 8.5.003 (in Oracle, fields with VARCHAR data types use explicit CHAR character-length semantics)

In partitioned databases, this table is not partitioned.

This table allows interaction-based facts to be described by the role of the associated resource and the technical result of the interaction or the interaction-based fact. For example, a queue resource received an interaction and diverted to another resource. Each row describes one distinct combination of attributes.

For detailed information about the available technical descriptor combinations, see [Technical Descriptors](#) in the *Genesys Info Mart User's Guide*.

### Tip

To assist you in preparing supplementary documentation, click the following link to download a comma-separated text file containing information such as the data types and descriptions for all columns in this table: [Download a CSV file](#).

**Hint:** For easiest viewing, open the downloaded CSV file in Excel and adjust settings for column widths, text wrapping, and so on as desired. Depending on your browser and other system settings, you might need to save the file to your desktop first.

## Column List

### Legend

Column	Data Type	P	M	F	DV
TECHNICAL_DESCRIPTOR_ID	NUMBER(10)	X	X		
TECHNICAL_RESULT	VARCHAR2(255)				

Table TECHNICAL\_DESCRIPTOR

Column	Data Type	P	M	F	DV
	CHAR)				
TECHNICAL_RESULT_CODE	VARCHAR2(32 CHAR)				
RESULT_REASON	VARCHAR2(255 CHAR)				
RESULT_REASON_CODE	VARCHAR2(32 CHAR)				
RESOURCE_ROLE	VARCHAR2(255 CHAR)				
RESOURCE_ROLE_CODE	VARCHAR2(32 CHAR)				
ROLE_REASON	VARCHAR2(255 CHAR)				
ROLE_REASON_CODE	VARCHAR2(32 CHAR)				
CREATE_AUDIT_KEY	NUMBER(19)		X	X	
UPDATE_AUDIT_KEY	NUMBER(19)		X	X	

## TECHNICAL\_DESCRIPTOR\_KEY

The surrogate key that is used to join this dimension table to the fact tables.

## TECHNICAL\_RESULT

The technical result of the handling attempt—that is, how the attempt ended. This field is set to one of the following values:

- Abandoned
- AbnormalStop
- Cleared
- Completed
- Conferenced
- CustomerAbandoned
- Deferred
- DestinationBusy
- Diverted
- Incomplete
- None
- OutboundStopped
- Pulled
- Redirected
- Routed
- Transferred
- Unspecified

This value can change with localization.

## TECHNICAL\_RESULT\_CODE

The technical result code of the handling attempt—that is, how the attempt ended. This field is set to one of the following values:

Table TECHNICAL\_DESCRIPTOR

- 
- |                     |                   |               |
|---------------------|-------------------|---------------|
| • ABANDONED         | • DEFERRED        | • PULLED      |
| • ABNORMALSTOP      | • DESTINATIONBUSY | • REDIRECTED  |
| • CLEARED           | • DIVERTED        | • ROUTED      |
| • COMPLETED         | • INCOMPLETE      | • TRANSFERRED |
| • CONFERENCED       | • NONE            | • UNSPECIFIED |
| • CUSTOMERABANDONED | • OUTBOUNDSTOPPED |               |

This value does not change with localization.

## RESULT\_REASON

The reason for the technical result. This field is set to one of the following values:

- |                            |  |                       |
|----------------------------|--|-----------------------|
| • AbandonedFromHold        | • Canceled   | • Revoked             |
| • AbandonedWhileQueued     | • DefaultRoutedByStrategy  | • RoutedFromAnotherVQ |
| • AbandonedWhileRinging    | • DefaultRoutedBySwitch  | • RoutedToOther       |
| • AbnormalStopWhileQueued  | • IntroducedTransfer   | • RouteOnNoAnswer     |
| • AbnormalStopWhileRinging | • PulledBack (starting with release 8.1.4) or PulledBackTimeout (in releases earlier than 8.1.4) | • Stopped             |
| • AnsweredByAgent          |  | • StuckCall           |
| • AnsweredByOther          |  | • TargetsCleared      |
| • Archived                 | • Redirected   | • Unspecified         |
| • CallbackAccepted         | • Rejected   |                       |

This value can change with localization.

## RESULT\_REASON\_CODE

The reason code for the technical result. This field is set to one of the following values:

- |                            |  |                       |
|----------------------------|--|-----------------------|
| • ABANDONEDFROMHOLD        | • CALLBACKACCEPTED   | • REDIRECTED          |
| • ABANDONEDWHILEQUEUED     | • CANCELED   | • REJECTED            |
| • ABANDONEDWHILERINGING    | • DEFAULTROUTEDBYSTRATEGY  | • REVOKED             |
| • ABNORMALSTOPWHILEQUEUED  | • DEFAULTROUTEDBYSWITCH  | • ROUTEDFROMANOTHERVQ |
| • ABNORMALSTOPWHILERINGING | • INTRODUCEDTRANSFER   | • ROUTEDTOOTHER       |
| • ANSWEREDBYAGENT          | • PULLEDBACK (starting with release 8.1.4) or PULLEDBACKTIMEOUT (in releases earlier than 8.1.4) | • ROUTEONNOANSWER     |
| • ANSWEREDBYOTHER          |  | • STOPPED             |
| • ARCHIVED                 |  | • STUCKCALL           |
-

- TARGETSCLEARED
- UNSPECIFIED

This value does not change with localization.

## RESOURCE\_ROLE

The role that is played by the resource that is associated with the handling attempt. This field is set to one of the following values:

- DivertedTo
- InConference
- Initiated
- InitiatedConsult
- Puller
- Received
- ReceivedConsult
- ReceivedRequest
- ReceivedTransfer
- RedirectedTo
- RoutedTo
- Unknown

This value can change with localization.

## RESOURCE\_ROLE\_CODE

The code of the role that is played by the resource that is associated with the handling attempt. This field is set to one of the following values:

- DIVERTEDTO
  - INCONFERENCE
  - INITIATED
  - INITIATEDCONSULT
  - PULLER
  - RECEIVED
  - RECEIVEDCONSULT
  - RECEIVEDREQUEST
  - RECEIVEDTRANSFER
-

- REDIRECTEDTO
- ROUTEDTO
- UNKNOWN

This value does not change with localization.

## ROLE\_REASON

The reason for the resource role. This field is set to one of the following values:

- Unspecified
- ConferenceInitiator
- ConferenceJoined
- IntroducedTransfer
- PulledBack (starting with release 8.1.4) or PulledBackTimeout (in releases earlier than 8.1.4)

This value can change with localization.

## ROLE\_REASON\_CODE

The code of the reason for the resource role. This field is set to one of the following values:

- UNSPECIFIED
- CONFERENCE\_INITIATOR
- CONFERENCE\_JOINED
- INTRODUCEDTRANSFER
- PULLEDBACK (starting with release 8.1.4) or PULLEDBACKTIMEOUT (in releases earlier than 8.1.4)

This value does not change with localization.

## CREATE\_AUDIT\_KEY

The surrogate key that is used to join to the CTL\_AUDIT\_LOG control table. The key specifies the lineage for data creation. This value can be useful for aggregation, enterprise application integration (EAI), and ETL tools—that is, applications that need to identify newly added data.

## UPDATE\_AUDIT\_KEY

The surrogate key that is used to join to the CTL\_AUDIT\_LOG control table. The key specifies the lineage for data update. This value can be useful for aggregation, enterprise application integration (EAI), and ETL tools—that is, applications that need to identify recently modified data.

## Index List

No indexes are defined.

## Subject Areas

- **Interaction\_Resource** — Represents a summary of each attempt to handle an interaction. It encompasses the mediation process that is required to offer the interaction to a target handling resource, as well as the activities of that target handling resource.
- **Mediation\_Segment** — Represents interaction activity from the perspective of contact center ACD queues, virtual queues, interaction queues, and interaction workbins, as well as groups thereof.