

# **GENESYS**

This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

# Genesys Info Mart Physical Data Model for a Microsoft SQL Server Database

Table SDR\_SURVEY\_TRANSCRIPT\_FACT

# Table SDR SURVEY TRANSCRIPT FACT

#### Description

**Introduced:** 8.5.005.20. Supported in certain Genesys Engage cloud deployments only. **Modified:** 8.5.116.45 (size of the SESSION\_ID column increased); 8.5.010.16 (UPDATE\_AUDIT\_KEY added); 8.5.010 (in Microsoft SQL Server, data type for SESSION\_ID modified in multi-language databases)

In partitioned databases, this table is partitioned.

This table captures transcriptions of voice messages left by survey respondents.

#### Tip

To assist you in preparing supplementary documentation, click the following link to download a comma-separated text file containing information such as the data types and descriptions for all columns in this table: Download a CSV file.

**Hint:** For easiest viewing, open the downloaded CSV file in Excel and adjust settings for column widths, text wrapping, and so on as desired. Depending on your browser and other system settings, you might need to save the file to your desktop first.

#### Column List

#### Legend

Column	Data Type	Р	M	F	DV
SESSION_ID	varchar(128)	Χ	X		
START_DATE_TIM	<u>Ei</u> nktEY	X	X	X	
TRANSCRIPTION_	<mark>T6u</mark> M <b>©</b> ric(19)		X		
TRANSCRIPTION	varchar(4000)/nv	varchar(4000)			

Column	Data Type	Р	M	F	DV
CREATE_AUDIT_k	(EYumeric(19)		X	Χ	
UPDATE_AUDIT_R	<b>⟨E</b> Yumeric(19)			X	

#### SESSION ID

**Modified:** 8.5.116.45 (size of the column increased); 8.5.010 (in Microsoft SQL Server, data type modified in multi-language databases)

The ID as assigned to the session by Orchestration Server. You can use the SESSION\_ID to link the SDR SURVEY TRANSCRIPT FACT record with an SDR SESSION FACT.

#### START DATE TIME KEY

Identifies the start of a 15-minute interval in which the fact began. Use this value as a key to join the fact tables to any configured DATE\_TIME dimension.

#### TRANSCRIPTION\_TS\_MS

The time stamp when the transcription was produced.

#### **TRANSCRIPTION**

The transcription of a voice message left by a survey respondent.

#### CREATE AUDIT KEY

The surrogate key that is used to join to the CTL\_AUDIT\_LOG control table. The key specifies the lineage for data creation. This value can be useful for aggregation, enterprise application integration (EAI), and ETL tools--that is, applications that need to identify newly added data.

#### UPDATE\_AUDIT\_KEY

Introduced: Release 8.5.010.16

The surrogate key that is used to join to the CTL\_AUDIT\_LOG control table. The key specifies the lineage for data update. This value can be useful for aggregation, enterprise application integration (EAI), and ETL tools — that is, applications that need to identify recently modified data.

### Index List

CODE	U	С	Description
I_SDR_SRV_TRANSCRIPT_F	ACT_SDT		Improves access time, based on the Start Date Time key.

## $Index\ I\_SDR\_SRV\_TRANSCRIPT\_FACT\_SDT$

Field	Sort	Comment
START_DATE_TIME_KEY	Ascending	

## Subject Areas

No subject area information available.