



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Genesys Mobile Services Deployment Guide

Single Sign-On

12/16/2025

Contents

- 1 Single Sign-On
 - 1.1 Login
 - 1.2 Logout
 - 1.3 Deployment

Single Sign-On

Important

This feature requires specific configuration/updates on **Genesys Management Framework components** (LDAP, IdP, Config Server, and so on).

GMS version 8.5.003.xx and higher enables you to use Single Sign-on (SSO) to access the GMS Service Management UI. This page describes the settings needed to configure GMS to use your existing SSO infrastructure.

Login

Initiates Security Assertion Markup Language (SAML) login procedure.

`http://<gmshost>:<gmsportport>/genesys/admin/`

All authenticated Genesys users defined in Configuration Manager can access the GMS Service Management UI. GMS requires a valid user defined in Configuration Manager in order to allow administration tasks. Genesys Config Server must be configured to use external authentication functionality; Config Server users must be defined to use external authentication, pointing to the authentication system (LDAP, and so on).

Logout

Close the browser or remove browser cookies.

Deployment

SSO deployment requires the following steps:

Start

1. Uncomment the SAML parameter in the launcher.xml file.
2. Create keystore.
3. Create server-settings.yaml file and configure the following settings:
 - adminUrl
 - caCertificate

- jksPassword
- encryptionKeyName
- signingKeyName
- identityProviderMetadata: idp-metadata.xml

4. Start GMS.

- Generate GMS metadata.
- Update IdP information with GMS metadata.

End

Launcher.xml

Uncomment the following parameter in launcher.xml:

```
<parameter name="saml-settings" displayName="saml-settings" mandatory="false">
  <description><![CDATA[GMS Server SAML init]]></description>
  <valid-description><![CDATA[]]></valid-description>
  <effective-description/>
  <format type="string" default="server-settings.yaml" />
  <validation></validation>
</parameter>
```

Generating Security Keys

To generate a keystore, you can use the keytool utility that is included with Java SDK. To generate a JKS keystore, use the following command:

```
keytool -genkey -keystore keystore.jks -alias <encryptionKeyName> -keypass <signingKeyName>
-storepass <jksPassword> -dname <distinguished_name>
```

server-settings.yaml

Security Keys

In order to enable SAML, you must specify the following mandatory properties in a general section into server-settings.yaml:

- adminUrl (mandatory) - the URL will be used as unique entity ID in SP metadata.
- caCertificate (mandatory) - a path to a key storage in JKS format containing all necessary keys.
- jksPassword (mandatory) - a password for the key storage specified above.

Example:

```
adminUrl: http://<gmshost>:<gmsportport>/genesys/admin
caCertificate: c:\GMS\keystore.jks
jksPassword: password
```

SAML Settings Section

In order to enable SAML, you must specify the following mandatory properties in the `samlSettings` section into `server-settings.yaml`:

- `encryptionKeyName`
- `signingKeyName`
- `identityProviderMetadata`

Example:

```
adminUrl: http://<gmshost>:<gmSPORTport>/genesys/admin
caCertificate: c:/GMS//keystore.jks
jksPassword: password
samlSettings:
  encryptionKeyName: client
  signingKeyName: client
  identityProviderMetadata: idp-metadata.xml
```

Settings

Name	Mandatory?	Description
<code>encryptionKeyName</code>	Yes	SAML encryption key name. This key must be present in the JKS key storage specified above. This key is used to encrypt SAML message sent to IdP.
<code>signingKeyName</code>	Yes	SAML signing key name. This key must be present in the JKS key storage specified above.
<code>responseSkewTime</code>	No	Sets maximum difference between local time and time of the assertion creation, which still allows messages to be processed. Determines the maximum difference between clocks of the IdP and SP servers. Defaults to 60 seconds.

Note: You can use the same key for signing and encryption.

Identity Provider

Name	Mandatory?	Description
<code>identityProviderMetadata</code>	Yes	Identity Provider XML metadata file path or URL. If the IdP metadata file is exposed by the remote server over HTTP, it is possible to also specify the URL (default request timeout of 5 seconds will be applied). Check

Name	Mandatory?	Description
		the metadata URL of your IdP server.

Generating GMS Metadata

GMS metadata (SP metadata) are available at the following URL:

`http://<gmshost>:<gmsportport>/genesys/saml/metadata`

Use this file to update your IdP server.