

GENESYS

This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Genesys Rules System REST API Reference Guide

Undeploy Rule Package or Snapshot

Contents

- 1 Undeploy Rule Package or Snapshot
 - 1.1 Method
 - 1.2 Syntax
 - 1.3 Request Body
 - 1.4 Response Body
 - 1.5 HTTP Status Codes
 - 1.6 Notes

Undeploy Rule Package or Snapshot

Method

POST

Syntax

/grs/v1/tenant/{tenantId}/package/{packageId}/undeploy

Request Body

```
{
  "target": "GRE_Cluster",
  "comments":"Undeploy to QA servers"
}
```

Response Body

```
{
  "target": "GRE_Cluster",
  "deploymentId": 3423322234,
  "comments":"Undeploy to QA servers"
}
```

HTTP Status Codes

- 201 Created—Response body provided with deployment ID
- 401 Unauthorized—APIToken not valid
- 403 Forbidden—User does not have permission for the specified tenant or does not have proper permission to perform this operation.
- · 404 Not Found—could not find specified package ID

Notes

User must have PACKAGE_UNDEPLOY and SNAPSHOT_VIEW permissions.

• target—Indicate which GRE or GRE Cluster you want to undeploy from. Use "Query Deploy Targets" to get the list of valid targets.