



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

GVP Web Services API

RM Historical Detailed CDR Reporting Services

5/10/2025

Contents

- 1 RM Historical Detailed CDR Reporting Services
 - 1.1 Web Service Endpoint
 - 1.2 Input Parameters
 - 1.3 Output Format

RM Historical Detailed CDR Reporting Services

This report describes the completed calls in the GVP Resource Manager. Each report contains a [manifest section](#).

Web Service Endpoint

This report is available at the web service endpoint `/ems-rs/HIST/CDRs/RM/details`.

Input Parameters

This report accepts the following Request URI parameters:

Parameter	Description
started-from	This describes the starting point of the "call start" field of the CDR. It takes the DateTime format as described in the Common Input Parameter Types page. This will cause the report to return only calls started after the specified value.
started-to	This describes the ending point of the "call start" field of the CDR. It takes the DateTime format as described in the Common Input Parameter Types page. This will cause the report to return only calls started before the specified value.
ended-from	This describes the starting point of the "call end" field of the CDR. It takes the DateTime format as described in the Common Input Parameter Types page. This will cause the report to return only calls ended after the specified value.
ended-to	This describes the ending point of the "call end" field of the CDR. It takes the DateTime format as described in the Common Input Parameter Types page. This will cause the report to return only calls ended before the specified value.
app-id	This describes the target IVR Profile Config Server DBID. This may be specified zero or more times. All the CDRs returned in the report must belong to one of the specified IVR Profiles. This cannot be specified together with either the tenant-id or the dn parameter.
tenant-id	This describes the target Tenant Config Server

Parameter	Description
	DBID. This may be specified zero or more times. All the CDRs returned in the report must belong to one of the specified tenants. This cannot be specified together with either the app-id or the dn parameter.
dn	<p>This describes the target DN of the CDR. This may be specified zero or more times. All the CDRs returned in the report must belong to one of the specified DNs. This cannot be specified together with either the app-id or the tenant-id parameter.</p> <p>The format of the dn parameter may be one of the following:</p> <ul style="list-style-type: none">• a single integer n - the result contains records that exactly matches the value n• a single integer n followed by a '*' - the result contains records that has the prefix n• a range in the format m-n - the result contains results with DN that is greater than or equal to m and less than or equal to n.
comp-id	This describes the target component's Config Server DBID. This may be specified one or zero times. All the CDRs returned in the report must have been processed on the specified component.
remote-uri	This may be specified zero or more times. All the CDRs returned in the report must have a matching remote-uri. A trailing asterisk (*) may be specified in the remote-uri query to indicate a prefix-match.
local-uri	This may be specified zero or more times. All the CDRs returned in the report must have a matching local-uri. A trailing asterisk (*) may be specified in the local-uri query to indicate a prefix-match.
call-status	<p>This causes the report to contain only calls with matching call-status. This can take one of the following values:</p> <ul style="list-style-type: none">• COMPLETED• TIMED_OUT
session-id	This causes the report to return a single call with a matching session-id. This must be accompanied by a comp-id parameter. If session-id is specified, no other parameters other than these two should be specified.
genesys-uuid	This causes the report to return all calls with a matching Genesys Framework session id. If this is specified, no other parameters should be specified.
vtag	This causes the report to contain only calls with matching virtual reporting tags. This parameter can appear more than once in a query. The vtag

Parameter	Description
	parameter takes on a format of <tag-name>,<tag-value> which returns all the calls having been tagged with <tag-name>=<tag-value>
call-type	This causes the report to contain only calls with matching call-type to be returned. Valid values are: <ul style="list-style-type: none">• INBOUND• OUTBOUND
duration-min	This is the minimum duration in milliseconds. When specified, the report contains calls with duration that is at least the specified value.
duration-max	This is the maximum duration in milliseconds. When specified, the report contains calls with duration that is at most the specified value.
sort-order	This can take on the value of either asc or desc, and it affects the way the CDRs in the report are sorted. If set to "asc" the CDRs are returned in ascending order, by time. If set to "desc" the CDRs are returned in descending order, by time. The default value is asc.
call-disposition	The can take on one of the following values, and the report will contain only calls with the matching call-disposition: <ul style="list-style-type: none">• COMPLETED_IN_IVR• ABANDONED_IN_QUEUE• TRANSFERRED_TO_AGENT• REJECTED• UNKNOWN
page-size	This specifies the per-page maximum number of items to be returned in a single CDR report. If this is greater than some maximum configured on the Reporting Server, this is silently ignored.
page	This specifies the page number to be returned. Together with sort-order and page-size, it determines the set of CDRs to be returned in the query. If this page exceeds some maximum value configured on the reporting server, or if the product of page×page-size is greater than the result set, an error is returned.

Output Format

The output for this report consists of a list of CDRs, where each CDR describes the information about the call on the RM which generated this CDR. It conforms to the RelaxNG schema RM_CDR.rng.

Download the GVP RNG Schemas An example report body for this report is as follows:

```
<cdr-list>
  <cdr comp-type="RM" gvp-guid="A3F87C2C-EA22-47D6-62A1-B27CEAE99000" session-id="A3F87C2C-
EA22-47D6-62A1-B27CEAE99000" app-id="215" comp-id="223" start="2010-02-02T11:00:03.455Z"
end="2010-02-02T11:00:08.345Z" duration="4890" call-status="COMPLETED" call-type="INBOUND"
local-uri="sip:366@138.120.84.153;aai=N/A" remote-uri="sip:111@10.0.0.97" tenant-id="1"
dn="366" usage-profile="1" burst-profile="1" usage-tenant="1" burst-tenant="1" call-
disposition="COMPLETED_IN_IVR">
    <usage-tenants>
      <usage-tenant>2</usage-tenant>
    </usage-tenants>
    <burst-tenants>
      <burst-tenant>1</burst-tenant>
    </burst-tenants>
  </cdr>
</cdr-list>
```