



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

GVP Documentation Supplement

Corrections to `request-uri` Value

5/6/2025

Corrections to request-uri Value

DONE HERE under GVP as a Self-service IVR

SUMMARY: Corrections to the valid values listed for the option request-uri.

DOCUMENT: The next publication of the [GVP 8.5 Deployment Guide](#) will include these revisions.

CHAPTER: Appendix E: Resource Manager High Availability

SECTION: GVP as a Self-service IVR

The table **Trunk Group DN Configuration (Outbound)** on page 405 of the [GVP 8.5 Deployment Guide](#) requires this correction:

For HPE, configure GVP as a Trunk Group DN in SIP Server:

Table: Trunk Group DN Configuration (Outbound)

Parameter Name	Parameter Value
...	
request-uri	sip:msml<RMHost>:<RMport>;gvp-tenantid=<Tenant-Name> sip:msml<RMHost>:<RMport>;gvp-tenant-id=[<Tenant-Name>]

SECTION: GVP as an Outbound Media Server

The unnamed table beneath "Configure GVP as a Trunk Group with these parameters:" on page 407 requires this correction:

Parameter Name	Parameter Value
...	
request-uri	sip:msml<RMHost>:<RMport>;gvp-tenantid=<Tenant-Name> sip:msml<RMHost>:<RMport>;media-service=cpd;gvp-tenant-id=[<Tenant-Name>] Note: If Call Progress Analysis will not occur, then remove the item media-service=cpd from the request-uri value, to avoid false reporting in Resource Manager.