



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

# Widgets Reference

API Commands

---

## Contents

- 1 API Commands
  - 1.1 configure
  - 1.2 open
  - 1.3 close
  - 1.4 minimize
  - 1.5 endChat
  - 1.6 invite
  - 1.7 reInvite
  - 1.8 injectMessage
  - 1.9 showChatButton
  - 1.10 hideChatButton
  - 1.11 showOverlay
  - 1.12 hideOverlay

# API Commands

Once you've registered your own plugin on the bus, you can call commands on other registered plugins. Below we'll quickly register a new plugin on the bus using the global bus object.

## Important

The global bus object is a debug tool. When implementing Widgets on your own site, do not use the global bus object to register your custom plugins. Instead, see [Widgets Extensions](#) for more information about extending Genesys Widgets.

```
var oMyPlugin = window._genesys.widgets.bus.registerPlugin('MyPlugin');  
oMyPlugin.command('WebChat.open');
```

## configure

Internal use only. The main App plugin shares configuration settings to widgets using each widget's configure command. The configure command can only be called once at startup. Calling configure again after startup may result in unpredictable behavior.

## Example

```
oMyPlugin.command('WebChat.configure', {  
  emojis: true,  
  actionsMenu: true,  
  inviteOnRestoreTimeout: true,  
  uploadsEnabled: true,  
  confirmCloseEnabled: true,  
  chatButton: {  
    enabled: false,  
    openDelay: 1000,  
    template: '<span>Done</span>',  
    effect: 'fade',  
    effectDuration: 1000,  
    hideDuringInvite: true  
  },  
  proactive: {  
    enabled: false,  
    idleTime: 1000,  
    cancelTimer: 1000  
  },  
});
```

```
        autoInvite:{
            enabled: true,
            timeToInviteSeconds: 1000,
            inviteTimeoutSeconds: 1000
        }
    }).done(function(e){
        // WebChat configured successfully
    }).fail(function(e){
        // WebChat wasn't configured properly
    });
```

## Options

| Option                      | Type    | Description                                                                                                          |
|-----------------------------|---------|----------------------------------------------------------------------------------------------------------------------|
| emojis                      | boolean | Enable/disable Emoji menu inside chat message input.                                                                 |
| actionsMenu                 | boolean | Enable/disable actions menu next to chat message input.                                                              |
| inviteOnRestoreTimeout      | boolean | If set to true the invite will restore itself back on the screen after back end services are back online.            |
| uploadsEnabled              | boolean | If set to true you will be able to upload files during the chat session.                                             |
| confirmFormCloseEnabled     | boolean | If set to false confirm box will not show when closing chat box.                                                     |
| chatButton.enabled          | boolean | Enable/disable chat button on screen.                                                                                |
| chatButton.openDelay        | number  | Number of milliseconds before displaying chat button on screen.                                                      |
| chatButton.template         | string  | Custom HTML string template for chat button.                                                                         |
| chatButton.effect           | string  | Type of animation effect when revealing chat button. 'slide' or 'fade'.                                              |
| chatButton.effectDuration   | number  | Length of animation effect in milliseconds.                                                                          |
| chatButton.hideDuringInvite | boolean | When auto-invite feature is activated, hide the chat button. When invite is dismissed, reveal the chat button again. |
| proactive.enabled           | boolean | Enable/disable web engagement.                                                                                       |
| proactive.idleTimer         | number  | Watch the number of seconds of                                                                                       |

---

| Option                          | Type    | Description                                                                                                      |
|---------------------------------|---------|------------------------------------------------------------------------------------------------------------------|
|                                 |         | idle time to invite a customer back.                                                                             |
| proactive.cancelTimer           | number  | Number of seconds to cancel an invite from web engagement.                                                       |
| autoInvite.enabled              | boolean | Enable/disable auto-invite feature. Automatically invites user to chat after user idles on page for preset time. |
| autoInvite.timeToInviteSeconds  | number  | Number of seconds of idle time before inviting customer to chat.                                                 |
| autoInvite.inviteTimeoutSeconds | number  | Number of seconds to wait, after showing invite, before closing chat invite.                                     |

## Resolutions

| Status   | When                                            | Returns                 |
|----------|-------------------------------------------------|-------------------------|
| resolved | When configuration options are provided and set | n/a                     |
| rejected | When no configuration options are provided      | 'Invalid configuration' |

## open

Opens the WebChat UI.

## Example

```
oMyPlugin.command('WebChat.open', {
  userData: {},
  form: {
    autoSubmit: false,
    firstname: 'John',
    lastname: 'Smith',
    email: 'John@mail.com',
    subject: 'Customer Satisfaction'
  }
}).done(function(e){
  // WebChat opened successfully
}).fail(function(e){
```

```
    // WebChat isn't open or no active chat session  
});
```

## Options

| Option          | Type    | Description                                                                                                                |
|-----------------|---------|----------------------------------------------------------------------------------------------------------------------------|
| userData        | object  | Object containing arbitrary data that gets sent to the server. Overrides userData set in the webchat configuration object. |
| form            | object  | Object containing form data to prefill in the chat entry form and optionally auto-submit the form.                         |
| form.autoSubmit | boolean | Automatically submit the form. Useful for bypassing the entry form step.                                                   |
| form.firstname  | string  | Value for the first name entry field.                                                                                      |
| form.lastname   | string  | Value for the last name entry field.                                                                                       |
| form.email      | string  | Value for the email entry field.                                                                                           |
| form.subject    | string  | Value for the subject entry field.                                                                                         |

## Resolutions

| Status   | When                                | Returns          |
|----------|-------------------------------------|------------------|
| resolved | When WebChat is successfully opened | n/a              |
| rejected | When WebChat is already open        | 'already opened' |

## close

Closes the WebChat UI.

## Example

```
oMyPlugin.command('WebChat.close').done(function(e){  
    // WebChat closed successfully  
});
```

```
}).fail(function(e){  
    // WebChat is already closed or no active chat session  
});
```

### Resolutions

| Status   | When                                | Returns          |
|----------|-------------------------------------|------------------|
| resolved | When WebChat is successfully closed | n/a              |
| rejected | When WebChat is already closed      | 'already closed' |

## minimize

Minimize or unminimize WebChat UI.

### Example

```
oMyPlugin.command('WebChat.minimize').done(function(e){  
    // WebChat minimized successfully  
}).fail(function(e){  
    // WebChat ignores command  
});
```

### Options

| Option    | Type    | Description                                                                                                                          |
|-----------|---------|--------------------------------------------------------------------------------------------------------------------------------------|
| minimized | boolean | Rather than toggling the current minimized state you can specify the minified state directly: true = minimized, false = unminimized. |

### Resolutions

| Status   | When   | Returns                 |
|----------|--------|-------------------------|
| resolved | Always | n/a                     |
| rejected | Never  | 'Invalid configuration' |

## endChat

Starts the 'end chat' procedure. User may be prompted to confirm.

### Example

```
oMyPlugin.command('WebChat.endChat').done(function(e){  
    // WebChat ended a chat successfully  
}).fail(function(e){  
    // WebChat has no active chat session  
});
```

### Resolutions

| Status   | When                                        | Returns                                  |
|----------|---------------------------------------------|------------------------------------------|
| resolved | When there is an active chat session to end | n/a                                      |
| rejected | When there is no active chat session to end | 'there is no active chat session to end' |

## invite

Show an invitation to chat using the Toaster popup element. Text shown in invitation can be edited in the localization file.

### Example

```
oMyPlugin.command('WebChat.invite').done(function(e){  
    // WebChat invited successfully  
}).fail(function(e){  
    // WebChat is already open and will be ignored  
});
```

## Resolutions

| Status   | When                                                                               | Returns                                          |
|----------|------------------------------------------------------------------------------------|--------------------------------------------------|
| resolved | When WebChat is closed and the toast element is created successfully               | n/a                                              |
| rejected | When WebChat is already open (prevents inviting a user that is already in a chat). | 'Chat is already open. Ignoring invite command.' |

## reInvite

When an active chat session is unable to restore, this invitation will offer the user to start a new chat. Text shown in invitation can be edited in the localization file.

## Example

```
oMyPlugin.command('WebChat.reInvite').done(function(e){  
    // WebChat reinvited successfully  
}).fail(function(e){  
    // WebChat is already open and will be ignored  
});
```

## Resolutions

| Status   | When                                                                                                                           | Returns                                          |
|----------|--------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------|
| resolved | When WebChat is closed, the config item 'webchat.inviteOnRestoreTimeout' is set, and the toast element is created successfully | n/a                                              |
| rejected | When WebChat is already open. Prevents inviting a user that is already in a chat                                               | 'Chat is already open. Ignoring invite command.' |

## injectMessage

Inject a custom message into the chat transcript. Useful for extending WebChat functionality with other Genesys products.

## Example

```
oMyPlugin.command('WebChat.injectMessage', {  
  type: 'text',  
  name: 'person',  
  text: 'hello',  
  custom: false,  
  bubble:{  
    fill: '#00FF00',  
    radius: '4px',  
    time: false,  
    name: false,  
    direction: 'right',  
    avatar:{  
      custom: '<div>word</div>',  
      icon: 'email'  
    }  
  }  
}).done(function(e){  
  // WebChat injected a message successfully  
  // e.data == The message HTML reference (jQuery wrapped set)  
}).fail(function(e){  
  // WebChat isn't open or no active chat  
});
```

## Options

| Option        | Type                              | Description                                                                                                                                                        |
|---------------|-----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| type          | string                            | Switch the rendering type of the injected message between text and html.                                                                                           |
| name          | string                            | Specify a name label for the message to identify what service or widget has injected the message.                                                                  |
| text          | string                            | The content of the message. Either plain text or HTML.                                                                                                             |
| custom        | boolean                           | If set to true, the default message template will not be used, allowing you to inject a highly customized HTML block unconstrained by the normal message template. |
| bubble.fill   | string of valid CSS color value   | The content of the message. Either plain text or HTML.                                                                                                             |
| bubble.radius | string of valid CSS border radius | The border radius you'd like for                                                                                                                                   |

---

| Option               | Type                     | Description                                                                  |
|----------------------|--------------------------|------------------------------------------------------------------------------|
|                      | vale                     | the bubble.                                                                  |
| bubble.time          | boolean                  | If you'd like to show the timestamp for the bubble.                          |
| bubble.name          | boolean                  | If you'd like to show the name for the bubble.                               |
| bubble.direction     | string                   | Which direction you want the message bubble to come from.                    |
| bubble.avatar.custom | string or HTML reference | Change the content of the html that would be the avatar for the chat bubble. |
| bubble.avatar.icon   | class name               | Generated common library provided for icon name.                             |

## Resolutions

| Status   | When                                                             | Returns                                                             |
|----------|------------------------------------------------------------------|---------------------------------------------------------------------|
| resolved | When WebChat is open and there is an active chat session         | An HTML reference (jQuery wrapped set) to the new injected message. |
| rejected | When WebChat is not open and/or there was no active chat session | 'No chat session to inject into'                                    |

## showChatButton

Makes the standalone chat button visible on the screen using either the default template and CSS or customer-defined ones.

### Example

```
oMyPlugin.command('WebChat.showChatButton', {  
    openDelay: 1000,  
    duration: 1500  
}).done(function(e){  
    // WebChat shows chat button successfully  
}).fail(function(e){  
    // WebChat button is already visible, side bar is active and overrides the chat  
    button, or chat button is disabled in configuration  
});
```

## Options

| Option    | Type   | Description                                                            |
|-----------|--------|------------------------------------------------------------------------|
| openDelay | number | Duration in milliseconds to delay showing the chat button on the page. |
| duration  | number | Duration in milliseconds for the show and hide animation.              |

## Resolutions

| Status   | When                                                                                                                      | Returns                                                   |
|----------|---------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------|
| resolved | When the chat button is enabled in the configuration, is currently not visible, and the SideBar plugin is not initialized | n/a                                                       |
| rejected | When the chat button is not enabled in the configuration, or it's already visible, or the SideBar plugin is initialized   | 'Chat button is already visible. Ignoring command.'       |
| rejected | When the sidebar plugin is active the standalone chat button will be disabled automatically                               | 'SideBar is active and overrides the default chat button' |

## hideChatButton

Hides the standalone chat button.

## Example

```
oMyPlugin.command('WebChat.hideChatButton', {duration: 1500}).done(function(e){
    // WebChat hid chat button successfully
}).fail(function(e){
    // WebChat button is already hidden
});
```

## Options

| Option   | Type   | Description                                               |
|----------|--------|-----------------------------------------------------------|
| duration | number | Duration in milliseconds for the show and hide animation. |

## Resolutions

| Status   | When                                      | Returns                                            |
|----------|-------------------------------------------|----------------------------------------------------|
| resolved | When the chat button is currently visible | n/a                                                |
| rejected | When the chat button is already hidden    | 'Chat button is already hidden. Ignoring command.' |

## showOverlay

A slide-down overlay the opens over WebChat's content. You can fill this overlay with content such as disclaimers, articles, and other information.

## Example

```
oMyPlugin.command('WebChat.showOverlay', {
    html: '<div>Example text</div>',
    hideFooter: false
}).done(function(e){
    // WebChat successfully shows overlay
}).fail(function(e){
    // WebChat isn't open
});
```

## Options

| Option     | Type                     | Description                                                  |
|------------|--------------------------|--------------------------------------------------------------|
| html       | string or HTML reference | The HTML content you want to display in the overlay.         |
| hideFooter | boolean                  | Normally the overlay appears between the titlebar and footer |

---

| Option | Type | Description                                                                                                                                                                       |
|--------|------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|        |      | bar. Set this to true to have the overlay overlap the footer to gain a bit more vertical space. This should only be used in special cases. For general use, don't set this value. |

## Resolutions

| Status   | When                                        | Returns                                          |
|----------|---------------------------------------------|--------------------------------------------------|
| resolved | When WebChat is open and the overlay opens. |                                                  |
| rejected | When WebChat is not currently open.         | WebChat is not currently open. Ignoring command. |

## hideOverlay

Hides the slide-down overlay.

## Example

```
oMyPlugin.command('WebChat.hideOverlay').done(function(e){
    // WebChat hid overlay successfully
}).fail(function(e){
    // WebChat isn't open
});
```

## Resolutions

| Status   | When                                         | Returns                                          |
|----------|----------------------------------------------|--------------------------------------------------|
| resolved | When WebChat is open and the overlay closes. |                                                  |
| rejected | When WebChat is not currently open.          | WebChat is not currently open. Ignoring command. |