



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Widgets Reference

Configuration

Contents

- 1 Configuration
 - 1.1 Description
 - 1.2 Example
 - 1.3 Options

Configuration

Description

ClickToCall and ClickToCallService share the configuration namespace '_genesys.widgets.clicktocall'. ClickToCall has UI options while ClickToCallService has connection options.

Example

```
window._genesys.widgets.clicktocall = {  
    'ajaxTimeout' : 3000,  
    'provideAccessCode' : true,  
    'dataURL' : 'http://www.myphoneservice.org',  
    'apikey' : 'YOUR_API_KEY',  
    'userData' : {}  
};
```

Options

Name	Type	Description	Default	Required
ajaxTimeout	Number	Sets the default ajax timeout in milliseconds.	3000	false
provideAccessCode	boolean	Enables or disables the use of a dial in access code for user verification.	true	false
dataURL	string	URL of GMS ClickToCall API endpoint.	n/a	true
apikey	string or number	Apigee Proxy secure token.	n/a	Yes, if using Apigee Proxy.
userData	object	Arbitrary JSON attached data to include while requesting ClickToCall phone number.	{}	n/a