



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

## Widgets Reference

API Events

# API Events

Once you've registered your own plugin on the bus, you can subscribe and listen for published events. Below we'll quickly register a new plugin on the bus using the global bus object.

## Important

The global bus object is a debug tool. When implementing Widgets on your own site, do not use the global bus object to register your custom plugins. Instead, see [Widgets Extensions](#) for more information about extending Genesys Widgets.

```
var oMyPlugin = window._genesys.widgets.bus.registerPlugin('MyPlugin');  
oMyPlugin.subscribe('ClickToCallService.ready', function(e){});
```

| Name           | Description  | Data  |
|----------------|--|---|
| ready          | ClickToCallService is initialized and ready to accept commands.    | n/a   |
| restored       | ClickToCallService has restored the currently active phone number. | {bRestoreSuccess: (boolean),<br>sPhoneNumber: (string),<br>sPhoneTelHref: (string),<br>sAccessCode: (string),<br>iExipreTime: (number)} |
| numberReceived | ClickToCallService has received a phone number from the server.    | {sPhoneNumber: (string),<br>sPhoneTelHref: (string),<br>sAccessCode: (string),<br>iExipreTime: (number)}                                |