



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Web Services API Reference

Ready

5/8/2025

Ready

This operation is part of the [Voice API](#) section of the [Web Services API](#).

Overview

Sets the current user to the Ready state. Ready is a **system-defined agent state** operation and is always available for use.

Request URL	/api/v2/me/channels/voice
HTTP method	POST
Required features	api-voice

Parameters

Parameter	Value
operationName	Ready
workmode	This optional parameter specifies which workmode is applied to the Ready operation. Valid values are ManualIn and AutoIn.

Sample

Request

```
POST /api/v2/me/channels/voice
{
  "operationName": "Ready"
}
```

HTTP response

```
{
  "statusCode": 0
}
```

CometD notification

```
{
```

```
"data": {
  "messageType": "DeviceStateChangeMessage",
  "devices": [
    {
      "id": "74152ed8-858f-4a33-9e96-36213a678d30",
      "deviceState": "Active",
      "userState": {
        "id": "9430250E-0A1B-421F-B372-F29E69366DED",
        "displayName": "Ready",
        "state": "Ready"
      },
      "phoneNumber": "5000",
      "e164Number": "5000",
      "telephonyNetwork": "Private",
      "doNotDisturb": "Off",
      "voiceEnvironmentUri": "http://127.0.0.1:8080/api/v2/voice-environments/
370ef5e6-9e3c-4d91-9588-7f4dfe67e011",
      "capabilities": [
        "ForwardCallsOn"
      ]
    }
  ]
},
"channel": "/v2/me/devices"
}
```