



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Web Services API Reference

SwapCalls

5/3/2025

SwapCalls

This operation is part of the [Voice API](#) section of the [Web Services API](#).

Overview

Swaps between two calls when one call is held and the other is established.

Request URL	/api/v2/me/calls/{id}
HTTP method	POST
Required features	api-voice

Parameters

Parameter	Value
operationName	SwapCalls
otherCallUri	The URI of the call to swap.

Sample 1

Request

```
POST api/v2/me/calls/013V08JRL498H10I04000VTAES00000S
{
  "operationName": "SwapCalls",
  "otherCallUri": "http://127.0.0.1:8080/api/v2/me/calls/01RCC3N118B1V0SL807GK2LAES00000P"
}
```

HTTP response

```
{
  "statusCode": 0
}
```

CometD notification

The SwapCalls operations results in two notifications. One for the call that is placed on hold, and a second for the held call is retrieved.

```
{
  "data":{
    "notificationType":"StatusChange",
    "call":{
      "id":"01RCC3N118B1V0SL807GK2LAES00000P",
      "state":"Established",
      "callUuid":"01RCC3N118B1V0SL807GK2LAES00000P",
      "connId":"0071027198180019",
      "deviceUri":"http://127.0.0.1:8080/api/v2/devices/631608b3-ceb1-472b-
ba05-2ae39555b0d1",
      "participants":[
        {
          "e164Number":"",
          "formattedPhoneNumber":"15001",
          "phoneNumber":"15001",
          "digits":"15001"
        }
      ],
      "dnis":"15001",
      "callType":"Internal",
      "capabilities":[
        "UpdateUserData",
        "SendDtmf",
        "SwapCalls",
        "InitiateConference",
        "Hold",
        "SingleStepTransfer",
        "InitiateTransfer",
        "AttachUserData",
        "CompleteConference",
        "DeleteUserDataPair",
        "SingleStepConference",
        "DeleteUserData",
        "Hangup",
        "CompleteTransfer"
      ],
      "duration":"156",
      "mute":"Off",
      "supervisorListeningIn":false,
      "monitoredUserMuted":false,
      "monitoring":false,
      "uri":"http://127.0.0.1:8080/api/v2/me/calls/01RCC3N118B1V0SL807GK2LAES00000P",
      "path":"/calls/01RCC3N118B1V0SL807GK2LAES00000P"
    },
    "phoneNumber":"15000",
    "extensions":{
      "BusinessCall":0
    },
    "messageType":"CallStateChangeMessage"
  },
  "channel":"/v2/me/calls"
}

{
  "data":{
    "notificationType":"StatusChange",
    "call":{
      "id":"01RCC3N118B1V0SL807GK2LAES00000Q",
      "state":"Held",
      "callUuid":"01RCC3N118B1V0SL807GK2LAES00000Q",
      "connId":"007102719818001a",
      "deviceUri":"http://127.0.0.1:8080/api/v2/devices/631608b3-ceb1-472b-
ba05-2ae39555b0d1",
```

```
    "participants": [
      {
        "e164Number": "",
        "formattedPhoneNumber": "15002",
        "phoneNumber": "15002",
        "digits": "15002"
      }
    ],
    "dnis": "15002",
    "callType": "Consult",
    "capabilities": [
      "UpdateUserData",
      "SendDtmf",
      "SwapCalls",
      "InitiateConference",
      "Hold",
      "SingleStepTransfer",
      "InitiateTransfer",
      "AttachUserData",
      "CompleteConference",
      "DeleteUserDataPair",
      "SingleStepConference",
      "DeleteUserData",
      "Hangup",
      "CompleteTransfer"
    ],
    "duration": "129",
    "mute": "Off",
    "supervisorListeningIn": false,
    "monitoredUserMuted": false,
    "monitoring": false,
    "uri": "http://127.0.0.1:8080/api/v2/me/calls/01RCC3N118B1V0SL807GK2LAES00000Q",
    "path": "/calls/01RCC3N118B1V0SL807GK2LAES00000Q"
  },
  "phoneNumber": "15000",
  "messageType": "CallStateChangeMessage"
},
"channel": "/v2/me/calls"
}
```

Sample 2

The following examples describe the full set of requests and events that demonstrate using the SwapCalls operation.

The agent receives a notification of an inbound call:

```
{
  "data": {
    "notificationType": "StatusChange",
    "call": {
      "id": "013V08JRL498H10I04000VTAES00000R",
      "state": "Ringing",
      "callUuid": "013V08JRL498H10I04000VTAES00000R",
      "connId": "0071023821aec01b",
      "deviceUri": "http://127.0.0.1:8080/api/v2/devices/efelab32-53f9-43ce-b65e-5768c61f7d4a",
      "participants": [
        {
```

```

        "e164Number": "",
        "formattedPhoneNumber": "5000",
        "phoneNumber": "5000",
        "digits": "5000"
    },
    ],
    "dnis": "5005",
    "callType": "Internal",
    "capabilities": [
        "Answer",
        "DeleteUserDataPair",
        "AttachUserData",
        "DeleteUserData",
        "UpdateUserData"
    ],
    "duration": "0",
    "mute": "Off",
    "supervisorListeningIn": false,
    "monitoredUserMuted": false,
    "uri": "http://127.0.0.1:8080/api/v2/me/calls/013V08JRL498H10I04000VTAES000000R",
    "path": "/calls/013V08JRL498H10I04000VTAES000000R"
},
"phoneNumber": "5005",
"extensions": {
    "WrapUpTime": 0,
    "BusinessCall": 0
},
"messageType": "CallStateChangeMessage"
},
"channel": "/v2/me/calls"
}

```

The agent answers the inbound call and receives notification of the call state change:

```

{
  "data": {
    "notificationType": "StatusChange",
    "call": {
      "id": "013V08JRL498H10I04000VTAES000000R",
      "state": "Established",
      "callUuid": "013V08JRL498H10I04000VTAES000000R",
      "connId": "0071023821aec01b",
      "deviceUri": "http://127.0.0.1:8080/api/v2/devices/efelab32-53f9-43ce-
b65e-5768c61f7d4a",
      "participants": [
        {
          "e164Number": "",
          "formattedPhoneNumber": "5000",
          "phoneNumber": "5000",
          "digits": "5000"
        }
      ],
      "dnis": "5005",
      "callType": "Internal",
      "capabilities": [
        "DeleteUserDataPair",
        "AttachUserData",
        "Hangup",
        "DeleteUserData",
        "Hold",
        "SendDtmf",
        "InitiateConference",
        "InitiateTransfer",

```

```
        "SingleStepConference",
        "UpdateUserData",
        "SingleStepTransfer"
    ],
    "duration": "5",
    "mute": "Off",
    "supervisorListeningIn": false,
    "monitoredUserMuted": false,
    "uri": "http://127.0.0.1:8080/api/v2/me/calls/013V08JRL498H10I04000VTAES00000R",
    "path": "calls/013V08JRL498H10I04000VTAES00000R"
  },
  "phoneNumber": "5005",
  "extensions": {
    "WrapUpTime": 0,
    "BusinessCall": 0
  },
  "messageType": "CallStateChangeMessage"
},
"channel": "/v2/me/calls"
}
```

The agent requests the inbound call be placed on hold:

```
POST api/v2/me/calls/013V08JRL498H10I04000VTAES00000R
{
  "operationName": "Hold"
}
```

Notification is received of the call being held:

```
{
  "data": {
    "notificationType": "StatusChange",
    "call": {
      "id": "013V08JRL498H10I04000VTAES00000R",
      "state": "Held",
      "callUuid": "013V08JRL498H10I04000VTAES00000R",
      "connId": "0071023821aec01b",
      "deviceUri": "http://127.0.0.1:8080/api/v2/devices/efe1ab32-53f9-43ce-
b65e-5768c61f7d4a",
      "participants": [
        {
          "e164Number": "",
          "formattedPhoneNumber": "5000",
          "phoneNumber": "5000",
          "digits": "5000"
        }
      ],
      "dnis": "5005",
      "callType": "Internal",
      "capabilities": [
        "Retrieve",
        "DeleteUserDataPair",
        "AttachUserData",
        "Hangup",
        "DeleteUserData",
        "InitiateConference",
        "InitiateTransfer",
        "SingleStepConference",
        "UpdateUserData",
        "SingleStepTransfer"
      ]
    }
  }
}
```

```
        "duration": "10",
        "mute": "Off",
        "supervisorListeningIn": false,
        "monitoredUserMuted": false,
        "uri": "http://127.0.0.1:8080/api/v2/me/calls/013V08JRL498H10I04000VTAES00000R",
        "path": "/calls/013V08JRL498H10I04000VTAES00000R"
    },
    "phoneNumber": "5005",
    "extensions": {
        "WrapUpTime": 0,
        "BusinessCall": 0
    },
    "messageType": "CallStateChangeMessage"
},
"channel": "/v2/me/calls"
}
```

The agent requests the second call be made:

```
POST api/v2/me/devices/efelab32-53f9-43ce-b65e-5768c61f7d4a/calls
{
  "operationName": "Dial",
  "destination": {
    "phoneNumber": "5001"
  }
}
```

The agent receives notification that the second call is dialing:

```
{
  "data": {
    "notificationType": "StatusChange",
    "call": {
      "id": "013V08JRL498H10I04000VTAES00000S",
      "state": "Dialing",
      "callUuid": "013V08JRL498H10I04000VTAES00000S",
      "connId": "0071023821aec01c",
      "deviceUri": "http://127.0.0.1:8080/api/v2/devices/efelab32-53f9-43ce-
b65e-5768c61f7d4a",
      "participants": [
        {
          "e164Number": "",
          "formattedPhoneNumber": "5001",
          "phoneNumber": "5001",
          "digits": "5001"
        }
      ],
      "dnis": "5001",
      "callType": "Internal",
      "capabilities": [
        "DeleteUserDataPair",
        "AttachUserData",
        "Hangup",
        "DeleteUserData",
        "SendDtmf",
        "SwapCalls",
        "UpdateUserData",
        "CompleteTransfer"
      ],
      "duration": "0",
      "mute": "Off",
      "supervisorListeningIn": false,
    }
  }
}
```

```
    "monitoredUserMuted":false,
    "uri":"http://127.0.0.1:8080/api/v2/me/calls/013V08JRL498H10I04000VTAES00000S",
    "path":"/calls/013V08JRL498H10I04000VTAES00000S"
  },
  "phoneNumber":"5005",
  "extensions":{
    "WrapUpTime":0,
    "BusinessCall":0
  },
  "messageType":"CallStateChangeMessage"
},
"channel":"/v2/me/calls"
}
```

and then notification that the second call is answered:

```
{
  "data":{
    "notificationType":"StatusChange",
    "call":{
      "id":"013V08JRL498H10I04000VTAES00000S",
      "state":"Established",
      "callUuid":"013V08JRL498H10I04000VTAES00000S",
      "connId":"0071023821aec01c",
      "deviceUri":"http://127.0.0.1:8080/api/v2/devices/efelab32-53f9-43ce-
b65e-5768c61f7d4a",
      "participants":[
        {
          "e164Number":"",
          "formattedPhoneNumber":"5001",
          "phoneNumber":"5001",
          "digits":"5001"
        }
      ],
      "dnis":"5001",
      "callType":"Internal",
      "capabilities":[
        "DeleteUserDataPair",
        "AttachUserData",
        "Hangup",
        "DeleteUserData",
        "Hold",
        "SendDtmf",
        "InitiateConference",
        "SwapCalls",
        "InitiateTransfer",
        "SingleStepConference",
        "UpdateUserData",
        "SingleStepTransfer",
        "CompleteTransfer",
        "CompleteConference"
      ],
      "duration":"10",
      "mute":"Off",
      "supervisorListeningIn":false,
      "monitoredUserMuted":false,
      "uri":"http://127.0.0.1:8080/api/v2/me/calls/013V08JRL498H10I04000VTAES00000S",
      "path":"/calls/013V08JRL498H10I04000VTAES00000S"
    },
    "phoneNumber":"5005",
    "extensions":{
      "WrapUpTime":0,
      "BusinessCall":0
    }
  }
}
```

```
    },
    "messageType": "CallStateChangeMessage"
  },
  "channel": "/v2/me/calls"
}
```

The agent then sends the SwapCalls request:

```
POST api/v2/me/calls/013V08JRL498H10I04000VTAES00000S
{
  "operationName": "SwapCalls",
  "otherCallUri": "http://localhost:8080/api/v2/me/calls/013V08JRL498H10I04000VTAES00000R"
}
```

The agent then receives notification that the second call is now held:

```
{
  "data": {
    "notificationType": "StatusChange",
    "call": {
      "id": "013V08JRL498H10I04000VTAES00000S",
      "state": "Held",
      "callUuid": "013V08JRL498H10I04000VTAES00000S",
      "connId": "0071023821aec01c",
      "deviceUri": "http://127.0.0.1:8080/api/v2/devices/efelab32-53f9-43ce-
b65e-5768c61f7d4a",
      "participants": [
        {
          "e164Number": "",
          "formattedPhoneNumber": "5001",
          "phoneNumber": "5001",
          "digits": "5001"
        }
      ],
      "dnis": "5001",
      "callType": "Internal",
      "capabilities": [
        "Retrieve",
        "DeleteUserDataPair",
        "AttachUserData",
        "Hangup",
        "DeleteUserData",
        "InitiateConference",
        "InitiateTransfer",
        "SingleStepConference",
        "UpdateUserData",
        "SingleStepTransfer"
      ],
      "duration": "41",
      "mute": "Off",
      "supervisorListeningIn": false,
      "monitoredUserMuted": false,
      "uri": "http://127.0.0.1:8080/api/v2/me/calls/013V08JRL498H10I04000VTAES00000S",
      "path": "/calls/013V08JRL498H10I04000VTAES00000S"
    },
    "phoneNumber": "5005",
    "extensions": {
      "WrapUpTime": 0,
      "BusinessCall": 0
    },
    "messageType": "CallStateChangeMessage"
  },
}
```

```
    "channel": "/v2/me/calls"  
  }
```

and to complete the operation, a notification that the first call is now be retrieved from hold:

```
{  
  "data": {  
    "notificationType": "StatusChange",  
    "call": {  
      "id": "013V08JRL498H10I04000VTAES00000R",  
      "state": "Established",  
      "callUuid": "013V08JRL498H10I04000VTAES00000R",  
      "connId": "0071023821aec01b",  
      "deviceUri": "http://127.0.0.1:8080/api/v2/devices/efelab32-53f9-43ce-  
b65e-5768c61f7d4a",  
      "participants": [  
        {  
          "e164Number": "",  
          "formattedPhoneNumber": "5000",  
          "phoneNumber": "5000",  
          "digits": "5000"  
        }  
      ],  
      "dnis": "5005",  
      "callType": "Internal",  
      "capabilities": [  
        "DeleteUserDataPair",  
        "AttachUserData",  
        "Hangup",  
        "DeleteUserData",  
        "Hold",  
        "SendDtmf",  
        "InitiateConference",  
        "SwapCalls",  
        "InitiateTransfer",  
        "SingleStepConference",  
        "UpdateUserData",  
        "SingleStepTransfer",  
        "CompleteTransfer",  
        "CompleteConference"  
      ],  
      "duration": "60",  
      "mute": "Off",  
      "supervisorListeningIn": false,  
      "monitoredUserMuted": false,  
      "uri": "http://127.0.0.1:8080/api/v2/me/calls/013V08JRL498H10I04000VTAES00000R",  
      "path": "/calls/013V08JRL498H10I04000VTAES00000R"  
    },  
    "phoneNumber": "5005",  
    "extensions": {  
      "WrapUpTime": 0,  
      "BusinessCall": 0  
    },  
    "messageType": "CallStateChangeMessage"  
  },  
  "channel": "/v2/me/calls"  
}
```