



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Web Services API Reference

NotReady

12/12/2025

Contents

- [1 NotReady](#)
 - [1.1 Overview](#)
 - [1.2 Parameters](#)
 - [1.3 Sample](#)

NotReady

This operation is part of the [Supervisor Agent State Control API](#) section of the [Web Services API](#).

Overview

With this request, the supervisor can set an agent's channel status to NotReady, meaning that the agent is not available for phone calls on the voice channel, or is not available to receive interaction invitations for media channels.

Request URL	/api/v2/users/{userId}/channels/{channelId}
HTTP method	POST
Required features	api-supervisor-agent-control

Valid values for channelId are voice, chat, email, and other defined media types.

Parameters

Parameter	Value
operationName	NotReady

Sample

Request

```
POST api/v2/users/6c991eb2c1ba48d5b637d569a5295388/channels/email
{
  "operationName": "NotReady"
}
```

HTTP response

```
{
  "statusCode": "0",
}
```

Notification

The agent whose state has been updated receives notification:

```
{
  "channel": "/v2/me/channels",
  "data": {
    "channels": [
      {
        "channel": "email",
        "dndState": "Off",
        "userState": {
          "displayName": "Not Ready",
          "id": "900D55CC-2BB0-431F-8BF9-D3525B383BE6",
          "state": "NotReady"
        }
      }
    ],
    "messageType": "ChannelStateChangeMessageV2"
  }
}
```