

GENESYS

This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Web Services API Reference

Outbound Campaign Resource

Outbound Campaign Resource

Contents

- 1 Outbound Campaign Resource
 - 1.1 Sample Data
 - 1.2 Resource Details

The Outbound Campaign resource contains information about the outbound campaign, including the name and dialing mode. Outbound campaigns have the following endpoints: /api/v2/me/outbound-campaigns and /api/v2/me/outbound-campaigns /<campaing-name>.

Sample Data

```
{
    "campaign": {
        "groupName": " Outbound Contact Campaigns",
        "groupDescription": "",
        "description": "",
        "applicationId": 124,
        "state": "Started",
        "name": "Outbound Contact - Customer Satisfaction Campaign",
        "dialingMode": "Preview",
        "devicePath": "/devices/1234567890"
    }
}
```

Resource Details

| Field | Description |
|------------------|--|
| groupName | The name of the agent or place group assigned to the outbound campaign. |
| groupDescription | A description of the agent or place group assigned to the outbound campaign. |
| description | A description of the outbound campaign. |
| applicationId | The Outbound Contact Server application ID. |
| state | The status of the campaign, such as Started or Loaded. |
| name | The name of the outbound campaign. |
| dialingMode | The dialing mode to use as the default for the agent group in a campaign. The dialing modes are Progressive, Predictive, Preview, Push Preview, and Power GVP. |
| devicePath | The path to a device. |

Important

Not all fields are sent for each response.