



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

# Web Services API Reference

End Preview Session

5/10/2025

# End Preview Session

This operation is part of the [Outbound API](#) section of the [Web Services API](#).

## Overview

This request ends a preview mode outbound session for the current user and specified campaign.

|                          |                                               |
|--------------------------|-----------------------------------------------|
| <b>Request URL</b>       | /api/v2/me/outbound-campaigns/<campaign-name> |
| <b>HTTP Method</b>       | POST                                          |
| <b>Required Features</b> | api-voice-outbound                            |

## Parameters

| Parameter     | Value                                                                                                                                                                                                   | Required |
|---------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------|
| operationName | EndPreviewSession                                                                                                                                                                                       | Yes      |
| applicationId | The unique identifier of the Outbound Contact Server application.                                                                                                                                       | Yes      |
| devicePath    | The relative path to the device used for sending the TLib request.                                                                                                                                      | Yes      |
| referenceId   | A unique identifier used to map the API call to the CometD response. If the request contains a referenceId, Web Services sends an acknowledgement or other event with the same reference ID via CometD. | No       |

## Samples

### Request

```
POST /api/v2/me/outbound-campaigns/<campaign-name>
{
  'operationName': 'EndPreviewSession',
  'applicationId': 124,
  'devicePath': '/devices/1234567890',
```

```
{  'referenceId': '123456789'}
```

## HTTP Response

```
{  'statusCode': 0}
```

## CometD Response

```
{  'messageType': 'OutboundCampaignMessage',  'notificationType': 'PreviewSessionEnded',  'campaign':    {    'devicePath': '/devices/5910b027-3e64-4c85-9b9d-87248a21d8a5',    'state': 'Started',    'applicationId': 134,    'name': 'Campaign1'  },  'referenceId': '123456789'}
```