



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

# Web Services API Reference

[Follow](#)

5/8/2025

# Follow

This operation is part of the [Twitter API](#) section of the [Web Services API](#).

## Overview

Enables monitoring of a specific Twitter user's tweets.

<b>Request URL</b>	/api/v2/me/tweets
<b>HTTP Method</b>	POST
<b>Required Features</b>	api-multimedia

## Parameters

Parameter	Value
operationName	Follow
twitterUserId	A Twitter user's numeric unique identifier.
from	The Twitter account name on whose behalf the Follow operation is performed.

## Samples

### Request

```
POST api/v2/me/tweets
{
  "operationName": "Follow",
  "twitterUserId": "1234567890",
  "from": "customer_support"
}
```

### HTTP Response

```
{
  "statusCode": 0,
  "referenceId": 1
}
```

## CometD Response

### Success

```
{
  "messageType": "TwitterOperationResponse",
  "referenceId": 1,
  "success": "true"
}
```

### Failure

```
{
  "messageType": "TwitterOperationResponse",
  "referenceId": 1,
  "success": "false",
  "errorMessage": "Unable to perform twitter operation"
}
```