



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Web Services API Reference

Reject

12/12/2025

Reject

This operation is part of the [Chat API](#) section of the [Web Services API](#).

Overview

When a new chat is offered, an agent can either **accept** or reject a new chat invitation.

This operation rejects an incoming chat.

Rejecting a chat allows an agent the opportunity to work on a different chat.

A successful reject request results in an empty HTTP 200 response and presents the chat to another agent.

Request URL	/api/v2/me/chats/{id}
HTTP Method	POST
Required Features	api-multimedia

Parameters

Parameter	Value
operationName	Reject

Sample

HTTP Request

POST on **/me/chats/{id}**

```
{
  "operationName": "Reject"
}
```

HTTP Response

```
{
  "status": 0
}
```

Reject

For details on the `statusCode` value, please refer to the [All Methods](#) sub-section of the [Return Values](#) page.

Notification

Here are the list of notifications received after rejecting a chat:

Status changed to Completed

```
{
  "referenceId": 5,
  "chat": {
    "participants": [
      ],
    "state": "Completed",
    "id": "0000Wa9CAM6W00FF",
    "uri": "http: //localhost: 8080/api/v2/chats/0000Wa9CAM6W00FF"
  },
  "notificationType": "StatusChange",
  "messageType": "ChatStateChangeMessage"
}
```