



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Web Services API Reference

InitiateTransfer

12/14/2025

InitiateTransfer

This operation is part of the [Voice API](#) section of the [Web Services API](#).

Overview

Initiates a two-step transfer to the specified destination. After initiating the transfer, you can use the [CompleteTransfer](#) operation to complete the transfer.

Request URL	/api/v2/me/calls/{id}
HTTP method	POST
Required features	api-voice

Parameters

Parameter	Value
operationName	InitiateTransfer
destination	A JSON object that includes the number to be dialed.
location	An optional parameter that is used by Web Services to set the location attribute for the corresponding T-Server requests.
userData	An optional JSON object that includes key/value data to be included with the call.

Sample 1

Request

```
POST api/v2/me/calls/01RCC3N118B1V0SL807GK2LAES000000M
{
  "operationName": "InitiateTransfer",
  "destination": {
    "phoneNumber": "15002"
  }
}
```

HTTP response

```
{
  "statusCode": 0
}
```

CometD notification

The first notification is that the original call has been placed on hold:

```
{
  "data": {
    "notificationType": "StatusChange",
    "call": {
      "id": "01RCC3N118B1V0SL807GK2LAES000000M",
      "state": "Held",
      "callUuid": "01RCC3N118B1V0SL807GK2LAES000000M",
      "connId": "0071027198180011",
      "deviceUri": "http://127.0.0.1:8080/api/v2/devices/631608b3-ceb1-472b-ba05-2ae39555b0d1",
      "participants": [
        {
          "e164Number": "",
          "formattedPhoneNumber": "15001",
          "phoneNumber": "15001",
          "digits": "15001"
        }
      ],
      "dnis": "15001",
      "callType": "Internal",
      "capabilities": [
        "UpdateUserData",
        "SwapCalls",
        "InitiateConference",
        "SingleStepTransfer",
        "InitiateTransfer",
        "AttachUserData",
        "DeleteUserDataPair",
        "SingleStepConference",
        "DeleteUserData",
        "Hangup",
        "CompleteTransfer"
      ],
      "duration": "99",
      "mute": "Off",
      "supervisorListeningIn": false,
      "monitoredUserMuted": false,
      "monitoring": false,
      "uri": "http://127.0.0.1:8080/api/v2/me/calls/01RCC3N118B1V0SL807GK2LAES000000M",
      "path": "/calls/01RCC3N118B1V0SL807GK2LAES000000M"
    },
    "phoneNumber": "15000",
    "messageType": "CallStateChangeMessage"
  },
  "channel": "/v2/me/calls"
}
```

The second notification is of the new consult call dialing:

```
{
```

```
"data":{
  "notificationType":"StatusChange",
  "call":{
    "id":"01RCC3N118B1V0SL807GK2LAES00000N",
    "state":"Dialing",
    "callUuid":"01RCC3N118B1V0SL807GK2LAES00000N",
    "connId":"0071027198180013",
    "deviceUri":"http://127.0.0.1:8080/api/v2/devices/631608b3-ceb1-472b-
ba05-2ae39555b0d1",
    "participants":[
      {
        "e164Number":"",
        "formattedPhoneNumber":"15002",
        "phoneNumber":"15002",
        "digits":"15002"
      }
    ],
    "dnis":"15002",
    "callType":"Consult",
    "capabilities":[
      "UpdateUserData",
      "SendDtmf",
      "SwapCalls",
      "AttachUserData",
      "DeleteUserDataPair",
      "DeleteUserData",
      "Hangup",
      "CompleteTransfer"
    ],
    "parentCallUri":"http://127.0.0.1:8080/api/v2/me/calls/
01RCC3N118B1V0SL807GK2LAES00000M",
    "duration":"0",
    "mute":"Off",
    "supervisorListeningIn":false,
    "monitoredUserMuted":false,
    "monitoring":false,
    "uri":"http://127.0.0.1:8080/api/v2/me/calls/01RCC3N118B1V0SL807GK2LAES00000N",
    "path":"/calls/01RCC3N118B1V0SL807GK2LAES00000N",
    "parentCallPath":"/calls/01RCC3N118B1V0SL807GK2LAES00000H"
  },
  "phoneNumber":"15000",
  "messageType":"CallStateChangeMessage"
},
"channel":"/v2/me/calls"
}
```

Sample 2

The following examples describe a full two-step transfer scenario from start to finish.

First, the agent receives a notification of the inbound call:

```
{
  "data":{
    "notificationType":"StatusChange",
    "call":{
      "id":"011DJV5JI898NB2L04000VTAES000005",
      "state":"Ringing",
      "callUuid":"011DJV5JI898NB2L04000VTAES000005",
```

```
    "connId": "007102385535e005",
    "deviceUri": "http://127.0.0.1:8080/api/v2/devices/efelab32-53f9-43ce-
b65e-5768c61f7d4a",
    "participants": [
      {
        "e164Number": "",
        "formattedPhoneNumber": "5000",
        "phoneNumber": "5000",
        "digits": "5000"
      }
    ],
    "dnis": "5005",
    "callType": "Internal",
    "capabilities": [
      "UpdateUserData",
      "DeleteUserData",
      "AttachUserData",
      "DeleteUserDataPair",
      "Answer"
    ],
    "duration": "0",
    "mute": "Off",
    "supervisorListeningIn": false,
    "monitoredUserMuted": false,
    "uri": "http://127.0.0.1:8080/api/v2/me/calls/011DJV5JI898NB2L04000VTAES000005",
    "path": "/calls/011DJV5JI898NB2L04000VTAES000005"
  },
  "phoneNumber": "5005",
  "extensions": {
    "WrapUpTime": 0,
    "BusinessCall": 0
  },
  "messageType": "CallStateChangeMessage"
},
"channel": "/v2/me/calls"
}
```

The agent sends a request to answer the call:

```
POST api/v2/me/calls/011DJV5JI898NB2L04000VTAES000005
{
  "operationName": "Answer"
}
```

The agent receives a notification that the call has been established:

```
{
  "data": {
    "notificationType": "StatusChange",
    "call": {
      "id": "011DJV5JI898NB2L04000VTAES000005",
      "state": "Established",
      "callUuid": "011DJV5JI898NB2L04000VTAES000005",
      "connId": "007102385535e005",
      "deviceUri": "http://127.0.0.1:8080/api/v2/devices/efelab32-53f9-43ce-
b65e-5768c61f7d4a",
      "participants": [
        {
          "e164Number": "",
          "formattedPhoneNumber": "5000",
          "phoneNumber": "5000",
          "digits": "5000"
        }
      ]
    }
  }
}
```

```
    },
    ],
    "dnis": "5005",
    "callType": "Internal",
    "capabilities": [
        "UpdateUserData",
        "SingleStepConference",
        "DeleteUserData",
        "Hangup",
        "SendDtmf",
        "Hold",
        "AttachUserData",
        "SingleStepTransfer",
        "InitiateConference",
        "DeleteUserDataPair",
        "InitiateTransfer"
    ],
    "duration": "10",
    "mute": "Off",
    "supervisorListeningIn": false,
    "monitoredUserMuted": false,
    "uri": "http://127.0.0.1:8080/api/v2/me/calls/011DJV5JI898NB2L04000VTAES000005",
    "path": "/calls/011DJV5JI898NB2L04000VTAES000005"
},
"phoneNumber": "5005",
"extensions": {
    "WrapUpTime": 0,
    "BusinessCall": 0
},
"messageType": "CallStateChangeMessage"
},
"channel": "/v2/me/calls"
}
```

The agent initiates the two-step transfer:

```
POST api/v2/me/calls/011DJV5JI898NB2L04000VTAES000005
{
  "operationName": "InitiateTransfer",
  "destination": {
    "phoneNumber": "5001"
  }
}
```

The agent receives notification that the first call has been held:

```
{
  "data": {
    "notificationType": "StatusChange",
    "call": {
      "id": "011DJV5JI898NB2L04000VTAES000005",
      "state": "Held",
      "callUuid": "011DJV5JI898NB2L04000VTAES000005",
      "connId": "007102385535e005",
      "deviceUri": "http://127.0.0.1:8080/api/v2/devices/efelab32-53f9-43ce-b65e-5768c61f7d4a",
      "participants": [
        {
          "e164Number": "",
          "formattedPhoneNumber": "5000",
          "phoneNumber": "5000",
          "digits": "5000"
        }
      ]
    }
  }
}
```

```
    },
    ],
    "dnis": "5005",
    "callType": "Internal",
    "capabilities": [
        "UpdateUserData",
        "SingleStepConference",
        "DeleteUserData",
        "Hangup",
        "Retrieve",
        "AttachUserData",
        "SingleStepTransfer",
        "InitiateConference",
        "DeleteUserDataPair",
        "InitiateTransfer"
    ],
    "duration": "36",
    "mute": "Off",
    "supervisorListeningIn": false,
    "monitoredUserMuted": false,
    "uri": "http://127.0.0.1:8080/api/v2/me/calls/011DJV5JI898NB2L04000VTAES000005",
    "path": "/calls/011DJV5JI898NB2L04000VTAES000005"
},
"phoneNumber": "5005",
"extensions": {
    "WrapUpTime": 0,
    "BusinessCall": 0
},
"messageType": "CallStateChangeMessage"
},
"channel": "/v2/me/calls"
}
```

and that the consult call is now dialing:

```
{
  "data": {
    "notificationType": "StatusChange",
    "call": {
      "id": "011DJV5JI898NB2L04000VTAES000006",
      "state": "Dialing",
      "callUuid": "011DJV5JI898NB2L04000VTAES000006",
      "connId": "007102385535e006",
      "deviceUri": "http://127.0.0.1:8080/api/v2/devices/efelab32-53f9-43ce-
b65e-5768c61f7d4a",
      "participants": [
        {
          "e164Number": "",
          "formattedPhoneNumber": "5001",
          "phoneNumber": "5001",
          "digits": "5001"
        }
      ],
      "dnis": "5001",
      "callType": "Consult",
      "capabilities": [
        "UpdateUserData",
        "DeleteUserData",
        "Hangup",
        "SwapCalls",
        "CompleteTransfer",
        "SendDtmf",
        "AttachUserData",

```

```

        "DeleteUserDataPair"
      ],
      "parentCallUri": "http://127.0.0.1:8080/api/v2/me/calls/011DJV5JI898NB2L04000VTAES0000005",
      "duration": "0",
      "mute": "Off",
      "supervisorListeningIn": false,
      "monitoredUserMuted": false,
      "uri": "http://127.0.0.1:8080/api/v2/me/calls/011DJV5JI898NB2L04000VTAES0000006",
      "path": "/calls/011DJV5JI898NB2L04000VTAES0000006"
    },
    "phoneNumber": "5005",
    "extensions": {
      "WrapUpTime": 0,
      "BusinessCall": 0
    },
    "messageType": "CallStateChangeMessage"
  },
  "channel": "/v2/me/calls"
}

```

To complete, the agent requests completion of the transfer:

```

POST api/v2/me/calls/011DJV5JI898NB2L04000VTAES0000006
{
  "operationName": "CompleteTransfer"
}

```

The agent then receives notification that original call has been released:

```

{
  "data": {
    "notificationType": "StatusChange",
    "call": {
      "id": "011DJV5JI898NB2L04000VTAES0000005",
      "state": "Released",
      "callUuid": "011DJV5JI898NB2L04000VTAES0000005",
      "connId": "007102385535e005",
      "deviceUri": "http://127.0.0.1:8080/api/v2/devices/efe1ab32-53f9-43ce-b65e-5768c61f7d4a",
      "participants": [
        {
          "e164Number": "",
          "formattedPhoneNumber": "5000",
          "phoneNumber": "5000",
          "digits": "5000"
        }
      ],
      "dnis": "5005",
      "callType": "Internal",
      "capabilities": [

      ],
      "duration": "48",
      "mute": "Off",
      "supervisorListeningIn": false,
      "monitoredUserMuted": false,
      "uri": "http://127.0.0.1:8080/api/v2/me/calls/011DJV5JI898NB2L04000VTAES0000005",
      "path": "/calls/011DJV5JI898NB2L04000VTAES0000005"
    },
    "phoneNumber": "5005",
    "extensions": {

```

```
        "WrapUpTime":0,
        "BusinessCall":0
    },
    "messageType":"CallStateChangeMessage"
},
"channel":"/v2/me/calls"
}
```

and the consult call has been released:

```
{
  "data":{
    "notificationType":"StatusChange",
    "call":{
      "id":"011DJV5JI898NB2L04000VTAES0000006",
      "state":"Released",
      "callUuid":"011DJV5JI898NB2L04000VTAES0000006",
      "connId":"007102385535e006",
      "deviceUri":"http://127.0.0.1:8080/api/v2/devices/efelab32-53f9-43ce-
b65e-5768c61f7d4a",
      "participants":[
        {
          "e164Number":"",
          "formattedPhoneNumber":"5001",
          "phoneNumber":"5001",
          "digits":"5001"
        }
      ],
      "dnis":"5001",
      "callType":"Consult",
      "capabilities":[
        ],
        "parentCallUri":"http://127.0.0.1:8080/api/v2/me/calls/
011DJV5JI898NB2L04000VTAES0000005",
        "duration":"12",
        "mute":"Off",
        "supervisorListeningIn":false,
        "monitoredUserMuted":false,
        "uri":"http://127.0.0.1:8080/api/v2/me/calls/011DJV5JI898NB2L04000VTAES0000006",
        "path":"/calls/011DJV5JI898NB2L04000VTAES0000006"
      ],
      "phoneNumber":"5005",
      "extensions":{
        "WrapUpTime":0,
        "BusinessCall":0
      },
      "messageType":"CallStateChangeMessage"
    },
    "channel":"/v2/me/calls"
  }
}
```