



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Interaction Concentrator Deployment Guide

Sample Script for Custom Attached Data

5/10/2025

Sample Script for Custom Attached Data

This page presents a sample SQL script to create a custom dispatcher stored procedure—**gudCustDISP1** or **gudCustDISP2**—and a custom attached data storage table in your Interaction Database (IDB) schema.

The sample script in this appendix is for Microsoft SQL Server (MSSQL). After you install the Interaction Concentrator (ICON) application, sample scripts for each supported RDBMS type—**SampleProc_db_type.sql**—are available in the scripts subfolder in the directory to which you installed the application.

Tip

Carefully verify the syntax and operation of your modified **gudCustDISP1** or **gudCustDISP2** stored procedure. Any types of errors or RDBMS violations that the custom dispatcher stored procedure produces can affect ICON processing of all other attached data for voice calls and multimedia interactions.

The following MSSQL sample script illustrates how you can create a custom attached data storage table (G_SAMPLE_CUST_ADATA) and modify the **gudCustDISP1** or **gudCustDISP2** stored procedure in the **CoreProcedures_db_type.sql** script. The modified stored procedure stores arguments in the G_SAMPLE_CUST_ADATA table.

```
Sample Custom Dispatcher
/*=====*/
/* Table: G_SAMPLE_CUST_ADATA */
/*=====*/
create table G_SAMPLE_CUST_ADATA (
    ID                numeric(16)          identity,
    CALLID            varchar(50)          not null,
    CALL_TS           int                  not null,
    SWITCH_ID         int                  not null,
    TENANT_ID         int                  not null,
    C_INT_1           int                  null,
    C_INT_2           int                  null,
    ...
    C_INT_34          int                  null,
    C_STR_1           varchar(10)          null,
    C_STR_2           varchar(10)          null,
    ...
    C_STR_34          varchar(10)          null,
    GSYS_DOMAIN       int                  null,
    GSYS_PARTITION    int                  null,
    GSYS_SYS_ID       int                  null,
    GSYS_SEQ          bigint               null,
    GSYS_USEQ         bigint               null,
    GSYS_TS           datetime             null,
    GSYS_TC           int                  null,
    GSYS_EXT_VCH1     varchar(255)         null,
    GSYS_EXT_VCH2     varchar(255)         null,
    GSYS_EXT_INT1     int                  null,
    GSYS_EXT_INT2     int                  null,
```

Sample Script for Custom Attached Data

```
constraint PK_G_SAMPLE_CUST_ADATA primary key (ID)
)
go

/*=====*/
/* Index: IDX_G_SAMPLE_CDATA_TS */
/*=====*/
create index IDX_G_SAMPLE_CDATA_TS on G_SAMPLE_CUST_ADATA (
CALL_TS ASC
)
go

-- ===== --
-- Name: -- gudCustDISP1 --
-- Group: User data related procedures
-- Brief: -- gudCustDISP DISPATCH --
-- ===== --
DROP PROCEDURE gudCustDISP1
go

CREATE PROCEDURE gudCustDISP1
    @GROUPID INTEGER,
    @CALLID VARCHAR(64),
    @P_CALL_TS INTEGER,
    @SWITCHID INTEGER,
    @TENANTID INTEGER,
    @TS_S INTEGER,
    @TS_MS INTEGER,
    @P_STR_1 VARCHAR(255),
    @P_STR_2 VARCHAR(255),
    ...
    @P_STR_17 VARCHAR(255),
    @P_INT_1 INTEGER,
    @P_INT_2 INTEGER,
    ...
    @P_INT_17 INTEGER,
    @P_STR_RES1 VARCHAR(255),
    @P_STR_RES2 VARCHAR(255),
    @P_STR_RES3 VARCHAR(64),
    @P_STR_RES4 VARCHAR(255),
    @P_INT_RES1 INTEGER,
    ...
    @P_INT_RES7 INTEGER,
    @DOMAIN INTEGER,
    @PARTITION INTEGER,
    @SYS_ID INTEGER,
    @SYS_SEQN NUMERIC(20,0),
    @SYS_TS DATETIME
AS
BEGIN
    -- Insert first portion in the long table --
    IF (@GROUPID = 1)
    BEGIN
        INSERT INTO G_SAMPLE_CUST_ADATA(
            CALLID,
            CALL_TS,
            SWITCH_ID,
            TENANT_ID,
            C_INT_1,
            C_INT_2,
            ...
            C_INT_17,
```

```
        C_STR_1,
        C_STR_2,
        ...
        C_STR_17,
        GSYS_DOMAIN,
        GSYS_PARTITION,
        GSYS_SYS_ID,
        GSYS_SEQ,
        GSYS_USEQ,
        GSYS_TS)
VALUES (
    @CALLID,
    @P_CALL_TS,
    @SWITCHID,
    @TENANTID,
    @P_INT_1,
    @P_INT_2,
    ...
    @P_INT_17,
    @P_STR_1,
    @P_STR_2,
    ...
    @P_STR_17,
    @DOMAIN,
    @PARTITION,
    @SYS_ID,
    @SYS_SEQN,
    0,
    @SYS_TS)

END

-- Update record and specify more fields --
ELSE
IF (@GROUPID = 2)
BEGIN
    UPDATE G_SAMPLE_CUST_ADATA SET
        C_INT_18                = @P_INT_1,
        ...
        C_INT_34                = @P_INT_17,
        C_STR_18                = @P_STR_1,
        C_STR_19                = @P_STR_2,
        ...
        C_STR_34                = @P_STR_17,
        GSYS_USEQ              = @SYS_SEQN
    WHERE CALLID = @CALLID AND CALL_TS = @P_CALL_TS

END
END
go
```