



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

# Interaction Concentrator Physical Data Model for a Microsoft SQL Database

Table GO\_CampProp\_Hist

## Table GO\_CampProp\_Hist

This table contains the history of Campaign property changes during the campaign processing attempt. Records are inserted into this table when ICON receives information about campaign property changes from OCS. Records in this table are never updated or deleted.

### Tip

To assist you in preparing supplementary documentation, click the following link to download a comma-separated text file containing information such as the data types and descriptions for all columns in this table: [Download a CSV file](#).

**Hint:** For easiest viewing, open the downloaded CSV file in Excel and adjust settings for column widths, text wrapping, and so on as desired. Depending on your browser and other system settings, you might need to save the file to your desktop first.

## Column List

### Legend

Column	Data Type	P	M	F	Description
ID	numeric(16)	X	X		The unique, autonumbered ID of this record. This is the primary key.
SessID	varchar(64)		X	X	The campaign processing session ID (GUID).
Seq	int		X		The sequence number of state and property changes in a campaign's history.
DialMode	int				The dial mode specified for campaign processing.

Table GO\_CampProp\_Hist

Column	Data Type	P	M	F	Description
PrevDialMode	int				The previous dialing mode, if the dialing mode was changed.
PrevDMEnter	datetime				The GMT-equivalent date and time when previous dialing mode was detected by OCS (according to timestamp provided by OCS).
PrevDMEnter_ts	int				The UTC-equivalent value of the PREVDMENTER field. Milliseconds are truncated.
PrevDMEnter_tcode	int				A reference, derived from the value of the PREVDMENTER_TS field, to a record in the G_TIMECODE table.
OptimMode	int				Code of optimization mode (overdialrate, waiting time, busy factor).
OptimValue	int				The current value of the optimization parameter that OCS uses for this campaign.
PrevOptimMode	int				The previous optimization mode that OCS ran with this campaign.
PrevOptimValue	int				The previous optimization parameter

Table GO\_CampProp\_Hist

Column	Data Type	P	M	F	Description
					value that OCS used for this campaign.
PrevOMEnter	datetime				The GMT-equivalent date and time when the previous optimization mode was reported by OCS.
PrevOMEnter_ts	int				The UTC-equivalent value of the PREVOMENTER field. Milliseconds are truncated.
PrevOMEnter_tcode	int				A reference, derived from the value of the PREVOMENTER_TS field, to a record in the G_TIMECODE table.
GeneralN	int				The numerical value of the priority parameter that OCS used for general records in this campaign.
PrevGeneralN	int				The previous value of the priority parameter that OCS used for General records in this campaign.
GeneralW	int				The current weight of the priority parameter value for general records that OCS used for this campaign.

Table GO\_CampProp\_Hist

Column	Data Type	P	M	F	Description
PrevGeneralW	int				The previous weight of the priority parameter value for general records that OCS used in this campaign.
CallBackN	int				The numerical value of the priority parameter that OCS used for callback records in this campaign.
PrevCallBackN	int				The previous value of the priority parameter that OCS used for callback records in this campaign.
CallBackW	int				The current weight of the priority parameter value for callback records that OCS used within this campaign.
PrevCallBackW	int				The previous weight of the priority parameter value for callback records that OCS used in this campaign.
SchedN	int				The current numerical value of the priority parameter that OCS used for scheduled records in this campaign.

Table GO\_CampProp\_Hist

Column	Data Type	P	M	F	Description
PrevSchedN	int				The previous value of the priority parameter that OCS used for scheduled records in this campaign.
SchedW	int				The current weight of the priority parameter value for scheduled records that OCS used in this campaign.
PrevSchedW	int				The previous weight of the priority parameter value for scheduled records that OCS used within this campaign.
PrevPPEnter	datetime				The GMT-equivalent date and time when the previous priority parameters were reported by OCS.
PrevPPEnter_ts	int				The UTC-equivalent value of the PREVPENTER field. Milliseconds are truncated.
PrevPPEnter_tcodent					A reference, derived from the value of the PREVPENTER_TS field, to a record in the G_TIMECODE table.
Added	datetime		X		The GMT-

Table GO\_CampProp\_Hist

Column	Data Type	P	M	F	Description
					equivalent date and time when any change of a parameter is reported by OCS.
Added_ts	int				The UTC-equivalent value of the ADDED field. Milliseconds are truncated.
Added_tcode	int				A reference, derived from the value of the ADDED_TS field, to a record in the G_TIMECODE table.
GSYS_DOMAIN	int				Contains the data source session ID (DSS_ID) for the session that was active when the data was processed by ICON. For more information, see the description in System Fields (for <a href="#">DB2</a> , <a href="#">Microsoft SQL Server</a> , <a href="#">Oracle</a> , or <a href="#">PostgreSQL</a> , respectively).
GSYS_PARTITION	int				Key used for partitioning.
GSYS_SYS_ID	int				System ID. Reserved for future use.
GSYS_SEQ	bigint				Insert Sequence. Not unique.
GSYS_USEQ	bigint				Update Sequence. Not unique.

Table GO\_CampProp\_Hist

---

Column	Data Type	P	M	F	Description
GSYS_TS	datetime				Reserved
GSYS_TC	int				Reserved
GSYS_EXT_VCH1	varchar(255)				Reserved
GSYS_EXT_VCH2	varchar(255)				Reserved
GSYS_EXT_INT1	int				Reserved
GSYS_EXT_INT2	int				Reserved

---