



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

# Interaction Concentrator Physical Data Model for a Microsoft SQL Database

Table G\_CALL

## Table G\_CALL

This table contains information regarding the latest state of the interaction, according to information received from either the T-Server or Interaction Server applications.

### Tip

To assist you in preparing supplementary documentation, click the following link to download a comma-separated text file containing information such as the data types and descriptions for all columns in this table: [Download a CSV file](#).

**Hint:** For easiest viewing, open the downloaded CSV file in Excel and adjust settings for column widths, text wrapping, and so on as desired. Depending on your browser and other system settings, you might need to save the file to your desktop first.

## Column List

### Legend

Column	Data Type	P	M	F	Description
ID	numeric(16)	X	X		The unique, autonumbered ID of this record. This is the primary key.
CallID	varchar(50)		X		The unique ID of the interaction. The lxnGUID.
ParentCallID	varchar(50)			X	The ID of the parent interaction. This is primary call UUID for consultation call interactions.
MergeCallID	varchar(50)		X		The actual call UUID of a target call, in a conference or a

Table G\_CALL

Column	Data Type	P	M	F	Description
					transfer interaction. This value may differ from that in the ParentCallID field. This value will be unspecified for multimedia interactions.
MergeType	int				The type of the link between this interaction and the parent interaction. This value will be unspecified for multimedia interactions. Refer to <a href="#">G_Dictionary Values</a> for a listing of permissible values.  #DICTIONARY TYPE 86
ConnID	varchar(50)				The current connection ID. This value will be unspecified for multimedia interactions.
ConnIDnum	numeric(20)				The numeric representation of the connection ID. This value will be unspecified for multimedia interactions.
SwitchCallID	int				The switch-specific call ID. This value will be unspecified for multimedia interactions.
IRID	varchar(50)			X	The reference to the entry in the interaction

Table G\_CALL

Column	Data Type	P	M	F	Description
					segments hierarchy (G_IR table).
RootIRID	varchar(50)				A reference to the first interaction segment in the interaction hierarchy (G_IR table).
State	int				<p>The call state. One of the following values:</p> <ul style="list-style-type: none"> <li>• 0—unknown—Reserved.</li> <li>• 1—active—The interaction is active.</li> <li>• 2—terminated—The interaction has been terminated.</li> </ul> <p>#DICTIONARY TYPE 4</p>
CallType	int				<p>The interaction's type. One of the following values:</p> <ul style="list-style-type: none"> <li>• 0—unknown—Reserved for cases when ICON is unable to determine the interaction's type.</li> <li>• 1—internal</li> <li>• 2—inbound</li> <li>• 3—outbound</li> <li>• 4—consult</li> </ul> <p>#DICTIONARY TYPE 5</p>
MediaType	int				The media type

Table G\_CALL

Column	Data Type	P	M	F	Description
					<p>of this interaction. One of the following values:</p> <ul style="list-style-type: none"> <li>• 0—Unknown. Reserved for when ICON is unable to determine media type.</li> <li>• 1—Voice.</li> <li>• 2—Email.</li> <li>• 3—Chat.</li> <li>• 1000—Open Media.</li> </ul> <p>#DICTIONARY TYPE 6</p>
SwitchID	int				The DBID of the Switch. This value will be unspecified for interactions originating from Interaction Server.
TenantID	int				The DBID of the Tenant.
CallANI	varchar(50)				The Automatic Number Identification, as reported by the T-Server.
CallDNIS	varchar(50)				The directory number to which the call was made, the DNIS, as reported by the T-Server. This value will be empty for multimedia interactions.
Created	datetime		X		The GMT-

Table G\_CALL

Column	Data Type	P	M	F	Description
					equivalent date and time when the interaction was initiated, as reported by T-Server or Interaction Server.
Created_ts	int				The UTC-equivalent value of the CREATED field.
Created_tcode	int				A reference, derived from the value of the CREATED_TS field, to a record in the G_TIMECODE table.
Terminated	datetime				The GMT-equivalent date and time when the interaction was terminated.
Terminated_ts	int				The UTC-equivalent value of the TERMINATED field.
Terminated_tcode	int				A reference, derived from the value of the TERMINATED_TS field, to a record in the G_TIMECODE table.
GSYS_DOMAIN	int				Contains the data source session ID (DSS_ID) for the session that was active when the data was processed by ICON. For more information,

Table G\_CALL

Column	Data Type	P	M	F	Description
					see the description in <a href="#">System Fields</a> .
GSYS_PARTITION	int				A key that is used for partitioning.
GSYS_SYS_ID	int				System ID. Reserved for future use.
GSYS_SEQ	bigint				Insert Sequence. Not unique.
GSYS_USEQ	bigint				Update Sequence. Not unique.
GSYS_TS	datetime				Reserved
GSYS_TC	int				Reserved
GSYS_EXT_VCH1	varchar(255)				<p>A string value with the name of the media type for a 3rd Party Media interaction, as reported by Interaction Server.</p> <p>When the field GSYS_EXT_INT1 indicates that this is a 3rd Party Media interaction (1000—Open Media), the stored string is the name of the media type. For example, "fax".</p>
GSYS_EXT_VCH2	varchar(255)				Reserved
GSYS_EXT_INT1	int				Reserved
GSYS_EXT_INT2	int				<p>A flag indicating stuck calls:</p> <ul style="list-style-type: none"> <li>• 0—Indicates that the interaction should not be marked as stuck.</li> </ul> <p>ICON</p>

Table G\_CALL

---

Column	Data Type	P	M	F	Description
					<p>records this value upon start of call termination to prevent marking calls as stuck and to complete the processing of the interaction following the recording of related user data in IDB.</p> <ul style="list-style-type: none"><li>• 1—Indicates an interaction that has been determined as stuck.</li><li>• NULL—The value before the processing of call termination begins.</li></ul>