



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Interaction Concentrator Physical Data Model for a Microsoft SQL Database

Table G_CALL_USERDATA

Table G_CALL_USERDATA

This table stores the principal information regarding user data that is attached to voice call interactions.

Tip

To assist you in preparing supplementary documentation, click the following link to download a comma-separated text file containing information such as the data types and descriptions for all columns in this table: [Download a CSV file](#).

Hint: For easiest viewing, open the downloaded CSV file in Excel and adjust settings for column widths, text wrapping, and so on as desired. Depending on your browser and other system settings, you might need to save the file to your desktop first.

Column List

Legend

Column	Data Type	P	M	F	Description
ID	numeric(16)	X	X		The unique, autonumbered ID of this record. This is the primary key.
CALLID	varchar(50)		X		The unique ID of the call interaction.
G_CUSTOMER_SEGMENT	varchar(255)				The value of the customer-segment attribute of userdata.
G_SERVICE_TYPE	varchar(255)				The value of the service-type attribute of userdata.
G_SERVICE_SUBTYPE	varchar(255)				The value of the service-subtype attribute of

Table G_CALL_USERDATA

Column	Data Type	P	M	F	Description
					userdata.
G_BUSINESS_RESULT	varchar(255)				The value of the business-result attribute of userdata.
CUSTOMER_ID	varchar(255)				The value of the customer-id attribute of userdata.
TRANSACTION_ID	varchar(255)				The value of the transaction-id attribute of userdata.
CAUSE_ID	varchar(255)				The value of the cause-id attribute of userdata.
ACCOUNT_ID	varchar(255)				The value of the account-id attribute of userdata.
DESTINATION_ID	varchar(255)				The value of the destination-id attribute of userdata.
TARGET_ID	varchar(255)				The value of the target-id attribute of userdata.
GSYS_DOMAIN	int				Contains the data source session ID (DSS_ID) for the session that was active when the data was processed by ICON. For more information, see the description in System Fields (for DB2 , Microsoft SQL Server , Oracle , or PostgreSQL , respectively).

Table G_CALL_USERDATA

Column	Data Type	P	M	F	Description
GSYS_PARTITION	int				A key that is used for partitioning.
GSYS_SYS_ID	int				System ID. Reserved for future use.
GSYS_SEQ	bigint				Insert Sequence. Not unique.
GSYS_USEQ	bigint				Update Sequence. Not unique.
GSYS_TS	datetime				Reserved
GSYS_TC	int				Reserved
GSYS_EXT_VCH1	varchar(255)				Reserved
GSYS_EXT_VCH2	varchar(255)				Reserved
GSYS_EXT_INT1	int				Reserved
GSYS_EXT_INT2	int				Reserved
