



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

iWD Deployment Guide

IWD Manager Configuration

12/17/2025

IWD Manager Configuration

Logging in

Logging in

User Login

Anyone who needs access to iWD Manager must be configured as a Person or in Genesys Administrator (GA) or Genesys Administrator Extension (GAX)

The login screen prompts for the following information:

- Username—The username for the Person or User as configured in GA/GAX.
- Password—The password for the Person or User as configured in GA/GAX.
- CME Application—The name of the iWD Manager Application object as configured in GA/GAX.

Programmatic Login

You can log into iWD Manager programmatically by providing the URL for iWD Manager login page along with a valid username and password. This can facilitate a single sign-on process.

The URL format to use is:

```
http://<appserverhost>:<appserverport>/<iwdmanagerapplication>/ui/  
login.jsf?username=<username>  
&password=<password>&application=<CMEApplication>&passwordEncoded
```

Where:

- <appserverhost> and <appserverport> are the host and port for the application server where iWD Manager is deployed.
- <iwdmanagerapplication> is the iWD Manager application running on the application server (for example, iwd_manager).
- <username> and <password> are a valid username and password combination for the user logging into iWD Manager.
- <CMEApplication> is the name of the iWD Manager application as configured in the Genesys Configuration database. You can find the name in GA or GAX. iWD Manager will be shown with an

application type of iWD Manager.

Important

If you want to include the `&passwordEncoded` at the end of the URL, then the value for `<password>` should be encoded using the BASE64 algorithm. Otherwise, you can pass a plain-text password in the `<password>` parameter and omit `&passwordEncoded`.

An example URL is:

```
<http://myTomcatHost:8080/iwd_manager/ui/  
login.jsf?username=jsmith&password=myPassword&CMEApplication=iWDManager
```

General Conditions for Configuring an iWD Manager User

General Conditions for Configuring an iWD Manager User

To access the Global Task List, the Person must be associated with a Place in Genesys Configuration. If the Person is not an Agent, the Place can be configured as an option on the Annex tab of the Person/User object. Create a section iWD (if it does not already exist) and within the iWD section, create an option iWDManagerPlace with the value of a valid Place name.

If you want a user to have access to a specific managed tenant in iWD, that user must have at least Read access to the Configuration Server tenant that is linked to that iWD managed tenant—either directly or by being a member of an Access Group that does. The user must have at least Read & Execute permissions to the iWD Manager application in Configuration Server, and Read permissions to the Configuration Server Host object where the Interaction Server is running, either directly or by being a member of an Access Group that does.

If the user is going to have access to the Global Task List, then the user must have at least Read and Execute permissions to these application objects in Configuration Server:

- Interaction Server
- The Database Access Point for the Interaction Server database
- The Database Access Point for the Interaction Server Event Log database.

These permissions may be applied directly to the user, or by the user being a member of an Access Group that has such permissions.

The Place that must be associated with the user must be a Place configured under the Configuration Server tenant that maps to the iWD managed tenant. (This presumes that the Interaction Server application also has an association with this Configuration Server tenant.) The Place is only used to give the user access to the Global Task List.

If you want to restrict what the user can do in iWD Manager, use roles and privileges as

described in Role-Based Access Control.

If the user is created under a Configuration Server child tenant, then the following additional conditions must be met:

- If you want the user to have access to both the iWD SYSTEM tenant as well as the iWD managed tenant to which the Configuration Server tenant maps, then this user must be either be a member of at least two Access Groups with the relevant permissions, or must have permissions granted directly to them.

Such Access Groups must have at least Read permission to the tenants.

If the user has no role privilege in a Tenant, then the Tenant is hidden from that user.

If the user is created under the Environment tenant—for example, such as the default user that is in the Configuration Server database when it is initially deployed, then in order for this user to have full control of the Global Task List (not just read-only access), two conditions must be met:

- The user must have a valid Place configured, where the Place is created under a child Configuration Server tenant to which the Interaction Server is associated.
- The user must have an Employee ID that also belongs to a user who is created under a child Configuration Server tenant to which the Interaction Server is associated.
- The user must have all role privileges from all the "iWD*" groups.

Importing Media Icons

Importing Media Icons

The **Media Icons** view provides a way to map graphical icons to media types to display in the GTL. iWD comes with some pre-loaded icons, but additional icons can be uploaded and mapped to existing media types, or new media types. Icons must be 16x16, but can be in any of the following file formats:

- GIF
- JPG
- BMP
- PNG

The following properties and actions are available in the **Media Icons** panel:

Icon	Description
Media Type	The media type to which the icon will be mapped. This list of media types is retrieved dynamically from Genesys Configuration Server. Media types are a type of Business Attribute in Configuration Server. Genesys provides out-of-the-box media

Icon	Description
	types but new custom media types can be added.
Icon	The graphical 16x16 icon that will be displayed in the GTL when a task is of the media type to which the icon is mapped.
File Name	The file name of the icon.
New Icon Mapping	Provides a way for you to upload a new icon from the file system.
Browse	Opens a File Upload dialog window to enable you to browse the file system to select an icon.
Upload	Uploads the icon selected via the Browse action.
Save/Save and Close/Cancel	Standard iWD Manager functions.

Changes in 8.5.0

Only Media Icons are imported/exported into/out of iWD Manager in release 8.5.0.

Prerequisites

- iWD Manager, iWD Runtime Node are installed.
- Application servers are started (if running on WebSphere – applications are started).

Procedure

1. Log in to iWD Manager.
2. Open Import/Export in the General section of the System tenant.
3. Import the following files:
 - <iWD Manager installation directory>\config\iwd_mediaicons.xml.

Important

The XML file is saved to the installation directory where the iWD Manager supporting files were installed.

- After each import a message appears at the bottom of the screen to indicate whether the import was

successful.

Filters

Filters

Filters allow you to refine the list of tasks that are displayed in the GTL. Each filter is defined by a set of filter criteria (optional) and table columns that will be displayed in the GTL.

Preconfigured Filters

The table below lists the attributes and actions that are available in the **Filters** view.

Filter Attributes

Attribute/Action	Description
Name	The name of the filter.
Public	Whether the filter will be available to all users (checked) or only the current user (unchecked).
Filter Criteria	Tasks that do not match the defined criteria will be excluded from the GTL when the filter is selected. New criteria conditions can be added by selecting them from the Select criteria to add drop-down list. Some criteria conditions are parameterized; for such conditions, parameters can be configured directly in a criteria table (such as, status for Status is ... criteria). Custom attributes can be used in many of the filter criteria, with proper configuration. Custom Attributes for tasks are configured in the iWD GAX Plugin component. See the Task Attributes tab of the Data Mart section of iWD GAX Plugin Help.
Table Columns	The GTL will display these columns when the filter is selected. Columns can be added, removed, and reordered. A user can select from a list that includes all iWD core and extended attributes, by default. With proper configuration, custom attributes can also be selected.

Attribute/Action	Description
Save, Save & Close, Cancel, Delete	Standard iWD Manager functions.

Creating Custom Filters

Creating a Custom Filter

1. Click **Filter > New** in the left navigation pane.
2. Check the **Public** checkbox to make the new filter available to all users. If this box is not checked, only the current user can view the new filter.
3. From the **Select criteria to add** drop-down menu at the bottom left, select filter criteria for the new filter. Use the red delete button displayed to the right of the selected criterion to delete it if required.
4. From the **Select column to add** drop-down menu at the bottom center, add any new table columns for displaying the filter output. The current selection of table columns appears to the right of the screen. Use the up/down arrows to sort the display of the table columns. Use the red delete button to delete any columns as required.
5. Click **Save** or **Save and Close**. The newly created filter is now available for selection in the main Global Task List window.