

GENESYS

This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

iWD REST API Reference Guide

Get common task attributes for modification

Contents

- 1 Get common task attributes for modification
 - 1.1 Method
 - 1.2 Syntax
 - 1.3 Request Body
 - 1.4 Response Body

Get common task attributes for modification

Method

POST

Syntax

```
POST /gtl/tasks/common_data/<solution_dbid>?entity_dbid=<dbid>&entity_type=<department/process/capturePoint/ solution>&filter=<filter_name>o_by=<qualified_attribute_name>o_direction=<ascending/descending>&snapshot_id=<snapshot_id>
```

Request Body

Up to 9.0.012

Or:

```
{
    "content": {
        "exclude": [ <task_idl>, <task_id2>, ...]
    },
    "qlExpression": [<ql_item>, <ql_item>, ...]
}
```

Notes

- It is not allowed to send both "include" and "exclude" lists.
- snapshot id is mandatory.
- The value for the qlExpression field is the same object as the request body from Fetch paginated list of tasks.

Response Body

```
"attribute_definitions":
       "name": "<attribute name>",
       "label": "<localized attribute label>",
"type": "<string/date/int/img/list>",
       "values":
          "value": "<name of value>",
"label": "<display name>"
         },
     ],
"category": "core/ext/data",
  "attribute values":
  {
     "core":
         <attribute definitions>
     "ext":
          <attribute definitions>
    },
"data":
          <attribute definitions>
}
```

- "attribute_definitions" contains only editable attributes.
- "attribute_values" contains only attributes that have the same value for all the selected tasks.