

GENESYS

This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

iWD REST API Reference Guide

Export selected tasks

Contents

- 1 Export selected tasks
 - 1.1 Method
 - 1.2 Syntax
 - 1.3 Headers
 - 1.4 Request Body: up to 9.0.012
 - 1.5 Request Body: from 9.0.013

Export selected tasks

Method

Up to 9.0.012

GET

From 9.0.013

POST

Important

The new request has exactly the same parameters as the old one and allows you to pass the ql_expression in the request body in JSON format.

Syntax

```
Up to 9.0.012
```

GET /gtl/tasks/{solutionDbid}/{page}

From 9.0.013

POST /gtl/tasks/{solutionDbid}/{page}/search

Headers

```
Accept: application/xml,*/*
```

Request Body: up to 9.0.012

```
"include": [ <task_idl>, <task_id2>, ...]
```

```
}
Or:
{
    "exclude": [ <task_id1>, <task_id2>, ...]
}
```

Request Body: from 9.0.013

```
{
    "content": {
        "include": [ <task_idl>, <task_id2>, ...]
},
    "qlExpression": [<ql_item>, <ql_item>, ...]
}
Or:
{
    "content": {
        "exclude": [ <task_idl>, <task_id2>, ...]
},
    "qlExpression": [<ql_item>, <ql_item>, ...]
}
```

- It is not allowed to send both "include" and "exclude" lists.
- snapshot id is mandatory.
- The returned format is XML.
- It is necessary to set the **Accept** header with application/xml as the first value. The following "*/*" is needed to correctly return an error message in JSON.
- The value for the qlExpression field is the same object as request body from Fetch paginated list of tasks.