



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

iWD REST API Reference Guide

[Fetch list of media icons](#)

Contents

- 1 Fetch list of media icons
 - 1.1 Method
 - 1.2 Syntax
 - 1.3 Parameters
 - 1.4 Response Body
 - 1.5 Notes

Fetch list of media icons

Method

GET

Syntax

GET /icons/<tenant_dbid>?invalidateCache=<true/false>

Parameters

Parameter Name	Description	Default Value
invalidateCache	Optional. Can be either true or false. With value true, the iWD Manager backend does not use the inner cache and must reload icons from Configuration Server. Value false means that iWD Manager can use the inner cache for better performance. If the parameter is not present, the inner cache is used (same as for invalidateCache=false).	false

Response Body

```
[
  {
    "media_type": "<media_type>",
    "media_icon": {
      "content_type": "<content_type>",
      "name": "<icon_file_name>",
      "encoding": "base64",
      "data": "<icon_data_encoded_with_encoding_method>"
    }
  },
  ...
]
```

Notes

- There may be icons with `media_type` that is missing in the media types list. They should be returned as well.
- Currently only "base64" is a valid value of "encoding".