



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Integrated Capture Points Guide

Configure unixODBC for DB2 on Solaris

5/12/2025

Configure unixODBC for DB2 on Solaris

1. In **\$DRIVER/clidriver/cfg**:

- a. Rename **db2cli.ini.sample** to **db2cli.ini**
- b. Rename **db2dsdriver.cfg.sample** to **db2dsdriver.cfg**
- c. Modify the **<dsncollection>** element of **db2dsdriver.cfg** by inserting

```
<dsn alias="DB2_ALIAS" name="DB2_NAME" host="db2host.<your company>.com"
port="5000"?><parameter name="Authentication" value="Client"/></dsn>
```

- d. Modify the **<databases>** element of **db2dsdriver.cfg** by inserting

```
<database name="DB2_NAME" host="db2host.<your company>.com" port="5000"?>
<parameter name="CurrentSchema" value="DB2I"/>
<wlb> <parameter name="enableWLB" value="true"/><parameter name="maxTransports"
value="50"/></wlb>
<acr> <parameter name="enableACR" value="true"/> </acr>
</database>
```

5. Modify **\$HOMEDIR/.odbc.ini** by adding the following:

```
[DB2_ALIAS]
Description=my DB2
Driver=DB2_DRIVER
```

6. Modify **\$UNIXODBC/etc/odbcinst.ini** by adding the following:

```
[DB2_DRIVER] Description=DB2 ODBC Driver Driver=$DRIVER/clidriver/lib/libdb2o.so
Fileusage=1 DontDLClose=1
```

7. Set variables:

```
export LD_LIBRARY_PATH=$DRIVER/clidriver/lib/:$UNIXODBC/lib/
```

8. Test the DSN connection:

```
./isql -v DB2_ALIAS username password
```