



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

Integrated Capture Points Guide

Generate Service Proxy with `wsimport`

12/18/2025

Generate Service Proxy with wsimport

Start

To generate a Web Service Capture Point service proxy for Java, use the `wsimport` utility, which is included in JDK:

```
wsimport -d <output directory> <WSDL URL>
```

For example:

```
wsimport -d c:\Temp\MyJSCClient  
http://zoolander.us.int.genesyslab.com:10080/Genesys/Interaction/WSCP_812_zoo/  
WebServiceCapturePoint?wsdl
```

The tool generates a set of files for the proxy.

Create a simple Java console application to ping the service:

```
import java.net.URL;  
import javax.xml.namespace.QName;  
import javax.xml.ws.Holder;  
import com.genesyslab.interaction.*;  
public class Test {  
  
    public static void main(String[] args) throws Exception {  
  
        WebServiceCapturePoint service = new WebServiceCapturePoint(new  
        URL("http://zoolander.us.int.genesyslab.com:10080/Genesys/Interaction/WSCP_812_zoo/  
        WebServiceCapturePoint/?WSDL"), new  
        QName("http://www.genesyslab.com/interaction", "WebServiceCapturePoint"));  
        IWebServiceCapturePoint cp = service.getIWebServiceCapturePointHttpBinding();  
  
        KeyValuePair val = new KeyValuePair();  
  
        val.setValueString("I am coming from JAXWS client");  
  
        KeyValuePair pair = new KeyValuePair();  
  
        pair.setKey("Source");  
        pair.setValue(val);  
  
        KVList extList = new KVList();  
  
        extList.getKvitem().add(pair);  
  
        Holder<KVList> extension = new Holder<KVList>(extList);  
  
        Holder<String> eventTime = new Holder<String>();  
        Holder<KVList> userData = new Holder<KVList>();  
        Holder<KVList> pingInfo = new Holder<KVList>();  
  
        cp.ping(extension, eventTime, userData, pingInfo);  
  
        System.out.println("Ping response time:" + eventTime.value);  
        printKVList("PingInfo", pingInfo.value);  
        printKVList("UserData", userData.value);  
    }  
}
```

```
    printKVList("Extension", extension.value);
}

public static void printKVList(String name, KVList kvList) {
    printKVList(name, kvList, "");
}

private static void printKVList(String name, KVList kvList, String shift) {
    if (null == kvList) {
        System.out.println(shift + name + "[KVList]=null");
    } else {
        System.out.println(shift + name + "[KVList]=");

        for (KeyValuePair pair : kvList.getKvitem()) {
            KeyValuePair value = pair.getValue();

            if (value.getValueInt() != null) {
                System.out.println(shift + "\t" + pair.getKey() + "[int]="
                    + value.getValueInt());
            } else if (null != value.getValueList()) {
                printKVList(pair.getKey(), value.getValueList(), shift
                    + "\t");
            } else {
                System.out.println(shift + "\t" + pair.getKey()
                    + "[string]=" + value.getValueString());
            }
        }
    }
}
}
```

End