



This PDF is generated from authoritative online content, and is provided for convenience only. This PDF cannot be used for legal purposes. For authoritative understanding of what is and is not supported, always use the online content. To copy code samples, always use the online content.

# Interaction Server Log Events Supplement

Interaction Server Proxy

12/17/2025

---

## Contents

- 1 Interaction Server Proxy
  - 1.1 Release 8.5.110
  - 1.2 Release 8.5.108
  - 1.3 Release 8.5.107

# Interaction Server Proxy

This page lists changes to Interaction Server Proxy log events after release 8.1.400.06. Log events for releases 8.1.400.06 and earlier are described in [Combined Log Events Help](#).

In the Text field, expressions %s and %d represent text (%s) or numeric (%d) values that are filled in according to the actual context that generates the message. The Attributes field identifies them with parenthesized numbers that correspond to the order they occur in the text. For example, for 01-30130 immediately below, (1) is the first %s and (2) is the second %s.

## Important

Prior to the 8.5.108.19 release, Interaction Server Proxy supported two application types in the Configuration Server database: T-Server and Interaction Server. When launched in Interaction Server mode, the log events all have the prefix **111-**, as shown here. When launched in T-Server mode, the event has the prefix **01-**, but the five digits after the hyphen are the same as those listed here

## Release 8.5.110

### New

#### 111-30130

<b>Level</b>	TRACE
<b>Text</b>	Ignoring message '%s' on connection '%s', received before proxy registered on that connection.
<b>Attributes</b>	(1) message name (2) Interaction Server's name
<b>Description</b>	Proxy ignored message received before registering on the node.
<b>Actions</b>	None
<b>Alarm Advisory</b>	None

#### 111-30131

<b>Level</b>	TRACE
<b>Text</b>	Distributing message '%s' (%d), message attributes:%s%s
<b>Attributes</b>	(1) message name

---

	(2) message id (3) new line (4) message attributes
<b>Description</b>	Content of reporting event that will be distributed to reporting clients.
<b>Actions</b>	None
<b>Alarm Advisory</b>	None

**111-30132**

<b>Level</b>	TRACE
<b>Text</b>	...distributing message '%s' (%d) to client '%s' - %s:%d:%d
<b>Attributes</b>	(1) message name  (2) message id (3) client name (4) client type name (5) client id (6) connection id
<b>Description</b>	Information about client to which message is being distributed.
<b>Actions</b>	None
<b>Alarm Advisory</b>	None

**111-30133**

<b>Level</b>	TRACE
<b>Text</b>	Sending message '%s' (%d) to multiple servers, message attributes:%s%s
<b>Attributes</b>	(1) message name  (2) message id (3) new line (4) message attributes
<b>Description</b>	Content of request that will be sent to multiple Interaction Servers.
<b>Actions</b>	None
<b>Alarm Advisory</b>	None

**111-30134**

<b>Level</b>	TRACE
<b>Text</b>	...sending message '%s' (%d) to server '%s' (%d) using proxy client id '%d'
<b>Attributes</b>	(1) message name

---

	(2) message id (3) Interaction Server's name (4) connection id (5) client id
<b>Description</b>	Information about target Interaction Server to which request is being distributed.
<b>Actions</b>	None
<b>Alarm Advisory</b>	None

**111-30135**

<b>Level</b>	TRACE
<b>Text</b>	...sending message '%s' (%d) to server '%s' (%d) using proxy client id '%d' and snapshot id '%d'
<b>Attributes</b>	(1) message name (2) message id (3) Interaction Server's name (4) connection id (5) client id (6) snapshot id
<b>Description</b>	Information about target Interaction Server to which snapshot-related request is being distributed.
<b>Actions</b>	None
<b>Alarm Advisory</b>	None

**111-30136**

<b>Level</b>	DEBUG
<b>Text</b>	Message '%s' (%d) will be sent to server '%s' based on '%s' rule
<b>Attributes</b>	(1) message name (2) message id (3) Interaction Server's name (4) rule name
<b>Description</b>	Debug information about reason why proxy is sending message to given server (name of the rule).
<b>Actions</b>	None
<b>Alarm Advisory</b>	None

**111-30137**

<b>Level</b>	DEBUG
<b>Text</b>	Message '%s' (%d) will be sent to servers %s based on '%s' rule

---

<b>Attributes</b>	(1) message name (2) message id (3) list of target Interaction Servers (4) rule name
<b>Description</b>	Debug information about reason why proxy is sending message to listed servers (name of the rule).
<b>Actions</b>	None
<b>Alarm Advisory</b>	None

**111-30138**

<b>Level</b>	DEBUG
<b>Text</b>	Desired Agent's State of place '%s' at tenant '%d':%s%s
<b>Attributes</b>	(1) place name (2) tenant DBID (3) new line (4) content
<b>Description</b>	Information about desired agent's state after processing state-related request.
<b>Actions</b>	None
<b>Alarm Advisory</b>	None

**111-30139**

<b>Level</b>	DEBUG
<b>Text</b>	Composite Agent's State of place '%s' at tenant '%d':%s%s
<b>Attributes</b>	(1) place name (2) tenant DBID (3) new line (4) content
<b>Description</b>	Information about composite agent's state after processing state-related reporting event.
<b>Actions</b>	None
<b>Alarm Advisory</b>	None

**111-30140**

<b>Level</b>	TRACE
<b>Text</b>	Proxy health information:%s%s
<b>Attributes</b>	(1) new line (2) health information

---

---

<b>Description</b>	Provides proxy health information and basic KPIs.
<b>Actions</b>	None
<b>Alarm Advisory</b>	None

**111-30141**

<b>Level</b>	DEBUG
<b>Text</b>	Proxy connection state:%s%s
<b>Attributes</b>	(1) new line (2) connection state of all nodes
<b>Description</b>	After change to proxy's connections (connected/disconnected/new connection added), proxy provides information about state of all currently connected nodes.
<b>Actions</b>	None
<b>Alarm Advisory</b>	None

## Release 8.5.108

## Added

**111-30126**

<b>Level</b>	STANDARD
<b>Text</b>	T-Server mode is not supported. Parameter ignored!
<b>Attributes</b>	None
<b>Description</b>	Interaction Server Proxy started with the option "-enable-tserver", which is no longer supported.
<b>Actions</b>	Change startup parameters
<b>Alarm Advisory</b>	None

**111-30127**

<b>Level</b>	TRACE
<b>Text</b>	Custom property '%s' is duplicated or uses name reserved for system properties.
<b>Attributes</b>	(1) Name of the interaction custom property
<b>Description</b>	Either there is already a mapping to the specified property or the name used for the property is reserved for system properties.

---

---

<b>Actions</b>	None
<b>Alarm Advisory</b>	None

**111-30128**

<b>Level</b>	TRACE
<b>Text</b>	Mapping custom property '%s' to '%s' (Tenant DBID=%d)
<b>Attributes</b>	(1) Name of the interaction custom property (2) Name of the database column (3) Tenant DBID
<b>Description</b>	The system has created a mapping between the specified custom property and the specified database column on the specified tenant.
<b>Actions</b>	None
<b>Alarm Advisory</b>	None

**111-30129**

<b>Level</b>	TRACE
<b>Text</b>	Custom property '%s' has been removed from tenant with DBID=%d
<b>Attributes</b>	(1) Name of the interaction custom property (2) Tenant DBID
<b>Description</b>	This custom property mapping has been removed from the specified tenant.
<b>Actions</b>	None
<b>Alarm Advisory</b>	None

## Release 8.5.107

## Added

**111-30100**

<b>Level</b>	TRACE
<b>Text</b>	Setting interactions cache size to %d.
<b>Attributes</b>	(1) new cache size
<b>Description</b>	The size of the interactions cache has been set to the specified value.

---



<b>Actions</b>	None
<b>Alarm Advisory</b>	None

**111-30102**

<b>Level</b>	TRACE
<b>Text</b>	Interaction Server '%s': 'media-types' option not found or empty. Accepting all media types
<b>Attributes</b>	(1) name of Interaction Server
<b>Description</b>	The option 'media-types' doesn't exist in the configuration, and proxy assumes server accepts all media types.
<b>Actions</b>	None
<b>Alarm Advisory</b>	None

**111-30103**

<b>Level</b>	TRACE
<b>Text</b>	Interaction Server '%s': supported medias: %s
<b>Attributes</b>	(1) Name of Interaction Server (2) list of supported medias
<b>Description</b>	Information about supported medias on interaction server (taken from media-types option).
<b>Actions</b>	None
<b>Alarm Advisory</b>	None

**111-30104**

<b>Level</b>	DEBUG
<b>Text</b>	Creating connection to '%s'
<b>Attributes</b>	(1) Name of Interaction Server
<b>Description</b>	Proxy has identified connection to Interaction Server and will try to use it.
<b>Actions</b>	None
<b>Alarm Advisory</b>	None

**111-30105**

<b>Level</b>	DEBUG
<b>Text</b>	Processing application cluster '%s' connections
<b>Attributes</b>	(1) Name of Application Cluster
<b>Description</b>	Proxy has identified connection to Application

---

---

	Cluster and will process its targets.
<b>Actions</b>	None
<b>Alarm Advisory</b>	None

**111-30106**

<b>Level</b>	STANDARD
<b>Text</b>	Found duplicated connection to '%s'. Resolve issue and restart proxy.
<b>Attributes</b>	(1) Name of Interaction Server
<b>Description</b>	Proxy is connected to the same server more than once (i.e. through Application Cluster).
<b>Actions</b>	Resolve issue in Configuration Server and restart the proxy.
<b>Alarm Advisory</b>	None

**111-30107**

<b>Level</b>	TRACE
<b>Text</b>	Connection to '%s' has been removed
<b>Attributes</b>	(1) Name of target connection
<b>Description</b>	The connection to the target has been removed from the configuration
<b>Actions</b>	None
<b>Alarm Advisory</b>	None

**111-30108**

<b>Level</b>	TRACE
<b>Text</b>	Can't send message '%s' because handler for client with id=%d doesn't exist
<b>Attributes</b>	(1) message name (2) proxy client id
<b>Description</b>	The message in question is for a client that no longer exists or never existed
<b>Actions</b>	None
<b>Alarm Advisory</b>	None

**111-30109**

<b>Level</b>	TRACE
--------------	-------

---

---

<b>Text</b>	Client '%s' is already connected to '%s'. Attempt aborted.
<b>Attributes</b>	(1) Client's name (2) Interaction Server's name
<b>Description</b>	Proxy was erroneously trying to connect client to a server that was already connected.
<b>Actions</b>	None
<b>Alarm Advisory</b>	None

**111-30110**

<b>Level</b>	TRACE
<b>Text</b>	There are no available servers able to accept message '%s'
<b>Attributes</b>	(1) message name
<b>Description</b>	Proxy couldn't find a proper target to send the message to
<b>Actions</b>	Check cluster settings (i.e. list of accepted media types per server, tenant assignment, and so on).
<b>Alarm Advisory</b>	None

**111-30111**

<b>Level</b>	STANDARD
<b>Text</b>	Found duplicated interaction with id '%s' on server '%s'.
<b>Attributes</b>	(1) Interaction id (2) Interaction Server's name
<b>Description</b>	The search request found the specified interaction on more than one server.
<b>Actions</b>	Investigate and take action depending on the situation. The situation may be as desired even though it prompts this message from the Proxy.
<b>Alarm Advisory</b>	None

**111-30112**

<b>Level</b>	TRACE
<b>Text</b>	Switching to subscriber-publisher server: '%s'
<b>Attributes</b>	(1) Interaction Server's name

---

<b>Description</b>	Proxy will be using the specified server for subscriber-publisher purposes
<b>Actions</b>	None
<b>Alarm Advisory</b>	None

**111-30113**

<b>Level</b>	STANDARD
<b>Text</b>	Detected proxy self connection. Ignoring.
<b>Attributes</b>	None
<b>Description</b>	Proxy is connected to itself and this connection is being ignored.
<b>Actions</b>	None
<b>Alarm Advisory</b>	None

**111-30114**

<b>Level</b>	STANDARD
<b>Text</b>	Proxy is not connected to any valid target. Port can not be opened!
<b>Attributes</b>	None
<b>Description</b>	There are no defined valid targets proxy can connect to.
<b>Actions</b>	Check list of proxy's connections in configuration.
<b>Alarm Advisory</b>	None

**111-30115**

<b>Level</b>	TRACE
<b>Text</b>	Interaction Server '%s': added tenant (DBID=%d)
<b>Attributes</b>	(1) Interaction Server's name (2) tenant's DBID
<b>Description</b>	Proxy detected a new tenant added to the tenants of the specified Interaction Server.
<b>Actions</b>	None
<b>Alarm Advisory</b>	None

**111-30116**

<b>Level</b>	TRACE
--------------	-------

---

---

<b>Text</b>	Interaction Server '%s': deleted tenant (DBID=%d)
<b>Attributes</b>	(1) Interaction Server's name (2) tenant's DBID
<b>Description</b>	Proxy detected a tenant deleted from the list of tenants of the specified Interaction Server.
<b>Actions</b>	None
<b>Alarm Advisory</b>	None

**111-30117**

<b>Level</b>	DEBUG
<b>Text</b>	Interaction Server '%s': supported tenants DBIDs: %s
<b>Attributes</b>	(1) Interaction Server's name (2) list of DBIDs of supported tenants
<b>Description</b>	A list of supported tenants per the specified connection.
<b>Actions</b>	None
<b>Alarm Advisory</b>	None

**111-30118**

<b>Level</b>	TRACE
<b>Text</b>	Interaction Server '%s': Media type '%s' became available
<b>Attributes</b>	(1) Interaction Server's name (2) media type name
<b>Description</b>	A new media type has become available on the specified server.
<b>Actions</b>	None
<b>Alarm Advisory</b>	None

**111-30119**

<b>Level</b>	TRACE
<b>Text</b>	Interaction Server '%s': Media type '%s' is no longer available
<b>Attributes</b>	(1) Interaction Server's name (2) media type name

---

<b>Description</b>	The specified media type is no longer available on the specified server.
<b>Actions</b>	None
<b>Alarm Advisory</b>	None

**111-30120**

<b>Level</b>	TRACE
<b>Text</b>	Media type '%s' has been added for tenant with id '%d' with state '%s'
<b>Attributes</b>	(1) media type name (2) tenant DBID (3) media type state
<b>Description</b>	This new media type has been added to the specified tenant.
<b>Actions</b>	None
<b>Alarm Advisory</b>	None

**111-30121**

<b>Level</b>	TRACE
<b>Text</b>	Media type '%s' has been removed from tenant with id '%d'
<b>Attributes</b>	(1) media type name (2) tenant DBID
<b>Description</b>	This media type has been removed from the tenant
<b>Actions</b>	None
<b>Alarm Advisory</b>	None

**111-30122**

<b>Level</b>	TRACE
<b>Text</b>	Media type '%s' has been enabled on tenant with id '%d'
<b>Attributes</b>	(1) media type name (2) tenant DBID
<b>Description</b>	Proxy detected that this media type was enabled on the specified tenant.
<b>Actions</b>	None
<b>Alarm Advisory</b>	None

---

**111-30123**

<b>Level</b>	TRACE
<b>Text</b>	Media type '%s' has been disabled on tenant with id '%d'
<b>Attributes</b>	(1) media type name (2) tenant DBID
<b>Description</b>	Proxy detected that this media type was disabled on the specified tenant.
<b>Actions</b>	None
<b>Alarm Advisory</b>	None

**111-30124**

<b>Level</b>	TRACE
<b>Text</b>	Interaction Server '%s': submit %s
<b>Attributes</b>	(1) Interaction Server's name (2) enabled/disabled
<b>Description</b>	Information about the specified server connection, based on the setting of the 'enable-submit' option.
<b>Actions</b>	None
<b>Alarm Advisory</b>	None

**111-30125**

<b>Level</b>	STANDARD
<b>Text</b>	Interaction Server '%s': minimal recommended version supporting all proxy's features is %s, while currently it's %s.
<b>Attributes</b>	(1) Interaction Server's name (2) required server version (3) current server version
<b>Description</b>	To get full support for all of the Proxy's features, the Proxy requires this minimum version of Interaction Server. If the requirement is not met the client may experience some unexpected behavior for some functionalities.
<b>Actions</b>	Upgrade Interaction Servers / downgrade proxy.
<b>Alarm Advisory</b>	None